

Package ‘RGraphSpace’

February 28, 2026

Type Package

Version 1.1.1

Title A Lightweight Interface Between 'igraph' and 'ggplot2' Graphics

Description Interface to integrate 'igraph' and 'ggplot2' graphics in a normalized coordinate system. 'RGraphSpace' implements new geometric objects using 'ggplot2' prototypes, customized for side-by-side visualization of multiple graphs. By scaling shapes and graph elements, 'RGraphSpace' helps to create layered visualizations that stay coherent across multiple graphs.

Depends R(>= 4.4), methods, ggplot2

Imports grDevices, scales, grid, igraph, rlang, lifecycle, patchwork, cowplot, gtable, ggrastr, circlize

Suggests knitr, rmarkdown, testthat

Enhances RedeR

License Artistic-2.0

VignetteBuilder knitr

URL <https://github.com/sysbiolab/RGraphSpace>

BugReports <https://github.com/sysbiolab/RGraphSpace/issues>

Collate gspaceChecks.R gspaceValidation.R gspaceConstructor.R
gspaceSupplements.R gspaceGeom.R gspaceClasses.R
gspaceGenerics.R gspaceMethods.R gspaceMisc.R

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation no

Author Victor Apolonio [ctb],
Vinicius Chagas [ctb],
Mauro Castro [aut, cre] (ORCID:
<<https://orcid.org/0000-0003-4942-8131>>)

Maintainer Mauro Castro <mauro.a.castro@gmail.com>

Repository CRAN

Date/Publication 2026-02-28 17:10:03 UTC

Contents

GeomEdgeSpace	2
GeomNodeSpace	3
geom_edgespace	4
geom_nodespace	6
getGraphSpace,GraphSpace-method	8
GraphSpace	9
GraphSpace-class	10
gs_nodes,GraphSpace-method	10
gtoys	12
make_gspace_legend	13
plot.GraphSpace	15
plotGraphSpace,GraphSpace-method	15
Index	18

GeomEdgeSpace	<i>GeomEdgeSpace: a ggplot2 prototype for GraphSpace-class methods</i>
---------------	--

Description

‘GeomEdgeSpace’ is the underlying ggproto object used by [geom_edgespace](#) to draw edge elements in a 2D graph layout, whose properties are controlled by aesthetics such as ‘colour’ and ‘linewidth’.

This ‘geom’ is designed for graph/network diagrams, where edge attributes are often already in their final form (e.g., hex colors). When used with identity scales, the appearance of edges can be fully controlled by the input data.

Usage

GeomEdgeSpace

Format

An object of class GeomEdgeSpace (inherits from Geom, ggproto, gg) of length 5.

Aesthetics

‘GeomEdgeSpace’ understands the following aesthetics:

- ‘x’ Starting horizontal position in ‘npc’ [unit](#) (required).
- ‘y’ Starting vertical position in ‘npc’ [unit](#) (required).
- ‘xend’ Ending horizontal position in ‘npc’ [unit](#) (required).
- ‘yend’ Ending vertical position in ‘npc’ [unit](#) (required).
- ‘colour’ Edge colour.
- ‘linewidth’ Edge width, using ‘lwd’ standard graphics unit (see [gpar](#)).

- 'linetype' Line type, using 'lty' standard graphics unit (see [gpar](#)).
- 'alpha' Transparency applied to the edge colour.

These aesthetics follow ggplot2's conventions for segment-like 'geoms'.

See Also

[geom_edgespace](#), [geom_segment](#)

GeomNodeSpace

GeomNodeSpace: a ggplot2 prototype for GraphSpace-class methods

Description

'GeomNodeSpace' is the underlying ggproto object used by [geom_nodespace](#) to draw node elements in a 2D graph layout. It produces point-like glyphs (typically circles) whose properties are controlled by aesthetics such as 'x', 'y', 'size' and 'colour'.

This geom is designed for graph/network diagrams, where node attributes are often already in their final form (e.g., hex colors). When used with identity scales, the appearance of nodes can be fully controlled by the input data.

Usage

```
GeomNodeSpace
```

Format

An object of class GeomNodeSpace (inherits from Geom, ggproto, gg) of length 5.

Aesthetics

'GeomNodeSpace' understands the following aesthetics:

- 'x' Horizontal position in 'npc' [unit](#) (required).
- 'y' Vertical position in 'npc' [unit](#) (required).
- 'size' Node size in 'npc' [unit](#) (required).
- 'fill' Node fill colour.
- 'colour' Node line colour.
- 'shape' Integer code between 0 and 25 (see [points](#)).
- 'linewidth' Line width, using 'lwd' standard graphics unit (see [gpar](#)).
- 'alpha' Transparency applied to fill and line colour.

These aesthetics follow ggplot2's conventions for point-like 'geoms'.

Drawing

The `draw_panel()` method transforms data into panel coordinates and constructs a `grid::pointsGrob()` for rendering. Node size is expected to be normalized to the range `[0, 1]`, so it can be interpreted in graph space using `'npc'` unit.

See Also

[geom_nodesspace](#), [geom_point](#)

geom_edgespace

Draw edge elements in a 2D graph layout

Description

Constructor for [GeomEdgeSpace](#) ggproto objects, a variant of [geom_segment](#) supporting edge attributes and bidirectional arrows.

This `'geom'` is designed to create edge-level aesthetics such as `'colour'` and `'linewidth'`, or any custom aesthetics defined in `'GeomEdgeSpace'`.

Usage

```
geom_edgespace(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  show.legend = NA,
  inherit.aes = FALSE,
  lineend = "butt",
  linejoin = "mitre",
  arrow_type = 0,
  arrow_size = 1,
  offset_start = 0,
  offset_end = 0
)
```

Arguments

mapping	Set of aesthetic mappings created by <code>[ggplot2::aes()]</code> . These mappings apply to the layer and may override global aesthetics.
data	Either a GraphSpace object or a data frame containing edge attributes. If <code>'NULL'</code> , the layer will use the default plot data.
stat	The statistical transformation to use on the data. Defaults to <code>"identity"</code> .
position	Position adjustment, either as a string or the result of a call to a position adjustment function.

...	Additional parameters passed to the underlying drawing function in 'GeomEdgeSpace'.
show.legend	Logical or a named logical vector indicating whether this layer should be included in legends.
inherit.aes	Logical. If 'FALSE' (default), the layer will use aesthetics defined in 'mapping'. Set to 'TRUE' if this geom should inherit aesthetics from the plot.
lineend	Line end style (round, butt, square).
linejoin	Line join style (round, mitre, bevel).
arrow_type	Arrowhead types (see 'drawing' section).
arrow_size	Numeric scaling factor controlling arrowhead geometry.
offset_start	Offset arrows as a fraction of graph space at start positions.
offset_end	Offset arrows as a fraction of graph space at end positions.

Details

Arrowhead size is a numeric scaling factor controlling arrowhead geometry. The value is interpreted in the same numeric space as line width ('lwd'), ensuring consistent scaling between edge strokes and arrowheads.

Arrowhead types can be specified using either integer or character codes:

- No arrow: 0 or "---"
- Forward arrow: 1 or "-->"
- Backward arrow: 2 or "<--"
- Bidirectional arrow: 3 or "<->"
- Forward arrow with backward bar: 4 or "|->"
- Forward bar: -1 or "--|"
- Backward bar: -2 or "|--"
- Bidirectional bar: -3 or "|-|"
- Backward arrow with forward bar: -4 or "<-|"

Value

A ggplot2 layer that renders edge segments defined by [GeomEdgeSpace](#).

Aesthetics

'geom_edgespace' understands the following aesthetics:

- 'x' Starting horizontal position in 'npc' [unit](#) (required).
- 'y' Starting vertical position in 'npc' [unit](#) (required).
- 'xend' Ending horizontal position in 'npc' [unit](#) (required).
- 'yend' Ending vertical position in 'npc' [unit](#) (required).
- 'colour' Edge colour.
- 'linewidth' Edge width, using 'lwd' standard graphics unit (see [gpar](#)).
- 'linetype' Line type, using 'lty' standard graphics unit (see [gpar](#)).
- 'alpha' Transparency applied to the edge colour.

See Also

[GeomEdgeSpace](#), [GraphSpace](#)

Examples

```
# Load a demo igraph
data('gtoy1', package = 'RGraphSpace')

# Create a GraphSpace object
gs <- GraphSpace(gtoy1)

## Not run:

ggplot() + geom_edgespace(aes(x = x, y = y, xend = xend, yend = yend),
  data = gs) + theme(aspect.ratio = 1) +
  scale_x_continuous(limits = c(0, 1)) +
  scale_y_continuous(limits = c(0, 1))

## End(Not run)
```

geom_nodesspace

Draw node elements in a 2D graph layout

Description

Constructor for [GeomNodeSpace](#) ggproto objects, a variant of [geom_point](#) supporting node attributes from [GraphSpace](#) objects.

This geom is designed to create node-level aesthetics such as 'size', 'fill', 'colour', or any custom aesthetics defined in 'GeomNodeSpace'.

Usage

```
geom_nodesspace(
  mapping = NULL,
  data = NULL,
  stat = "identity",
  position = "identity",
  ...,
  na.rm = TRUE,
  show.legend = NA,
  inherit.aes = FALSE
)
```

Arguments

mapping	Set of aesthetic mappings created by <code>[ggplot2::aes()]</code> . These mappings apply to the layer and may override global aesthetics.
data	Either a GraphSpace object or a data frame containing node attributes. If 'NULL', the layer will use the default plot data.
stat	The statistical transformation to use on the data. Defaults to "identity".
position	Position adjustment, either as a string or the result of a call to a position adjustment function.
...	Additional parameters passed to the underlying drawing function in 'GeomNodeSpace'.
na.rm	Logical. Should missing values be removed? Defaults to 'TRUE'.
show.legend	Logical or a named logical vector indicating whether this layer should be included in legends.
inherit.aes	Logical. If 'FALSE' (default), the layer will use aesthetics defined in 'mapping'. Set to 'TRUE' if this geom should inherit aesthetics from the plot.

Value

A ggplot2 layer that renders node glyphs defined by 'GeomNodeSpace'.

Aesthetics

'geom_nodesspace' understands the following aesthetics:

- 'x' Horizontal position in 'npc' [unit](#) (required).
- 'y' Vertical position in 'npc' [unit](#) (required).
- 'size' Node size in 'npc' [unit](#) (required).
- 'fill' Node fill colour.
- 'colour' Node line colour.
- 'shape' Integer code between 0 and 25 (see [points](#)).
- 'linewidth' Line width, using 'lwd' standard graphics unit (see [gpar](#)).
- 'alpha' Transparency applied to fill and line colour.

See Also

[GeomNodeSpace](#), [GraphSpace](#)

Examples

```
# Load a demo igraph
data('gtoy1', package = 'RGraphSpace')

# Create a GraphSpace object
gs <- GraphSpace(gtoy1)

## Not run:
```

```
ggplot() + geom_nodesspace(aes(x = x, y = y), data = gs)

## End(Not run)
```

getGraphSpace, GraphSpace-method

Accessors for fetching slots from a GraphSpace object

Description

getGraphSpace retrieves information from individual slots available in a GraphSpace object.

Usage

```
## S4 method for signature 'GraphSpace'
getGraphSpace(gs, what = "graph")
```

Arguments

gs	A preprocessed GraphSpace class object
what	A single character value specifying which information should be retrieved from the slots. Options: 'graph', 'gxy', 'gxyz', 'pars', 'misc', 'status', 'summits', 'summit_mask', and 'summit_contour'.

Value

Content from slots in the [GraphSpace](#) object.

Examples

```
# Load a demo igraph
data('gtoy1', package = 'RGraphSpace')

# Create a new GraphSpace object
gs <- GraphSpace(gtoy1)

# Get the 'summary' slot in gs
getGraphSpace(gs, what = 'graph')
```

GraphSpace*Constructor of GraphSpace-class objects*

Description

GraphSpace is a constructor of GraphSpace-class objects.

Usage

```
GraphSpace(g, mar = 0.1, layout = NULL, image = NULL, verbose = TRUE)
```

Arguments

<code>g</code>	An igraph object. It must include graph coordinates assigned to <code>x</code> and <code>y</code> vertex attributes, and vertex labels assigned to <code>name</code> vertex attribute.
<code>mar</code>	A single numeric value (in $[0, 1]$) indicating the size of the outer margins as a fraction of the graph space. Note: When an image is provided, <code>mar</code> is a fraction of image margins.
<code>layout</code>	An optional numeric matrix with two columns for <code>x</code> and <code>y</code> coordinates.
<code>image</code>	An optional background image. When provided, <code>x</code> and <code>y</code> coordinates must represent pixel positions in the image space.
<code>verbose</code>	A single logical value specifying to display detailed messages (when <code>verbose=TRUE</code>) or not (when <code>verbose=FALSE</code>).

Value

A [GraphSpace](#) class object.

Author(s)

Sysbiolab.

See Also

[plotGraphSpace](#)

Examples

```
# Load a demo igraph
data('gtoy1', package = 'RGraphSpace')

gs <- GraphSpace(gtoy1)
```

GraphSpace-class *GraphSpace: An S4 class for igraph objects*

Description

GraphSpace: An S4 class for igraph objects

Value

An S4 class object.

Slots

nodes A data frame with xy-vertex coordinates.
edges A data frame with edges.
graph An igraph object.
image A raster background image matrix.
pars A list with parameters.
misc A list with intermediate objects for downstream methods.

Constructor

see [GraphSpace](#) constructor.

gs_nodes, GraphSpace-method
Accessors for applying essential igraph methods to modify attributes of GraphSpace objects.

Description

Access and modify individual slots of a GraphSpace object. Selected 'igraph' methods are applied to the 'graph' slot and propagated to downstream components.

Usage

```
## S4 method for signature 'GraphSpace'
gs_nodes(x)

## S4 method for signature 'GraphSpace'
gs_edges(x)

## S4 method for signature 'GraphSpace'
gs_vcount(x)
```

```
## S4 method for signature 'GraphSpace'
gs_ecount(x)

## S4 method for signature 'GraphSpace'
names(x)

## S4 replacement method for signature 'GraphSpace'
names(x) <- value

## S4 method for signature 'GraphSpace'
gs_vertex_attr(x, name, ...)

## S4 replacement method for signature 'GraphSpace'
gs_vertex_attr(x, name, ...) <- value

## S4 method for signature 'GraphSpace'
gs_edge_attr(x, name, ...)

## S4 replacement method for signature 'GraphSpace'
gs_edge_attr(x, name, ...) <- value
```

Arguments

x	A GraphSpace class object
value	The new value of the attribute.
name	Name of the attribute.
...	Additional arguments passed to igraph methods.

Value

Updated [GraphSpace](#) object.

See Also

[vertex_attr](#), [edge_attr](#)

Examples

```
# Load a demo igraph
data('gtoy1', package = 'RGraphSpace')

# Create a new GraphSpace object
gs <- GraphSpace(gtoy1)

#--- Usage of GraphSpace attribute accessors:

# Get a data frame with nodes for plotting methods
gs_nodes(gs)
```

```
# Get a data frame with edges for plotting methods
gs_edges(gs)

# Get vertex count
gs_vcount(gs)

# Get edge count
gs_ecount(gs)

# Get vertex names
names(gs)

# Access all vertex attributes
gs_vertex_attr(gs)

# Access a specific vertex attribute
gs_vertex_attr(gs, "nodeLabel")

# Modify a single value within a vertex attribute
gs_vertex_attr(gs, "nodeSize")["n1"] <- 10

# Replace an entire vertex attribute
gs_vertex_attr(gs, "nodeSize") <- 10

# Alternative syntax using `` accessor
gs_vertex_attr(gs)$nodeSize <- 10

# Access a specific edge attribute
gs_edge_attr(gs, "edgeLineColor")

# Replace an entire edge attribute
gs_edge_attr(gs, "edgeLineWidth") <- 1

# Alternative syntax using `` for edge attributes
gs_edge_attr(gs)$edgeLineWidth <- 3
```

gtoys

Toy 'igraph' objects

Description

Small 'igraph' objects used for workflow demonstrations. All graphs include 'x', 'y', and 'name' vertex attributes.

Usage

```
data(gtoy1)
```

Format

igraph

Value

A pre-processed igraph object.

Source

This package.

Examples

```
data(gtoy1)
data(gtoy2)
```

make_gspace_legend *Create standalone legends for RGraphSpace's ggplot objects*

Description

This accessor builds a standalone legend from a named vector of colors. The resulting legend is returned as a 'grob' object that can be used to add external legends to existing ggplots.

Usage

```
make_gspace_legend(
  color_palette,
  breaks = NULL,
  legend_title = "Title",
  legend_shape = 21,
  legend_size = 6,
  text_size = 10,
  orientation = c("vertical", "horizontal"),
  justification = c("left", "right"),
  custom_theme = theme()
)

add_gspace_legend(
  plot,
  legend,
  spacer = unit(2, "mm"),
  position = c("right", "top", "bottom", "left")
)
```

Arguments

color_palette	A named character vector of colors. Names become legend labels. Values must be valid R color specifications, e.g. 'color_palette = c(A = "#FF0000", B = "blue")'.
breaks	A vector indicating numeric breaks for a continuous legend. If missing, 'color_palette' will instead produce a discrete legend.
legend_title	The legend title.
legend_shape	Point shape (default 21, for circle).
legend_size	Size of legend points (default 6 mm).
text_size	Text size (default 10 mm).
orientation	Legend arrangement ("vertical" or "horizontal").
justification	Legend justification within bounding box ("left" or "right").
custom_theme	An optional 'ggplot2' theme object applied to the legend panel. This allows customizing the appearance of the legend without affecting the main plot.
plot	A GraphSpace plot.
legend	A list with multiple 'gspace' legends.
spacer	A grid::unit() value specifying space inserted between merged legends.
position	Placement of legend relative to the main plot.

Details

The object returned by 'add_gspace_legend()' behaves like a ggplot for saving, combining with patchwork, arranging in grids, and rendering in standard graphics devices. Internally, however, the original ggplot is converted into a static 'grob' embedded inside a blank ggplot. As a result, the returned object cannot accept new layers, scales, or other ggplot modifications; it is no longer an editable ggplot, but a wrapped graphical representation of the composed figure.

Value

The 'make_gspace_legend()' function returns a standalone legend, while the 'add_gspace_legend()' function returns a patchwork object containing a plot combined with the generated legend in the specified position.

Examples

```
library(ggplot2)
library(patchwork)

p <- ggplot(mtcars, aes(wt, mpg)) + geom_point()

# Add a discrete standalone legend to a plot
leg1 <- make_gspace_legend(c(A="red", B="blue"), legend_size = 5)
p + leg1 + plot_layout(widths = c(1, 0.1))

# Add a continuous standalone legend to a plot
leg2 <- make_gspace_legend(c("blue", "white", "red"), breaks = c(0, 1, 2))
```

```
p + leg2 + plot_layout(widths = c(1, 0.1))

# Add a legend list to a plot
legs <- list(leg1, leg2)
add_gspace_legend(plot = p, legs, position = "right")
```

plot.GraphSpace *Plot GraphSpace objects*

Description

Plot GraphSpace objects

Usage

```
## S3 method for class 'GraphSpace'
plot(x, ...)
```

Arguments

x A [GraphSpace](#) class object.
 ... Additional arguments passed to the [plotGraphSpace](#) function.

See Also

[plotGraphSpace](#)

plotGraphSpace, GraphSpace-method
Plotting igraph objects with RGraphSpace

Description

plotGraphSpace is a wrapper function to create dedicated ggplot graphics for igraph- and GraphSpace-class objects.

Usage

```
## S4 method for signature 'GraphSpace'
plotGraphSpace(
  gs,
  theme = c("th0", "th1", "th2", "th3"),
  xlab = "Graph coordinates 1",
  ylab = "Graph coordinates 2",
  font.size = 1,
```

```

    bg.color = "grey95",
    add.labels = FALSE,
    node.labels = NULL,
    label.size = 3,
    label.color = "grey20",
    add.image = FALSE,
    raster = FALSE,
    dpi = 300,
    dev = "cairo_png"
  )

  ## S4 method for signature 'igraph'
  plotGraphSpace(gs, ..., mar = 0.1)

```

Arguments

<code>gs</code>	Either an <code>igraph</code> or <code>GraphSpace</code> class object. If <code>gs</code> is an <code>igraph</code> , then it must include <code>x</code> , <code>y</code> , and <code>name</code> vertex attributes (see <code>GraphSpace</code>).
<code>theme</code>	Name of a custom <code>RGraphSpace</code> theme. These themes (from <code>'th1'</code> to <code>'th3'</code>) consist of preconfigured <code>ggplot</code> settings, which the user can subsequently refine using <code>ggplot2</code> .
<code>xlab</code>	The title for the <code>'x'</code> axis of a 2D-image space.
<code>ylab</code>	The title for the <code>'y'</code> axis of a 2D-image space.
<code>font.size</code>	A single numeric value passed to <code>ggplot</code> themes.
<code>bg.color</code>	A single color for background.
<code>add.labels</code>	A logical value indicating whether to plot vertex labels.
<code>node.labels</code>	A vector of vertex names to be highlighted in the graph space. This argument overrides <code>'add.labels'</code> .
<code>label.size</code>	A size argument passed to <code>geom_text</code> .
<code>label.color</code>	A color passed to <code>geom_text</code> .
<code>add.image</code>	A logical value indicating whether to add a background image, when one is available (see <code>GraphSpace</code>).
<code>raster</code>	A logical value indicating whether to rasterize the main plot. See <code>rasterise</code> for further specifications.
<code>dpi</code>	Raster resolution, in dots per inch.
<code>dev</code>	Device used in the <code>rasterise</code> call.
<code>...</code>	Additional arguments passed to the <code>plotGraphSpace</code> function.
<code>mar</code>	A single numeric value (in $[0, 1]$) indicating the size of the outer margins as a fraction of the graph space.

Value

A `ggplot`-class object.

Author(s)

Sysbiolab.

See Also

[GraphSpace](#)

Examples

```
# Load a demo igraph
data('gtoy1', package = 'RGraphSpace')

# Generate a ggplot for igraph
plotGraphSpace(gtoy1)

# Create a GraphSpace object
gs <- GraphSpace(gtoy1)

# Generate a ggplot for gs
plotGraphSpace(gs)
```

Index

- * **datasets**
 - GeomEdgeSpace, [2](#)
 - GeomNodeSpace, [3](#)
- * **gtoys**
 - gtoys, [12](#)
- add_gspace_legend (make_gspace_legend), [13](#)
- edge_attr, [11](#)
- geom_edgespace, [2](#), [3](#), [4](#)
- geom_nodespace, [3](#), [4](#), [6](#)
- geom_point, [4](#), [6](#)
- geom_segment, [3](#), [4](#)
- geom_text, [16](#)
- GeomEdgeSpace, [2](#), [4–6](#)
- GeomNodeSpace, [3](#), [6](#), [7](#)
- getGraphSpace
 - (getGraphSpace, GraphSpace-method), [8](#)
- getGraphSpace, GraphSpace-method, [8](#)
- ggplot2, [16](#)
- gpar, [2](#), [3](#), [5](#), [7](#)
- GraphSpace, [4](#), [6–9](#), [9](#), [10](#), [11](#), [15–17](#)
- GraphSpace-class, [10](#)
- gs_ccount (gs_nodes, GraphSpace-method), [10](#)
- gs_ccount, GraphSpace-method
 - (gs_nodes, GraphSpace-method), [10](#)
- gs_edge_attr
 - (gs_nodes, GraphSpace-method), [10](#)
- gs_edge_attr, GraphSpace-method
 - (gs_nodes, GraphSpace-method), [10](#)
- gs_edge_attr<-
 - (gs_nodes, GraphSpace-method), [10](#)
- gs_edge_attr<-, GraphSpace-method
 - (gs_nodes, GraphSpace-method), [10](#)
- gs_edges (gs_nodes, GraphSpace-method), [10](#)
- gs_edges, GraphSpace-method
 - (gs_nodes, GraphSpace-method), [10](#)
- gs_nodes (gs_nodes, GraphSpace-method), [10](#)
- gs_nodes, GraphSpace-method, [10](#)
- gs_vcount (gs_nodes, GraphSpace-method), [10](#)
- gs_vcount, GraphSpace-method
 - (gs_nodes, GraphSpace-method), [10](#)
- gs_vertex_attr
 - (gs_nodes, GraphSpace-method), [10](#)
- gs_vertex_attr, GraphSpace-method
 - (gs_nodes, GraphSpace-method), [10](#)
- gs_vertex_attr<-
 - (gs_nodes, GraphSpace-method), [10](#)
- gs_vertex_attr<-, GraphSpace-method
 - (gs_nodes, GraphSpace-method), [10](#)
- gtoy1 (gtoys), [12](#)
- gtoy2 (gtoys), [12](#)
- gtoys, [12](#)
- igraph, [9](#)
- make_gspace_legend, [13](#)
- names (gs_nodes, GraphSpace-method), [10](#)
- names, GraphSpace-method
 - (gs_nodes, GraphSpace-method), [10](#)

names<- (gs_nodes, GraphSpace-method), [10](#)
names<- , GraphSpace-method
 (gs_nodes, GraphSpace-method),
 [10](#)

plot.GraphSpace, [15](#)
plotGraphSpace, [9](#), [15](#), [16](#)
plotGraphSpace
 (plotGraphSpace, GraphSpace-method),
 [15](#)
plotGraphSpace, GraphSpace-method, [15](#)
plotGraphSpace, igraph-method
 (plotGraphSpace, GraphSpace-method),
 [15](#)
points, [3](#), [7](#)

rasterise, [16](#)

unit, [2](#), [3](#), [5](#), [7](#)

vertex_attr, [11](#)