

Package ‘actuaRE’

February 27, 2026

Type Package

Title Handling Single-Level and Hierarchically Structured Risk Factors using Credibility and Random Effects Models

Version 1.0.0

Description Fits random effects models for multi-level/high-cardinality factors using credibility theory (Buhlmann-Straub for single-level, Jewell for hierarchical structures), GLM extensions following Ohlsson (2008) <[doi:10.1080/03461230701878612](https://doi.org/10.1080/03461230701878612)>, or Tweedie generalized linear mixed models. Provides functions for model fitting, visualization, and prediction. See Campo, B.D.C. and Antonio, K. (2023) <[doi:10.1080/03461238.2022.2161413](https://doi.org/10.1080/03461238.2022.2161413)>.

License GPL (>= 3)

Depends R (>= 3.5.0), stats, methods, cplm

Imports statmod, nlme, lme4, magrittr, data.table, ggplot2, reformulas

Suggests plyr, knitr, bookdown, insuranceData, actuar, utils, lattice, minqa, rmarkdown, dplyr

LazyData true

Encoding UTF-8

RoxygenNote 7.3.3

VignetteBuilder knitr

Config/testthat/edition 3

URL <https://bavodc.github.io/websiteactuaRE/>

NeedsCompilation no

Author Campo Bavo D.C. [aut, cre]

Maintainer Campo Bavo D.C. <bavo.decock@kuleuven.be>

Repository CRAN

Date/Publication 2026-02-27 18:22:13 UTC

Contents

actuaRE-package	3
.addREs	4
adjustIntercept	4
BalanceProperty	5
buhlmannStraub	6
buhlmannStraubGLM	7
buhlmannStraubTweedie	10
dataCar	12
findbars	13
fixef	14
fixef-actuaRE	15
hachemeisterLong	16
hierCredGLM	17
hierCredGLM-class	19
hierCredibility	20
hierCredibility-class	22
hierCredTweedie	23
hierCredTweedie-class	26
is.formula	27
isNested	28
modular	28
nobars	31
NrUnique	32
plotRE	33
predict.buhlmannStraub	34
predict.buhlmannStraubGLM	35
predict.buhlmannStraubTweedie	36
predict.hierCredGLM	38
predict.hierCredibility	39
predict.hierCredTweedie	39
print.BalanceProperty	40
ranef	41
ranef-actuaRE	41
simulatedclustereddata	42
tweedieGLMM	44
weights-actuaRE	45
Index	47

actuaRE-package

Handling Single-Level and Hierarchically Structured Risk Factors using Credibility and Random Effects Models

Description

Fits random effects models for multi-level/high-cardinality factors using credibility theory (Buhlmann-Straub for single-level, Jewell for hierarchical structures), GLM extensions following Ohlsson (2008) <doi:10.1080/03461230701878612>, or Tweedie generalized linear mixed models. Provides functions for model fitting, visualization, and prediction. See Campo, B.D.C. and Antonio, K. (2023) <doi:10.1080/03461238.2022.2161413>.

References

- Campo, B.D.C. and Antonio, Katrien (2023). Insurance pricing with hierarchically structured data an illustration with a workers' compensation insurance portfolio. *Scandinavian Actuarial Journal*, doi: 10.1080/03461238.2022.2161413
- Dannenburg, D. R., Kaas, R. and Goovaerts, M. J. (1996). *Practical actuarial credibility models*. Amsterdam: IAE (Institute of Actuarial Science and Econometrics of the University of Amsterdam).
- Jewell, W. S. (1975). *The use of collateral data in credibility theory: a hierarchical model*. Laxenburg: IIASA.
- Ohlsson, E. (2005). Simplified estimation of structure parameters in hierarchical credibility. *Presented at the Zurich ASTIN Colloquium*.
- Ohlsson, E. (2008). Combining generalized linear models and credibility models in practice. *Scandinavian Actuarial Journal* **2008**(4), 301–314.

See Also

[buhlmannStraub](#) [buhlmannStraubGLM](#) [buhlmannStraubTweedie](#) [hierCredibility](#) [hierCredGLM](#) [hierCredTweedie](#) [tweedieGLMM](#) [BalanceProperty](#)

Examples

```
library(actuaRE)
# Vignette of the package
vignette(package = "actuaRE")

# Load data
data(hachemeisterLong)
data(dataCar)

# Hierarchical credibility model of Jewell
fit = hierCredibility(ratio, weight, cohort, state, hachemeisterLong)

# Combination of the hierarchical credibility model with a GLM (Ohlsson, 2008)
fit = hierCredGLM(Y ~ area + (1 | VehicleType / VehicleBody), dataCar, weights = w,
p = 1.7)
```

<code>.addREs</code>	<i>Add random effects to the data frame</i>
----------------------	---

Description

Internal function

Usage

```
.addREs(obj, newdata)
```

Arguments

<code>obj</code>	object with model fit
<code>newdata</code>	an object coercible to <code>data.table</code> .

<code>adjustIntercept</code>	<i>Adjust the intercept to regain the balance property</i>
------------------------------	--

Description

This function updates the intercept term of the model fit such that the balance property is satisfied.

Usage

```
adjustIntercept(obj, data)
```

Arguments

<code>obj</code>	an object of type <code>glm</code> , <code>cpglm</code> or <code>cpglm</code> containing the model fit.
<code>data</code>	a <code>data.frame</code> or <code>data.table</code> object that was used to fit the model.

Value

The object with the adjusted (fixed effects) coefficients.

References

Campo, B.D.C. and Antonio, Katrien (2023). Insurance pricing with hierarchically structured data an illustration with a workers' compensation insurance portfolio. *Scandinavian Actuarial Journal*, doi: 10.1080/03461238.2022.2161413

Wüthrich, M. V. (2020). Bias regularization in neural network models for general insurance pricing. *European actuarial journal* **10**(1), 179–202.

Examples

```

library(statmod)
datas = dataCar[1:1e3, ]
Fit = glm(Y ~ area + gender, data = datas, weights = datas$w, family = tweedie(1.75, 0),
model = TRUE, control = glm.control(epsilon = 1e-4, maxit = 5e2))
w = weights(Fit, "prior")
y = Fit$y
sum(w * y) == sum(w * fitted(Fit))
adjFit = adjustIntercept(Fit, datas)
coef(adjFit)
sum(w * y) == sum(w * fitted(adjFit))

```

BalanceProperty	<i>Balance property</i>
-----------------	-------------------------

Description

Function to assess whether the balance property holds

Usage

```
BalanceProperty(obj)
```

Arguments

obj an object containing the model fit

Value

a list with the slots call (the original call), BalanceProperty (logical indicating whether the balance property is satisfied) and Alpha (Ratio total observed damage to total predicted damage).

References

Campo, B.D.C. and Antonio, Katrien (2023). Insurance pricing with hierarchically structured data an illustration with a workers' compensation insurance portfolio. *Scandinavian Actuarial Journal*, doi: 10.1080/03461238.2022.2161413

Wüthrich, M. V. (2020). Bias regularization in neural network models for general insurance pricing. *European actuarial journal* **10**(1), 179–202.

Examples

```

fit = hierCredGLM(Y ~ area + (1 | VehicleType / VehicleBody), dataCar, weights = w,
p = 1.75, epsilon = 1e-6)
BalanceProperty(fit)

```

buhlmannStraub	<i>Buhlmann-Straub credibility model</i>
----------------	--

Description

Fit a credibility model using the Buhlmann-Straub model.

Usage

```
buhlmannStraub(
  Yijt,
  wijt,
  MLFj,
  data,
  muHat = NULL,
  type = c("additive", "multiplicative"),
  returnData = FALSE
)
```

Arguments

Yijt	variable name of the response variable.
wijt	variable name of the exposure weight.
MLFj	variable name of the risk class or cluster.
data	an object that is coercible by <code>as.data.table</code> , containing the variables in the model.
muHat	estimate for the collective premium (portfolio mean). Default is NULL and in this case, the credibility-weighted estimator is used.
type	specifies whether the additive or multiplicative formulation of the credibility model is used. Default is additive.
returnData	Logical, indicates whether the data object has to be returned. Default is FALSE.

Value

An object of type `buhlmannStraub` with the following slots:

call	the matched call
type	Whether additive or multiplicative credibility model is used.
Variances	The estimated variance components. Sigma is the estimated within-group variance, and Tau is the estimate of the between-group variance.
Means	The estimated averages at the portfolio level (collective premium $\hat{\mu}$) and at the cluster level (weighted average \bar{Y}_j).
Weights	The total weights w_j for each cluster.
Credibility	The credibility factors z_j for each cluster.

Premiums	The collective premium $\hat{\mu}$ and individual premiums \hat{V}_j for each cluster.
Relativity	The estimated random effects \hat{U}_j of each cluster.
RawResults	Object of type <code>data.table</code> with all intermediate results.
<code>fitted.values</code>	the fitted mean values, resulting from the model fit.

References

Buhlmann, H. and Straub, E. (1970). Glaubwürdigkeit für Schadensätze. *Mitteilungen der Vereinigung schweizerischer Versicherungsmathematiker*, 70, 111-133.

Buhlmann, H. and Gisler, A. (2005). *A Course in Credibility Theory and its Applications*. Springer.

See Also

[buhlmannStraub-class](#), [plotRE](#), [buhlmannStraubGLM](#), [buhlmannStraubTweedie](#), [tweedieGLMM](#), [adjustIntercept](#), [BalanceProperty](#)

Examples

```
library(actuar)
library(actuaRE)
data("hachemeister", package = "actuar")
# Prepare data
X = as.data.frame(hachemeister)
Df = reshape(X, idvar = "state",
             varying = list(paste0("ratio.", 1:12), paste0("weight.", 1:12)),
             direction = "long")
# Fit Buhlmann-Straub model
fitBS = buhlmannStraub(ratio.1, weight.1, state, Df)
summary(fitBS)
# Compare with actuar package
fit <- cm(~state, hachemeister, ratios = ratio.1:ratio.12,
         weights = weight.1:weight.12)
summary(fit)
```

buhlmannStraubGLM	<i>Combining the Buhlmann-Straub credibility model with a GLM (Ohlsson, 2008)</i>
-------------------	---

Description

Fit a single-level random effects model using Ohlsson's methodology combined with Buhlmann-Straub credibility. This is the single-level analogue of [hierCredGLM](#).

Usage

```

buhlmannStraubGLM(
  formula,
  data,
  weights,
  p = 1.5,
  link.power = 0,
  muHatGLM = FALSE,
  epsilon = 1e-04,
  maxiter = 500,
  maxiterGLM = 500,
  verbose = FALSE,
  returnData = TRUE,
  balanceProperty = TRUE,
  y = TRUE,
  ...
)

```

Arguments

formula	object of type <code>formula</code> that specifies which model should be fitted. Syntax follows <code>lmer</code> : e.g., $Y \sim x_1 + x_2 + (1 \mid \text{Cluster})$. Only one random effect is allowed.
data	an object that is coercible by <code>as.data.table</code> , containing the variables in the model.
weights	variable name of the exposure weight.
p	the value for the power parameter of the Tweedie distribution, which is passed to <code>tweedie</code> . Default is 1.5.
link.power	index of power link function, which is passed to <code>tweedie</code> . <code>link.power = 0</code> produces a log-link. Defaults to the canonical link, which is $1 - p$.
muHatGLM	indicates which estimate has to be used in the algorithm for the intercept term. Default is TRUE, which uses the intercept as estimated by the GLM. If FALSE, the estimate of the Buhlmann-Straub credibility model is used.
epsilon	positive convergence tolerance ϵ ; the iterations converge when $\ \theta[k] - \theta[k - 1]\ _2^2 / \ \theta[k - 1]\ _2^2 < \epsilon$. Here, $\theta[k]$ is the parameter vector at the k^{th} iteration.
maxiter	maximum number of iterations.
maxiterGLM	maximum number of iterations when fitting the GLM part. Passed to <code>glm</code> .
verbose	logical indicating if output should be produced during the algorithm.
returnData	logical indicating if input data has to be returned.
balanceProperty	logical indicating if the balance property should be satisfied.
y	logical indicating whether the response vector should be returned as a component of the returned value.
...	arguments passed to <code>glm</code>

Value

An object of type `buhlmannStraubGLM` with the following slots:

<code>call</code>	the matched call
<code>CredibilityResults</code>	results of the Buhlmann-Straub credibility model.
<code>fitGLM</code>	the results from fitting the GLM part.
<code>iter</code>	total number of iterations.
<code>Converged</code>	logical indicating whether the algorithm converged.
<code>LevelsCov</code>	object that summarizes the unique levels of each of the contract-specific covariates.
<code>fitted.values</code>	the fitted mean values, resulting from the model fit.
<code>prior.weights</code>	the weights (exposure) initially supplied.
<code>y</code>	if requested, the response vector. Default is TRUE.

References

Campo, B.D.C. and Antonio, Katrien (2023). Insurance pricing with hierarchically structured data an illustration with a workers' compensation insurance portfolio. *Scandinavian Actuarial Journal*, doi: 10.1080/03461238.2022.2161413

Ohlsson, E. (2008). Combining generalized linear models and credibility models in practice. *Scandinavian Actuarial Journal* **2008**(4), 301–314.

See Also

[buhlmannStraubGLM-class](#), [buhlmannStraubTweedie](#), [buhlmannStraub](#), [plotRE](#), [adjustIntercept](#), [BalanceProperty](#), [tweedieGLMM](#)

Examples

```
data("hachemeister", package = "actuar")
# Prepare data
X = as.data.frame(hachemeister)
Df = reshape(X, idvar = "state",
             varying = list(paste0("ratio.", 1:12), paste0("weight.", 1:12)),
             direction = "long")
# Add a covariate
Df$time_factor = factor(Df$time)
# Fit model
fit = buhlmannStraubGLM(ratio.1 ~ time_factor + (1 | state), Df,
                       weights = weight.1, p = 1.5)
summary(fit)
ranef(fit)
```

buhlmannStraubTweedie *Combining the Buhlmann-Straub credibility model with a Tweedie GLM (Ohlsson, 2008)*

Description

Fit a single-level random effects model using Ohlsson's methodology combined with Buhlmann-Straub credibility. This function estimates the power parameter p . For fixed p , see [buhlmannStraubGLM](#).

Usage

```
buhlmannStraubTweedie(
  formula,
  data,
  weights,
  muHatGLM = FALSE,
  epsilon = 1e-04,
  maxiter = 500,
  verbose = FALSE,
  returnData = TRUE,
  cpglmControl = list(bound.p = c(1.01, 1.99)),
  balanceProperty = TRUE,
  optimizer = "bobyqa",
  y = TRUE,
  ...
)
```

Arguments

formula	object of type formula that specifies which model should be fitted. Syntax follows lmer : e.g., $Y \sim x_1 + x_2 + (1 \mid \text{Cluster})$. Only one random effect is allowed.
data	an object that is coercible by as.data.table , containing the variables in the model.
weights	variable name of the exposure weight.
muHatGLM	indicates which estimate has to be used in the algorithm for the intercept term. Default is TRUE, which uses the intercept as estimated by the GLM. If FALSE, the estimate of the Buhlmann-Straub credibility model is used.
epsilon	positive convergence tolerance ϵ ; the iterations converge when $\ \theta[k] - \theta[k - 1]\ _2^2 / \ \theta[k - 1]\ _2^2 < \epsilon$. Here, $\theta[k]$ is the parameter vector at the k^{th} iteration.
maxiter	maximum number of iterations.
verbose	logical indicating if output should be produced during the algorithm.
returnData	logical indicating if input data has to be returned.

<code>cpglmControl</code>	a list of parameters to control the fitting process in the GLM part. By default, <code>cpglmControl = list(bound.p = c(1.01, 1.99))</code> which restricts the range of the power parameter <code>p</code> to <code>[1.01, 1.99]</code> in the fitting process. This list is passed to <code>cpglm</code> .
<code>balanceProperty</code>	logical indicating if the balance property should be satisfied.
<code>optimizer</code>	a character string that determines which optimization routine is to be used in estimating the index and the dispersion parameters. Possible choices are "nlminb" (the default, see <code>nlminb</code>), "bobyqa" (<code>bobyqa</code>) and "L-BFGS-B" (<code>optim</code>).
<code>y</code>	logical indicating whether the response vector should be returned as a component of the returned value.
<code>...</code>	arguments passed to <code>cpglm</code> .

Details

When estimating the GLM part, this function uses the `cpglm` function from the `cp1m` package.

Value

An object of type `buhlmannStraubTweedie` with the following slots:

<code>call</code>	the matched call
<code>CredibilityResults</code>	results of the Buhlmann-Straub credibility model.
<code>fitGLM</code>	the results from fitting the GLM part.
<code>iter</code>	total number of iterations.
<code>Converged</code>	logical indicating whether the algorithm converged.
<code>LevelsCov</code>	object that summarizes the unique levels of each of the contract-specific covariates.
<code>fitted.values</code>	the fitted mean values, resulting from the model fit.
<code>prior.weights</code>	the weights (exposure) initially supplied.
<code>y</code>	if requested, the response vector. Default is TRUE.

References

- Campo, B.D.C. and Antonio, Katrien (2023). Insurance pricing with hierarchically structured data an illustration with a workers' compensation insurance portfolio. *Scandinavian Actuarial Journal*, doi: 10.1080/03461238.2022.2161413
- Ohlsson, E. (2008). Combining generalized linear models and credibility models in practice. *Scandinavian Actuarial Journal* **2008**(4), 301–314.

See Also

[buhlmannStraubTweedie-class](#), [buhlmannStraub](#), [buhlmannStraubGLM](#), [hierCredTweedie](#), [cpglm](#), [plotRE](#), [adjustIntercept](#), [BalanceProperty](#)

Examples

```

data("hachemeister", package = "actuar")
X = as.data.frame(hachemeister)
Df = reshape(X, idvar = "state",
             varying = list(paste0("ratio.", 1:12), paste0("weight.", 1:12)),
             direction = "long")
Df$time_factor = factor(Df$time)
fit = buhlmannStraubTweedie(ratio.1 ~ time_factor + (1 | state), Df,
                           weights = weight.1, epsilon = 1e-6)

summary(fit)
ranef(fit)
fixef(fit)

```

dataCar

data Car

Description

This data set is taken from the [dataCar](#) data set of the insuranceData package and slightly adjusted (see the code in examples for reproducing this data set). The original data set is based on one-year vehicle insurance policies taken out in 2004 or 2005. There are 67566 policies, of which 4589 (6.8%) had at least one claim.

Usage

```
data(dataCar)
```

Format

A data frame with 67566 observations on the following 15 variables.

veh_value vehicle value, in \$10,000s

exposure 0-1

clm occurrence of claim (0 = no, 1 = yes)

numclaims number of claims

claimcst0 claim amount (0 if no claim)

veh_body vehicle body, coded as BUS CONV T COUPE HBACK HDTOP MCARA MIBUS PANVN RDSTR SEDAN
STNWG TRUCK UTE

veh_age 1 (youngest), 2, 3, 4

gender a factor with levels F M

area a factor with levels A B C D E F

agecat 1 (youngest), 2, 3, 4, 5, 6

X_OBSTAT_ a factor with levels 01101 0 0 0

Y the loss ratio, defined as the number of claims divided by the exposure

w the exposure, identical to exposure
 VehicleType type of vehicle, common vehicle or uncommon vehicle
 VehicleBody vehicle body, identical to veh_body

Details

Adjusted data set dataCar, where we removed claims with a loss ratio larger than 1 000 000. In addition, we summed the exposure per vehicle body and removed those where the summed exposure was less than 100. Hereby, we ensure that there is sufficient exposure for each vehicle body category.

Source

<http://www.acst.mq.edu.au/GLMsforInsuranceData>

References

De Jong P., Heller G.Z. (2008), Generalized linear models for insurance data, Cambridge University Press

Examples

```
# How to construct the data set using the original dataCar data set from the insuranceData package
library(plyr)
library(magrittr)
data("dataCar", package = "insuranceData")
dataCar$Y = with(dataCar, claimst0 / exposure)
dataCar$w = dataCar$exposure
dataCar = dataCar[which(dataCar$Y < 1e6), ]
Yw = ddply(dataCar, .(veh_body), function(x) c(crossprod(x$Y, x$w) / sum(x$w), sum(x$w)))
dataCar = dataCar[!dataCar$veh_body %in% Yw[Yw$V2 < 1e2, "veh_body"], ]
dataCar$veh_body %<>% droplevels()
dataCar$VehicleType = sapply(tolower(dataCar$veh_body), function(x) {
  if(x %in% c("sedan", "ute", "hback"))
    "Common vehicle"
  else
    "Uncommon vehicle"
})
dataCar$VehicleBody = dataCar$veh_body
```

findbars

Determine random-effects expressions from a formula

Description

From the right hand side of a formula for a mixed-effects model, determine the pairs of expressions that are separated by the vertical bar operator. Also expand the slash operator in grouping factor expressions and expand terms with the double vertical bar operator into separate, independent random effect terms.

Usage

```
findbars(term)
```

Arguments

term a mixed-model formula

Value

pairs of expressions that were separated by vertical bars

Note

This function is called recursively on individual terms in the model, which is why the argument is called `term` and not a name like `form`, indicating a formula.

See Also

[formula](#), [model.frame](#), [model.matrix](#).

Other utilities: [mkRespMod](#), [mkReTrms](#), [nlformula](#), [nobars](#), [subbars](#)

Examples

```
findbars(f1 <- Reaction ~ Days + (Days | Subject))
## => list( Days | Subject )
## These two are equivalent:% tests in ../inst/tests/test-doubleVertNotation.R
findbars(y ~ Days + (1 | Subject) + (0 + Days | Subject))
findbars(y ~ Days + (Days || Subject))
## => list of length 2: list ( 1 | Subject , 0 + Days | Subject)
findbars(~ 1 + (1 | batch / cask))
## => list of length 2: list ( 1 | cask:batch , 1 | batch)
```

fixef

Extract fixed-effects estimates

Description

Extract the fixed-effects estimates

Arguments

object any fitted model object from which fixed effects estimates can be extracted.

Details

Extract the estimates of the fixed-effects parameters from a fitted model.

Value

a named, numeric vector of fixed-effects estimates.

Examples

```
library(lme4)
fixef(lmer(Reaction ~ Days + (1|Subject) + (0+Days|Subject), sleepstudy))
fm2 <- lmer(Reaction ~ Days + Days2 + (1|Subject),
           data=transform(sleepstudy,Days2=Days))
fixef(fm2,add.dropped=TRUE)
## first two parameters are the same ...
stopifnot(all.equal(fixef(fm2,add.dropped=TRUE)[1:2],
                    fixef(fm2)))
```

fixef-actuaRE

Extract the fixed-effects estimates from a fitted random effects model

Description

A generic function to extract the fixed effects (i.e. the company-specific effects) estimates from a fitted random effects model.

Usage

```
## S3 method for class 'hierCredGLM'
fixef(object, ...)

## S3 method for class 'hierCredTweedie'
fixef(object, ...)

## S3 method for class 'buhlmannStraubGLM'
fixef(object, ...)

## S3 method for class 'buhlmannStraubTweedie'
fixef(object, ...)
```

Arguments

object an object of type [hierCredGLM](#) or [hierCredTweedie](#)
... ignored.

Value

a named, numeric vector of fixed-effects estimates.

Examples

```
fit = hierCredGLM(Y ~ area + (1 | VehicleType / VehicleBody), dataCar,  
weights = w, p = 1.75, epsilon = 1e-6)  
fixef(fit)
```

hachemeisterLong *Hachemeister Data Set*

Description

Long format of the Hachemeister (1975) data set giving average claim amounts in private passenger bodily injury insurance. We have data of five U.S. states over 12 quarters between July 1970 and June 1973 and we have the corresponding number of claims. To obtain a hierarchical structure, we created an artificial variable cohort. With this, we created a hierarchical multi-level factor, with cohort as the first hierarchical level and state as the second hierarchical level, nested within cohort.

Usage

```
hachemeisterLong
```

Format

A data.frame with 60 rows and the following 5 columns:

cohort artificially created variable;

state the state number;

time time variable (quarter of the observation);

ratio the average claim amount;

weight the corresponding number of claims.

Source

Hachemeister, C. A. (1975), *Credibility for regression models with application to trend*, Proceedings of the Berkeley Actuarial Research Conference on Credibility, Academic Press.

hierCredGLM	<i>Combining the hierarchical credibility model with a GLM (Ohlsson, 2008)</i>
-------------	--

Description

Fit a random effects model using Ohlsson's methodology. In this function you explicitly specify the power parameter p . See [hierCredTweedie](#) when you also want to estimate the p .

Usage

```
hierCredGLM(
  formula,
  data,
  weights,
  p = 1.5,
  link.power = 0,
  muHatGLM = TRUE,
  epsilon = 1e-04,
  maxiter = 500,
  maxiterGLM = 500,
  verbose = FALSE,
  returnData = TRUE,
  balanceProperty = TRUE,
  y = TRUE,
  ...
)
```

Arguments

formula	object of type formula that specifies which model should be fitted. Syntax is the same as for lmer and glmer . For example, $Y_{ijkt} \sim x_1 + x_2 + (1 \text{Industry} / \text{Branch})$.
data	an object that is coercible by as.data.table , containing the variables in the model.
weights	variable name of the exposure weight.
p	the value for the power parameter of the Tweedie distribution, which is passed to tweedie . Default is 1.5.
link.power	index of power link function, which is passed to tweedie . <code>link.power = 0</code> produces a log-link. Defaults to the canonical link, which is $1 - p$.
muHatGLM	indicates which estimate has to be used in the algorithm for the intercept term. Default is TRUE, which used the intercept as estimated by the GLM. If FALSE, the estimate of the hierarchical credibility model is used.
epsilon	positive convergence tolerance ϵ ; the iterations converge when $7 \ \theta[k] - \theta[k - 1]\ ^2[[2]] / \ \theta[k - 1]\ ^2[[2]] < \epsilon$. Here, $\theta[k]$ is the parameter vector at the k^{th} iteration.

maxiter	maximum number of iterations.
maxiterGLM	maximum number of iterations when fitting the GLM part. Passed to glm.
verbose	logical indicating if output should be produced during the algorithm.
returnData	logical indicating if input data has to be returned.
balanceProperty	logical indicating if the balance property should be satisfied.
y	logical indicating whether the response vector should be returned as a component of the returned value.
...	arguments passed to glm

Value

An object of type hierCredGLM with the following slots:

call	the matched call
HierarchicalResults	results of the hierarchical credibility model.
fitGLM	the results from fitting the GLM part.
iter	total number of iterations.
Converged	logical indicating whether the algorithm converged.
LevelsCov	object that summarizes the unique levels of each of the contract-specific covariates.
fitted.values	the fitted mean values, resulting from the model fit.
prior.weights	the weights (exposure) initially supplied.
y	if requested, the response vector. Default is TRUE.

References

- Campo, B.D.C. and Antonio, Katrien (2023). Insurance pricing with hierarchically structured data an illustration with a workers' compensation insurance portfolio. *Scandinavian Actuarial Journal*, doi: 10.1080/03461238.2022.2161413
- Ohlsson, E. (2008). Combining generalized linear models and credibility models in practice. *Scandinavian Actuarial Journal* **2008**(4), 301–314.

See Also

[hierCredGLM-class](#), [fitted.hierCredGLM](#), [predict.hierCredGLM](#), [ranef-actuaRE](#), [weights-actuaRE](#), [hierCredibility](#), [hierCredTweedie](#), [plotRE](#), [adjustIntercept](#), [BalanceProperty](#)

Examples

```
data("tweedietraindata")
fit = hierCredGLM(y ~ x1 + (1 | cluster / subcluster), tweedietraindata, weights = wt,
p = 1.7)
fit
summary(fit)
```

```
ranef(fit)
fixef(fit)
```

```
hierCredGLM-class      Class "hierCredGLM" of fitted random effects models estimated with
                        Ohlsson's GLMC algorithm
```

Description

Class "hierCredGLM" of fitted random effects models estimated with Ohlsson's GLMC algorithm

Usage

```
## S3 method for class 'hierCredGLM'
print(x, ...)

## S3 method for class 'hierCredGLM'
summary(object, ...)

## S3 method for class 'hierCredGLM'
fitted(object, ...)
```

Arguments

x	an object of class hierCredGLM
...	currently ignored.
object	an object of class hierCredGLM

Value

The function [hierCredGLM](#) returns an object of class `hierCredGLM`, which has the following slots:

call	the matched call
HierarchicalResults	results of the hierarchical credibility model.
fitGLM	the results from fitting the GLM part.
iter	total number of iterations.
Converged	logical indicating whether the algorithm converged.
LevelsCov	object that summarizes the unique levels of each of the contract-specific covariates.
fitted.values	the fitted mean values, resulting from the model fit.
prior.weights	the weights (exposure) initially supplied.
y	if requested, the response vector. Default is TRUE.

S3 methods

print: Prints the call, the estimated variance parameters, the unique number of categories of the hierarchical MLF and the output of the GLM part. The ... argument is currently ignored. Returns an invisible copy of the original object.

summary: In addition to the output of the `print.hierCredGLM` function, the `summary` function also prints the random effect estimates and a summary of the GLM (see `summary.glm`). Returns an invisible copy of the original object.

fitted: Returns the fitted values.

See Also

[hierCredGLM](#)

hierCredibility

Hierarchical credibility model of Jewell

Description

Fit a random effects model, without contract-specific risk factors, using the hierarchical credibility model of Jewell.

Usage

```
hierCredibility(
  Yijkt,
  wijkt,
  sector,
  group,
  data,
  muHat = NULL,
  type = c("additive", "multiplicative"),
  returnData = FALSE
)
```

Arguments

<code>Yijkt</code>	variable name of the response variable (the loss cost within actuarial applications).
<code>wijkt</code>	variable name of the exposure weight.
<code>sector</code>	variable name of the first hierarchical level.
<code>group</code>	variable name of the second hierarchical level that is nested within the first hierarchical level.
<code>data</code>	an object that is coercible by <code>as.data.table</code> , containing the variables in the model.

muHat	estimate for the intercept term. Default is NULL and in this case, the estimator as given in Ohlsson (2005) is used.
type	specifies whether the additive (Dannenburg, 1996) or multiplicative (Ohlsson, 2005) formulation of the hierarchical credibility model is used. Default is additive.
returnData	Logical, indicates whether the data object has to be returned. Default is FALSE.

Value

An object of type hierCredibility with the following slots:

call	the matched call
type	Whether additive or multiplicative hierarchical credibility model is used.
Variances	The estimated variance components. s2 is the estimated variance of the individual contracts, tausq the estimate of $Var(V[j])$ and nusq is the estimate of $Var(V[jk])$.
Means	The estimated averages at the portfolio level (intercept term μ), at the first hierarchical level ($\bar{Y}[\%j\%]\%z$) and at the second hierarchical level ($\bar{Y}[\%jk\%]$).
Weights	The weights at the first hierarchical level $z[j\%]$ and at the second hierarchical level $w[\%jk\%]$.
Credibility	The credibility weights at the first hierarchical level $q[j\%]$ and at the second hierarchical level $z[jk]$.
Premiums	The overall expectation $\widehat{\mu}$, sector expectation $\widehat{V}[j]$ and group expectation $\widehat{V}[jk]$.
Relativity	The estimated random effects $\widehat{U}[j]$ and $\widehat{U}[jk]$ of the sector and group, respectively.
RawResults	Objects of type data.table with all intermediate results.
fitted.values	the fitted mean values, resulting from the model fit.

References

Campo, B.D.C. and Antonio, Katrien (2023). Insurance pricing with hierarchically structured data an illustration with a workers' compensation insurance portfolio. *Scandinavian Actuarial Journal*, doi: 10.1080/03461238.2022.2161413

Dannenburg, D. R., Kaas, R. and Goovaerts, M. J. (1996). *Practical actuarial credibility models*. Amsterdam: IAE (Institute of Actuarial Science and Econometrics of the University of Amsterdam).

Jewell, W. S. (1975). *The use of collateral data in credibility theory: a hierarchical model*. Laxenburg: IIASA.

Ohlsson, E. (2005). Simplified estimation of structure parameters in hierarchical credibility. *Presented at the Zurich ASTIN Colloquium*.

See Also

[hierCredibility-class](#), [hierCredTweedie](#), [hierCredGLM](#), [cpglm](#), [plotRE](#)

Examples

```

library(actuar)
library(actuaRE)
data("hachemeister", package = "actuar")
Df = as.data.frame(hachemeister)
X = as.data.frame(cbind(cohort = c(1, 2, 1, 2, 2), hachemeister))
Df = reshape(X, idvar = "state", varying = list(paste0("ratio.", 1:12),
  paste0("weight.", 1:12)), direction = "long")
fitActuar = cm(~ cohort + cohort:state, data = X, ratios = ratio.1:ratio.12,
weights = weight.1:weight.12, method = "Ohlsson")
fitActuaRE = hierCredibility(ratio.1, weight.1, cohort, state, Df)
summary(fitActuar)
summary(fitActuaRE)

```

hierCredibility-class *Class "hierCredibility" of fitted hierarchical credibility models*

Description

Class "hierCredibility" of fitted hierarchical credibility models

Usage

```

## S3 method for class 'hierCredibility'
print(x, ...)

## S3 method for class 'hierCredibility'
summary(object, ...)

## S3 method for class 'hierCredibility'
fitted(object, ...)

```

Arguments

x	an object of class hierCredibility
...	currently ignored.
object	an object of class hierCredibility

Value

The function [hierCredibility](#) returns an object of class [hierCredibility](#), which has the following slots:

call	the matched call
type	Whether additive or multiplicative hierarchical credibility model is used.

Variances	The estimated variance components. s_2 is the estimated variance of the individual contracts, τ_{ausq} the estimate of $Var(V[j])$ and nusq is the estimate of $Var(V[jk])$.
Means	The estimated averages at the portfolio level (intercept term μ), at the first hierarchical level ($\text{bar}(Y)[\%.\%j\%.\%\%.\%]^z$) and at the second hierarchical level ($\text{bar}(Y)[\%.\%jk\%.\%\%]$).
Weights	The weights at the first hierarchical level $z[j\%.\%]$ and at the second hierarchical level $w[\%.\%jk\%.\%\%]$.
Credibility	The credibility weights at the first hierarchical level $q[j\%.\%]$ and at the second hierarchical level $z[jk]$.
Premiums	The overall expectation $\widehat{\mu}$, sector expectation $\widehat{V}[j]$ and group expectation $\widehat{V}[jk]$.
Relativity	The estimated random effects $\widehat{U}[j]$ and $\widehat{U}[jk]$ of the sector and group, respectively.
RawResults	Objects of type <code>data.table</code> with all intermediate results.
fitted.values	the fitted mean values, resulting from the model fit.

S3 methods

- `print`: Prints the call, the estimated variance parameters and the unique number of categories of the hierarchical MLF. The `...` argument is currently ignored. Returns an invisible copy of the original object.
- `summary`: In addition to the output of the `print.hierCredibility` function, the `summary` function prints the random effect estimates as well. Returns an invisible copy of the original object.
- `fitted`: Returns the fitted values.

See Also

[hierCredibility](#)

hierCredTweedie	<i>Combining the hierarchical credibility model with a GLM (Ohlsson, 2008)</i>
-----------------	--

Description

Fit a random effects model using Ohlsson's methodology. In this function you estimate the power parameter p . See `hierCredGLM` when you want fix p .

Usage

```

hierCredTweedie(
  formula,
  data,
  weights,
  muHatGLM = TRUE,
  epsilon = 1e-04,
  maxiter = 500,
  verbose = FALSE,
  returnData = TRUE,
  cpglmControl = list(bound.p = c(1.01, 1.99)),
  balanceProperty = TRUE,
  optimizer = "bobyqa",
  y = TRUE,
  ...
)

```

Arguments

formula	object of type formula that specifies which model should be fitted. Syntax is the same as for lmer and glmer . For example, $Y_{ijkt} \sim x_1 + x_2 + (1 \text{Industry} / \text{Branch})$.
data	an object that is coercible by as.data.table , containing the variables in the model.
weights	variable name of the exposure weight.
muHatGLM	indicates which estimate has to be used in the algorithm for the intercept term. Default is TRUE, which used the intercept as estimated by the GLM. If FALSE, the estimate of the hierarchical credibility model is used.
epsilon	positive convergence tolerance ϵ ; the iterations converge when $\ \theta[k] - \theta[k - 1]\ ^2[[2]] / \ \theta[k - 1]\ ^2[[2]] < \epsilon$. Here, $\theta[k]$ is the parameter vector at the k^{th} iteration.
maxiter	maximum number of iterations.
verbose	logical indicating if output should be produced during the algorithm.
returnData	logical indicating if input data has to be returned.
cpglmControl	a list of parameters to control the fitting process in the GLM part. By default, <code>cpglmControl = list(bound.p = c(1.01, 1.99))</code> which restricts the range of the power parameter p to $[1.01, 1.99]$ in the fitting process. This list is passed to cpglm .
balanceProperty	logical indicating if the balance property should be satisfied.
optimizer	a character string that determines which optimization routine is to be used in estimating the index and the dispersion parameters. Possible choices are "nlminb" (the default, see nlminb), "bobyqa" (bobyqa) and "L-BFGS-B" (optim).
y	logical indicating whether the response vector should be returned as a component of the returned value.
...	arguments passed to cpglm .

Details

When estimating the GLM part, this function uses the `cpglm` function from the `cplm` package.

Value

An object of type `hierCredTweedie` with the following slots:

<code>call</code>	the matched call
<code>HierarchicalResults</code>	results of the hierarchical credibility model.
<code>fitGLM</code>	the results from fitting the GLM part.
<code>iter</code>	total number of iterations.
<code>Converged</code>	logical indicating whether the algorithm converged.
<code>LevelsCov</code>	object that summarizes the unique levels of each of the contract-specific covariates.
<code>fitted.values</code>	the fitted mean values, resulting from the model fit.
<code>prior.weights</code>	the weights (exposure) initially supplied.
<code>y</code>	if requested, the response vector. Default is TRUE.

References

Campo, B.D.C. and Antonio, Katrien (2023). Insurance pricing with hierarchically structured data an illustration with a workers' compensation insurance portfolio. *Scandinavian Actuarial Journal*, doi: 10.1080/03461238.2022.2161413

Ohlsson, E. (2008). Combining generalized linear models and credibility models in practice. *Scandinavian Actuarial Journal* **2008**(4), 301–314.

See Also

[hierCredTweedie-class](#), [hierCredibility](#), [hierCredGLM](#), [cpglm](#), [plotRE](#), [adjustIntercept](#), [BalanceProperty](#)

Examples

```
data("tweedietraindata")
fit = hierCredTweedie(y ~ x1 + (1 | cluster / subcluster), tweedietraindata, weights = wt,
p = 1.7)
fit
summary(fit)
ranef(fit)
fixef(fit)
```

hierCredTweedie-class *Class "hierCredTweedie" of fitted random effects models estimated with Ohlsson's GLMC algorithm*

Description

Class "hierCredTweedie" of fitted random effects models estimated with Ohlsson's GLMC algorithm

Usage

```
## S3 method for class 'hierCredTweedie'
print(x, ...)

## S3 method for class 'hierCredTweedie'
summary(object, ...)

## S3 method for class 'hierCredTweedie'
fitted(object, ...)
```

Arguments

x an object of class [hierCredTweedie](#)
 ... currently ignored.
 object an object of class [hierCredTweedie](#)

Value

The function [hierCredGLM](#) returns an object of class `hierCredGLM`, which has the following slots:

call	the matched call
HierarchicalResults	results of the hierarchical credibility model.
fitGLM	the results from fitting the GLM part.
iter	total number of iterations.
Converged	logical indicating whether the algorithm converged.
LevelsCov	object that summarizes the unique levels of each of the contract-specific covariates.
fitted.values	the fitted mean values, resulting from the model fit.
prior.weights	the weights (exposure) initially supplied.
y	if requested, the response vector. Default is TRUE.

S3 methods

print: Prints the call, the estimated variance parameters, the unique number of categories of the hierarchical MLF and the output of the GLM part. The ... argument is currently ignored. Returns an invisible copy of the original object.

summary: In addition to the output of the print.hierCredTweedie function, the summary function also prints the random effect estimates and a summary of the GLM (see [summary.glm](#)). Returns an invisible copy of the original object.

fitted: Returns the fitted values.

See Also

[hierCredTweedie](#)

is.formula

Formula

Description

Checks if the object is of the type formula

Usage

```
is.formula(x)
```

Arguments

x the object.

Value

logical indicating if the object is a formula or not.

Examples

```
f = formula(y ~ x)
is.formula(f)
```

isNested	<i>Is f1 nested within f2?</i>
----------	--------------------------------

Description

Does every level of f1 occur in conjunction with exactly one level of f2? The function is based on converting a triplet sparse matrix to a compressed column-oriented form in which the nesting can be quickly evaluated.

Usage

```
isNested(f1, f2)
```

Arguments

f1	factor 1
f2	factor 2

Value

TRUE if factor 1 is nested within factor 2

Examples

```
library(lme4)
with(Pastes, isNested(cask, batch)) ## => FALSE
with(Pastes, isNested(sample, batch)) ## => TRUE
```

modular	<i>Modular Functions for Mixed Model Fits</i>
---------	---

Description

Modular functions for mixed model fits

Usage

```
glFormula(formula, data = NULL, family = gaussian,
           subset, weights, na.action, offset, contrasts = NULL,
           start, mustart, etastart, control = glmerControl(), ...)
```

Arguments

formula	a two-sided linear formula object describing both the fixed-effects and random-effects parts of the model, with the response on the left of a <code>~</code> operator and the terms, separated by <code>+</code> operators, on the right. Random-effects terms are distinguished by vertical bars (" <code> </code> ") separating expressions for design matrices from grouping factors.
data	an optional data frame containing the variables named in formula. By default the variables are taken from the environment from which <code>lmer</code> is called. While data is optional, the package authors <i>strongly</i> recommend its use, especially when later applying methods such as <code>update</code> and <code>drop1</code> to the fitted model (<i>such methods are not guaranteed to work properly if data is omitted</i>). If data is omitted, variables will be taken from the environment of formula (if specified as a formula) or from the parent frame (if specified as a character vector).
subset	an optional expression indicating the subset of the rows of data that should be used in the fit. This can be a logical vector, or a numeric vector indicating which observation numbers are to be included, or a character vector of the row names to be included. All observations are included by default.
weights	an optional vector of ‘prior weights’ to be used in the fitting process. Should be <code>NULL</code> or a numeric vector.
na.action	a function that indicates what should happen when the data contain NAs. The default action (<code>na.omit</code> , inherited from the ‘factory fresh’ value of <code>getOption("na.action")</code>) strips any observations with any missing values in any variables.
offset	this can be used to specify an <i>a priori</i> known component to be included in the linear predictor during fitting. This should be <code>NULL</code> or a numeric vector of length equal to the number of cases. One or more <code>offset</code> terms can be included in the formula instead or as well, and if more than one is specified their sum is used. See <code>model.offset</code> .
contrasts	an optional <code>list</code> . See the <code>contrasts.arg</code> of <code>model.matrix.default</code> .
control	a list giving for <code>[g]lFormula</code> : all options for running the model, see <code>lmerControl</code> ; for <code>mkLmerDevfun</code> , <code>mkGlmDevfun</code> : options for the inner optimization step; for <code>optimizeLmer</code> and <code>optimizeGlm</code> : control parameters for nonlinear optimizer (typically inherited from the <code>...</code> argument to <code>lmerControl</code>).
start	starting values (see <code>lmer</code> ; for <code>glFormula</code> , should be just a numeric vector of fixed-effect coefficients)
family	a GLM family; see <code>glm</code> and <code>family</code> .
mustart	optional starting values on the scale of the conditional mean; see <code>glm</code> for details.
etastart	optional starting values on the scale of the unbounded predictor; see <code>glm</code> for details.
...	other potential arguments; for <code>optimizeLmer</code> and <code>optimizeGlm</code> , these are passed to internal function <code>optwrap</code> , which has relevant parameters <code>calc.derivs</code> and <code>use.last.params</code> (see <code>lmerControl</code>).

Details

These functions make up the internal components of an `[gn]lmer` fit.

- `[g]lFormula` takes the arguments that would normally be passed to `[g]lmer`, checking for errors and processing the formula and data input to create a list of objects required to fit a mixed model.
- `mk(Gl|L)merDevfun` takes the output of the previous step (minus the formula component) and creates a deviance function
- `optimize(Gl|L)mer` takes a deviance function and optimizes over theta (or over theta and beta, if `stage` is set to 2 for `optimizeGlmer`)
- `updateGlmerDevfun` takes the first stage of a GLMM optimization (with `nAGQ=0`, optimizing over theta only) and produces a second-stage deviance function
- `mkMerMod` takes the *environment* of a deviance function, the results of an optimization, a list of random-effect terms, a model frame, and a model all and produces a `[g]lmerMod` object.

Value

`lFormula` and `glFormula` return a list containing components:

fr model frame

X fixed-effect design matrix

reTrms list containing information on random effects structure: result of `mkReTrms`

`mkLmerDevfun` and `mkGlmerDevfun` return a function to calculate deviance (or restricted deviance) as a function of the theta (random-effect) parameters. `updateGlmerDevfun` returns a function to calculate the deviance as a function of a concatenation of theta and beta (fixed-effect) parameters. These deviance functions have an environment containing objects required for their evaluation. CAUTION: The *environment* of functions returned by `mk(Gl|L)merDevfun` contains reference class objects (see `ReferenceClasses`, `merPredD-class`, `lmResp-class`), which behave in ways that may surprise many users. For example, if the output of `mk(Gl|L)merDevfun` is naively copied, then modifications to the original will also appear in the copy (and vice versa). To avoid this behavior one must make a deep copy (see `ReferenceClasses` for details).

`optimizeLmer` and `optimizeGlmer` return the results of an optimization.

Examples

```
library(lme4)
### Fitting a linear mixed model in 4 modularized steps

## 1. Parse the data and formula:
lmod <- lFormula(Reaction ~ Days + (Days|Subject), sleepstudy)
names(lmod)
## 2. Create the deviance function to be optimized:
(devfun <- do.call(mkLmerDevfun, lmod))
ls(environment(devfun)) # the environment of 'devfun' contains objects
# required for its evaluation
## 3. Optimize the deviance function:
opt <- optimizeLmer(devfun)
```

```

opt[1:3]
## 4. Package up the results:
mkMerMod(environment(devfun), opt, lmod$reTrms, fr = lmod$fr)

### Same model in one line
lmer(Reaction ~ Days + (Days|Subject), sleepstudy)

### Fitting a generalized linear mixed model in six modularized steps

## 1. Parse the data and formula:
glmod <- glFormula(cbind(incidence, size - incidence) ~ period + (1 | herd),
                  data = cbpp, family = binomial)
#... see what've got :
str(glmod, max=1, give.attr=FALSE)
## 2. Create the deviance function for optimizing over theta:
(devfun <- do.call(mkGlmerDevfun, glmod))
ls(environment(devfun)) # the environment of devfun contains lots of info
## 3. Optimize over theta using a rough approximation (i.e. nAGQ = 0):
(opt <- optimizeGlmer(devfun))
## 4. Update the deviance function for optimizing over theta and beta:
(devfun <- updateGlmerDevfun(devfun, glmod$reTrms))
## 5. Optimize over theta and beta:
opt <- optimizeGlmer(devfun, stage=2)
str(opt, max=1) # seeing what we've got
## 6. Package up the results:
(fMod <- mkMerMod(environment(devfun), opt, glmod$reTrms, fr = glmod$fr))

### Same model in one line
fM <- glmer(cbind(incidence, size - incidence) ~ period + (1 | herd),
            data = cbpp, family = binomial)
all.equal(fMod, fM, check.attributes=FALSE, tolerance = 1e-12)
# ---- -- even tolerance = 0 may work

```

nobars

Omit terms separated by vertical bars in a formula

Description

Remove the random-effects terms from a mixed-effects formula, thereby producing the fixed-effects formula.

Usage

```
nobars(term)
```

Arguments

term the right-hand side of a mixed-model formula

Value

the fixed-effects part of the formula

Note

This function is called recursively on individual terms in the model, which is why the argument is called `term` and not a name like `form`, indicating a formula.

See Also

[formula](#), [model.frame](#), [model.matrix](#).

Other utilities: [findbars](#), [mkRespMod](#), [mkReTrms](#), [nlformula](#), [subbars](#)

Examples

```
nobars(Reaction ~ Days + (Days|Subject)) ## => Reaction ~ Days
```

NrUnique

Number of unique elements in a vector

Description

Number of unique elements in a vector

Usage

```
NrUnique(x, na.rm = TRUE)
```

Arguments

`x` object of type vector.

`na.rm` logical indicating if missing values have to be removed. Default to TRUE.

Value

vector with the number of unique elements

Examples

```
set.seed(1)
x = sample(letters, 50, TRUE)
NrUnique(x)
```

Description

Using this function, you can create plots of the random effect estimates from fitted random effects models. To make the plots, we rely on the [ggplot2](#) package.

Usage

```
plotRE(  
  obj,  
  levelRE = c("all", "first", "second"),  
  colour = "black",  
  plot = TRUE  
)
```

Arguments

obj	an object of type hierCredibility , hierCredGLM , hierCredTweedie , buhlmannStraub , buhlmannStraubGLM or buhlmannStraubTweedie
levelRE	indicates which hierarchical level has to be used. "all" plots both levels in the hierarchy, "first" the first level in the hierarchy and "second" the second level. For buhlmannStraub objects, this parameter is ignored.
colour	colour for geom_point
plot	logical indicating if the ggplot objects have to be plotted.

Value

a list with [ggplot](#) objects.

Examples

```
data("tweedietraindata")  
fithGLM <- hierCredGLM(y ~ x1 + (1 | cluster / subcluster), tweedietraindata, weights = wt)  
plotRE(fithGLM)
```

predict.buhlmannStraub

Class "buhlmannStraub" of fitted Buhlmann-Straub credibility models

Description

Class "buhlmannStraub" of fitted Buhlmann-Straub credibility models

Usage

```
## S3 method for class 'buhlmannStraub'
predict(object, newdata = NULL, ...)

## S3 method for class 'buhlmannStraub'
print(x, ...)

## S3 method for class 'buhlmannStraub'
summary(object, ...)

## S3 method for class 'buhlmannStraub'
fitted(object, ...)
```

Arguments

object	an object of class <code>buhlmannStraub</code>
newdata	optionally, a data frame in which to look for variables with which to predict.
...	currently ignored.
x	an object of class <code>buhlmannStraub</code>

Value

The function `buhlmannStraub` returns an object of class `buhlmannStraub`, which has the following slots:

call	the matched call
type	Whether additive or multiplicative credibility model is used.
Variances	The estimated variance components. Sigma is the estimated within-group variance, and Tau is the estimate of the between-group variance.
Means	The estimated averages at the portfolio level (collective premium $\hat{\mu}$) and at the cluster level (weighted average \hat{Y}_j).
Weights	The total weights w_j for each cluster.
Credibility	The credibility factors z_j for each cluster.
Premiums	The collective premium $\hat{\mu}$ and individual premiums \hat{V}_j for each cluster.
Relativity	The estimated random effects \hat{U}_j of each cluster.
RawResults	Object of type <code>data.table</code> with all intermediate results.
fitted.values	the fitted mean values, resulting from the model fit.

S3 methods

print: Prints the call, the estimated variance parameters and the unique number of clusters. The ... argument is currently ignored. Returns an invisible copy of the original object.

summary: In addition to the output of the print.buhlmannStraub function, the summary function prints the cluster-level estimates as well. Returns an invisible copy of the original object.

fitted: Returns the fitted values.

See Also

[buhlmannStraub](#)

predict.buhlmannStraubGLM

Class "buhlmannStraubGLM" of fitted Buhlmann-Straub GLM credibility models

Description

Class "buhlmannStraubGLM" of fitted Buhlmann-Straub GLM credibility models

Usage

```
## S3 method for class 'buhlmannStraubGLM'
predict(object, newdata = NULL, ...)
```

```
## S3 method for class 'buhlmannStraubGLM'
print(x, ...)
```

```
## S3 method for class 'buhlmannStraubGLM'
summary(object, ...)
```

```
## S3 method for class 'buhlmannStraubGLM'
fitted(object, ...)
```

Arguments

object	an object of class buhlmannStraubGLM
newdata	optionally, a data frame in which to look for variables with which to predict.
...	currently ignored.
x	an object of class buhlmannStraubGLM

Value

The function `buhlmannStraubGLM` returns an object of class `buhlmannStraubGLM`, which has the following slots:

<code>call</code>	the matched call
<code>CredibilityResults</code>	results of the Buhlmann-Straub credibility model.
<code>fitGLM</code>	the results from fitting the GLM part.
<code>iter</code>	total number of iterations.
<code>Converged</code>	logical indicating whether the algorithm converged.
<code>LevelsCov</code>	object that summarizes the unique levels of each of the contract-specific covariates.
<code>fitted.values</code>	the fitted mean values, resulting from the model fit.
<code>prior.weights</code>	the weights (exposure) initially supplied.
<code>y</code>	if requested, the response vector.

S3 methods

`print`: Prints the call, convergence status, number of iterations, and GLM summary. The ... argument is currently ignored. Returns an invisible copy of the original object.

`summary`: In addition to the output of the `print.buhlmannStraubGLM` function, the `summary` function prints the credibility results and random effect estimates as well. Returns an invisible copy of the original object.

`fitted`: Returns the fitted values.

`predict`: Predict method for new data.

`ranef`: Returns the random effects (cluster relativities).

`fixef`: Returns the fixed effects coefficients.

`weights`: Returns either credibility weights or exposure weights.

See Also

[buhlmannStraubGLM](#)

`predict.buhlmannStraubTweedie`

Class "buhlmannStraubTweedie" of fitted Buhlmann-Straub GLM credibility models

Description

Class "buhlmannStraubTweedie" of fitted Buhlmann-Straub GLM credibility models

Usage

```
## S3 method for class 'buhlmannStraubTweedie'
predict(object, newdata = NULL, ...)

## S3 method for class 'buhlmannStraubTweedie'
print(x, ...)

## S3 method for class 'buhlmannStraubTweedie'
summary(object, ...)

## S3 method for class 'buhlmannStraubTweedie'
fitted(object, ...)
```

Arguments

object	an object of class <code>buhlmannStraubTweedie</code>
newdata	optionally, a data frame in which to look for variables with which to predict.
...	currently ignored.
x	an object of class <code>buhlmannStraubTweedie</code>

Value

The function `buhlmannStraubTweedie` returns an object of class `buhlmannStraubTweedie`, which has the following slots:

call	the matched call
CredibilityResults	results of the Buhlmann-Straub credibility model.
fitGLM	the results from fitting the GLM part.
iter	total number of iterations.
Converged	logical indicating whether the algorithm converged.
LevelsCov	object that summarizes the unique levels of each of the contract-specific covariates.
fitted.values	the fitted mean values, resulting from the model fit.
prior.weights	the weights (exposure) initially supplied.
y	if requested, the response vector.

S3 methods

print: Prints the call, convergence status, number of iterations, and GLM summary. The ... argument is currently ignored. Returns an invisible copy of the original object.

summary: In addition to the output of the `print.buhlmannStraubTweedie` function, the `summary` function prints the credibility results and random effect estimates as well. Returns an invisible copy of the original object.

fitted: Returns the fitted values.

predict: Predict method for new data.
ranef: Returns the random effects (cluster relativities).
fixef: Returns the fixed effects coefficients.
weights: Returns either credibility weights or exposure weights.

See Also

[buhlmannStraubTweedie](#)

predict.hierCredGLM *Model predictions*

Description

Obtain predictions based on the model fit with hierCredGLM

Usage

```
## S3 method for class 'hierCredGLM'  
predict(object, newdata = NULL, ...)
```

Arguments

object	a model object for which prediction is desired.
newdata	optionally, a data frame in which to look for variables with which to predict. If omitted, the fitted values are used.
...	arguments passed to glm

Details

The random effects are taken into account by specifying these as an offset in the predict.glm function.

Value

If newdata is omitted the predictions are based on the data used for the fit.

See Also

[hierCredGLM](#)

predict.hierCredibility
Model predictions

Description

Obtain predictions based on a model fit with hierCredibility

Usage

```
## S3 method for class 'hierCredibility'  
predict(object, newdata = NULL, ...)
```

Arguments

object	a model object for which prediction is desired.
newdata	optionally, a data frame in which to look for variables with which to predict. If omitted, the fitted values are used.
...	ignored.

Value

If newdata is omitted the predictions are based on the data used for the fit.

See Also

[hierCredibility](#)

predict.hierCredTweedie
Model predictions

Description

Obtain predictions based on the model fit with hierCredTweedie

Usage

```
## S3 method for class 'hierCredTweedie'  
predict(object, newdata = NULL, ...)
```

Arguments

object	a model object for which prediction is desired.
newdata	optionally, a data frame in which to look for variables with which to predict. If omitted, the fitted values are used.
...	arguments passed to cpglm

Details

The random effects are taken into account by specifying these as an offset in the `predict.cpglm` function.

Value

If `newdata` is omitted the predictions are based on the data used for the fit.

See Also

[hierCredTweedie](#)

`print.BalanceProperty` *Print method for an object of class BalanceProperty*

Description

Print method for an object of class `BalanceProperty`

Usage

```
## S3 method for class 'BalanceProperty'  
print(x, ...)
```

Arguments

<code>x</code>	an object of type <code>BalanceProperty</code>
<code>...</code>	Currently ignored.

Value

Prints the call and whether the balance property is satisfied or not. Returns an invisible copy of the original object.

See Also

[BalanceProperty](#)

ranef	<i>Extract the modes of the random effects</i>
-------	--

Description

A generic function to extract the conditional modes of the random effects from a fitted model object. For linear mixed models the conditional modes of the random effects are also the conditional means.

Arguments

object an object of a class of fitted models with random effects.

Details

If grouping factor i has k levels and j random effects per level the i th component of the list returned by `ranef` is a data frame with k rows and j columns.

Value

- From `ranef`: An object composed of a list of data frames, one for each grouping factor for the random effects. The number of rows in the data frame is the number of levels of the grouping factor. The number of columns is the dimension of the random effect associated with each level of the factor.

Examples

```
library(lattice) ## for dotplot, qqmath
library(lme4)
fm1 <- lmer(Reaction ~ Days + (Days|Subject), sleepstudy)
fm2 <- lmer(Reaction ~ Days + (1|Subject) + (0+Days|Subject), sleepstudy)
fm3 <- lmer(diameter ~ (1|plate) + (1|sample), Penicillin)
ranef(fm1)
```

ranef-actuaRE	<i>Extract the random effect estimates from a fitted random effects model</i>
---------------	---

Description

A generic function to extract the estimates/predictions of the random effects from a fitted random effects model.

Usage

```
## S3 method for class 'hierCredibility'  
ranef(object, ...)  
  
## S3 method for class 'hierCredGLM'  
ranef(object, ...)  
  
## S3 method for class 'hierCredTweedie'  
ranef(object, ...)  
  
## S3 method for class 'buhlmannStraubGLM'  
ranef(object, ...)  
  
## S3 method for class 'buhlmannStraub'  
ranef(object, ...)  
  
## S3 method for class 'buhlmannStraubTweedie'  
ranef(object, ...)
```

Arguments

object	an object of type hierCredibility , hierCredGLM or hierCredTweedie
...	Currently ignored.

Value

A list of data frames, one for each grouping factor for the random effects. The number of rows in the data frame is the number of levels of the grouping factor. The first (two) columns correspond(s) to the grouping factor. The last column corresponds to the estimated random effect.

simulatedclustereddata

Simulated data sets to illustrate the package functionality

Description

Both the `tweedietraindata` and `tweedietestdata` dataframe are synthetically generated data sets to illustrate the functionality of the package. The `tweedietraindata` has 250 000 observations and the `tweedietestdata` has 250 000 observations. The same settings were used to generate both data sets.

Usage

```
data(tweedietraindata)  
data(tweedietestdata)
```

Format

y the tweedie distributed outcome variable
 cluster the cluster
 subcluster the subcluster nested within cluster
 x1 covariate 1
 x2 covariate 2
 x3 covariate 3
 x4 covariate 4
 x5 covariate 5

Details

See the examples for how the data sets were generated.

Examples

```

# The data sets were generated as follows
lapply(c("magrittr", "dplyr", "data.table", "tweedie"), library, character.only = TRUE)
set.seed(1)

# Simulate training data
set.seed(1)
nClusters = 5
nSubclusters = 5
p = 5
Uj = scale(rnorm(nClusters))
Ujk = do.call("c", lapply(seq_len(nClusters), function(x) scale(rnorm(nSubclusters)))))
nPop = 1e6
nSample = 50
nTest = 1e3
X = replicate(p, rnorm(nPop))
Beta = rnorm(p)
cluster = sample(seq_len(nClusters), nPop, TRUE)
subcluster = NULL
uniqueCl = sort(unique(cluster))
for(cl in uniqueCl)
  subcluster[cluster == cl] <- sample(
    1 - seq_len(nSubclusters) + which(cl == uniqueCl) * nSubclusters,
    sum(cluster == cl),
    TRUE)
table(subcluster, cluster)
eta = X %*% Beta + Uj[match(cluster, seq_len(nClusters))] +
  Ujk[match(subcluster, seq_len(nClusters) * nSubclusters)]
y = rtweedie(nPop, mu = exp(as.vector(eta)), phi = 1, power = 1.5)
wt = runif(nPop)
Dt = data.frame(y, X, wt, cluster, subcluster)
colnames(Dt) %<>% tolower

tweedietraindata = Dt %>%

```

```

group_by(subcluster) %>%
sample_n(size = nSample) %>%
as.data.table

tweedietestdata = Dt %>%
group_by(subcluster) %>%
sample_n(size = nSample) %>%
as.data.table

```

tweedieGLMM	<i>Fitting a Tweedie GLMM, using initial estimates from credibility models</i>
-------------	--

Description

This function first estimates the random effects model using Ohlsson's GLMC algorithm (Ohlsson, 2008) and then uses these estimates as initial estimates when fitting a Tweedie GLMM. Supports both single random effects and nested random effects.

Usage

```

tweedieGLMM(
  formula,
  data,
  weights,
  muHatGLM = FALSE,
  epsilon = 1e-04,
  maxiter = 500,
  verbose = FALSE,
  balanceProperty = TRUE
)

```

Arguments

formula	object of type <code>formula</code> that specifies which model should be fitted. Syntax is the same as for <code>lmer</code> and <code>glmer</code> . For single random effect: $Y \sim x_1 + x_2 + (1 \text{Cluster})$. For nested random effects: $Y \sim x_1 + x_2 + (1 \text{cluster} / \text{subcluster})$.
data	an object that is coercible by <code>as.data.table</code> , containing the variables in the model.
weights	variable name of the exposure weight.
muHatGLM	indicates which estimate has to be used in the algorithm for the intercept term. Default is <code>FALSE</code> , which uses the intercept as estimated by the credibility model. If <code>TRUE</code> , the estimate of the GLM is used.
epsilon	positive convergence tolerance ϵ ; the iterations converge when $\ \theta[k] - \theta[k - 1]\ _2^2 / \ \theta[k - 1]\ _2^2 < \epsilon$. Here, $\theta[k]$ is the parameter vector at the k^{th} iteration.
maxiter	maximum number of iterations.

verbose logical indicating if output should be produced during the algorithm.
 balanceProperty logical indicating if the balance property should be satisfied.

Value

an object of class `cpplmm`, containing the model fit.

References

Campo, B.D.C. and Antonio, Katrien (2023). Insurance pricing with hierarchically structured data an illustration with a workers' compensation insurance portfolio. *Scandinavian Actuarial Journal*, doi: 10.1080/03461238.2022.2161413

Ohlsson, E. (2008). Combining generalized linear models and credibility models in practice. *Scandinavian Actuarial Journal* **2008**(4), 301–314.

See Also

[cpplmm](#), [hierCredTweedie](#)

Examples

```
# Nested random effects example
data("tweedietraindata")
fit = tweedieGLMM(y ~ x1 + (1 | cluster / subcluster), tweedietraindata, weights = wt)
fit
```

<code>weights-actuaRE</code>	<i>Extract the model weights</i>
------------------------------	----------------------------------

Description

`weights` is a generic function which extracts fitting weights from objects returned by modeling functions. Methods can make use of [napredict](#) methods to compensate for the omission of missing values. The default methods does so.

Usage

```
## S3 method for class 'cpplm'
weights(object, type = c("prior", "working"), ...)

## S3 method for class 'hierCredGLM'
weights(object, type = c("prior", "working"), ...)

## S3 method for class 'hierCredTweedie'
weights(object, type = c("prior", "working"), ...)
```

```
## S3 method for class 'buhlmannStraubGLM'  
weights(object, type = c("prior", "working"), ...)
```

```
## S3 method for class 'buhlmannStraubTweedie'  
weights(object, type = c("prior", "working"), ...)
```

Arguments

object	an object for which the extraction of model weights is meaningful. Can be either cpglm , glm , hierCredibility , hierCredGLM or hierCredTweedie
type	indicates if prior or working weights need to be extracted.
...	ignored

Value

Weights extracted from the object object: the default method looks for component "weights" and if not NULL calls [napredict](#) on it.

See Also

[weights](#), [cpglm](#), [glm](#), [hierCredibility](#), [hierCredGLM](#) or [hierCredTweedie](#)

Index

- * **datasets**
 - dataCar, [12](#)
 - hachemeisterLong, [16](#)
 - simulatedclustereddata, [42](#)
- * **methods**
 - ranef, [41](#)
- * **models**
 - findbars, [13](#)
 - fixef, [14](#)
 - modular, [28](#)
 - nobars, [31](#)
 - ranef, [41](#)
- * **package**
 - actuaRE-package, [3](#)
- * **utilities**
 - findbars, [13](#)
 - nobars, [31](#)
- .addRES, [4](#)
- actuaRE (actuaRE-package), [3](#)
- actuaRE-package, [3](#)
- adjustIntercept, [4](#), [7](#), [9](#), [11](#), [18](#), [25](#)
- as.data.table, [6](#), [8](#), [10](#), [17](#), [20](#), [24](#), [44](#)
- BalanceProperty, [3](#), [5](#), [7](#), [9](#), [11](#), [18](#), [25](#), [40](#)
- bobyqa, [11](#), [24](#)
- buhlmannStraub, [3](#), [6](#), [9](#), [11](#), [33–35](#)
- buhlmannStraub-class
 - (predict.buhlmannStraub), [34](#)
- buhlmannStraubGLM, [3](#), [7](#), [7](#), [10](#), [11](#), [33](#), [35](#), [36](#)
- buhlmannStraubGLM-class
 - (predict.buhlmannStraubGLM), [35](#)
- buhlmannStraubTweedie, [3](#), [7](#), [9](#), [10](#), [33](#), [37](#), [38](#)
- buhlmannStraubTweedie-class
 - (predict.buhlmannStraubTweedie), [36](#)
- cpglm, [4](#), [11](#), [21](#), [24](#), [25](#), [39](#), [46](#)
- cpglm, [4](#), [45](#)
- data.frame, [4](#)
- data.table, [4](#)
- dataCar, [12](#), [12](#)
- environment, [30](#)
- family, [29](#)
- findbars, [13](#), [32](#)
- fitted.buhlmannStraub
 - (predict.buhlmannStraub), [34](#)
- fitted.buhlmannStraubGLM
 - (predict.buhlmannStraubGLM), [35](#)
- fitted.buhlmannStraubTweedie
 - (predict.buhlmannStraubTweedie), [36](#)
- fitted.hierCredGLM, [18](#)
- fitted.hierCredGLM (hierCredGLM-class), [19](#)
- fitted.hierCredibility
 - (hierCredibility-class), [22](#)
- fitted.hierCredTweedie
 - (hierCredTweedie-class), [26](#)
- fixed.effects (fixef), [14](#)
- fixef, [14](#)
- fixef-actuaRE, [15](#)
- fixef.buhlmannStraubGLM
 - (fixef-actuaRE), [15](#)
- fixef.buhlmannStraubTweedie
 - (fixef-actuaRE), [15](#)
- fixef.hierCredGLM (fixef-actuaRE), [15](#)
- fixef.hierCredTweedie (fixef-actuaRE), [15](#)
- formula, [8](#), [10](#), [14](#), [17](#), [24](#), [32](#), [44](#)
- geom_point, [33](#)
- ggplot, [33](#)
- ggplot2, [33](#)
- glFormula (modular), [28](#)
- glm, [4](#), [29](#), [46](#)
- glmer, [17](#), [24](#), [44](#)

- hachemeisterLong, 16
- hierCredGLM, 3, 7, 15, 17, 19–21, 25, 26, 33, 38, 42, 46
- hierCredGLM-class, 19
- hierCredibility, 3, 18, 20, 22, 23, 25, 33, 39, 42, 46
- hierCredibility-class, 22
- hierCredTweedie, 3, 11, 15, 17, 18, 21, 23, 26, 27, 33, 40, 42, 45, 46
- hierCredTweedie-class, 26

- is.formula, 27
- isNested, 28

- list, 29
- lmer, 8, 10, 17, 24, 29, 44
- lmerControl, 29

- mkMerMod, 30
- mkRespMod, 14, 32
- mkReTrms, 14, 30, 32
- model.frame, 14, 32
- model.matrix, 14, 32
- model.matrix.default, 29
- model.offset, 29
- modular, 28

- napredict, 45, 46
- nlformula, 14, 32
- nlminb, 11, 24
- nobars, 14, 31
- NrUnique, 32

- offset, 29
- optim, 11, 24

- plotRE, 7, 9, 11, 18, 21, 25, 33
- predict.buhlmannStraub, 34
- predict.buhlmannStraubGLM, 35
- predict.buhlmannStraubTweedie, 36
- predict.hierCredGLM, 18, 38
- predict.hierCredibility, 39
- predict.hierCredTweedie, 39
- print.BalanceProperty, 40
- print.buhlmannStraub
 - (predict.buhlmannStraub), 34
- print.buhlmannStraubGLM
 - (predict.buhlmannStraubGLM), 35
- print.buhlmannStraubTweedie
 - (predict.buhlmannStraubTweedie), 36
- print.hierCredGLM (hierCredGLM-class), 19
- print.hierCredibility
 - (hierCredibility-class), 22
- print.hierCredTweedie
 - (hierCredTweedie-class), 26

- ranef, 41
- ranef-actuaRE, 41
- ranef.buhlmannStraub (ranef-actuaRE), 41
- ranef.buhlmannStraubGLM
 - (ranef-actuaRE), 41
- ranef.buhlmannStraubTweedie
 - (ranef-actuaRE), 41
- ranef.hierCredGLM (ranef-actuaRE), 41
- ranef.hierCredibility (ranef-actuaRE), 41
- ranef.hierCredTweedie (ranef-actuaRE), 41
- ReferenceClasses, 30

- simulatedclustereddata, 42
- subbars, 14, 32
- summary.buhlmannStraub
 - (predict.buhlmannStraub), 34
- summary.buhlmannStraubGLM
 - (predict.buhlmannStraubGLM), 35
- summary.buhlmannStraubTweedie
 - (predict.buhlmannStraubTweedie), 36
- summary.glm, 20, 27
- summary.hierCredGLM
 - (hierCredGLM-class), 19
- summary.hierCredibility
 - (hierCredibility-class), 22
- summary.hierCredTweedie
 - (hierCredTweedie-class), 26

- tweedie, 8, 17
- tweedieGLMM, 3, 7, 9, 44
- tweedietestdata
 - (simulatedclustereddata), 42
- tweedietraindata
 - (simulatedclustereddata), 42
- weights, 46

weights-actuaRE, [45](#)
weights.buhlmannStraubGLM
 (weights-actuaRE), [45](#)
weights.buhlmannStraubTweedie
 (weights-actuaRE), [45](#)
weights.cpglm (weights-actuaRE), [45](#)
weights.hierCredGLM (weights-actuaRE),
 [45](#)
weights.hierCredTweedie
 (weights-actuaRE), [45](#)