

Package ‘c060’

March 24, 2026

Version 0.5-0

Date 2026-03-24

Maintainer Frederic Bertrand <frederic.bertrand@lecnam.net>

Title Extended Inference for Lasso and Elastic-Net Regularized Cox and Generalized Linear Models

Imports glmnet, survival, parallel, mlegp, tgp, pamr, peperr, penalized, penalizedSVM, lattice, methods

Suggests withr, testthat (>= 3.0.0)

Description The c060 package provides additional functions to perform stability selection, model validation and parameter tuning for glmnet models.

License GPL-2

LazyLoad yes

NeedsCompilation no

URL <https://fbertran.github.io/c060/>, <https://github.com/fbertran/c060>

BugReports <https://github.com/fbertran/c060/issues>

Config/testthat/edition 3

RoxygenNote 7.3.3

Encoding UTF-8

Author Martin Sill [aut],
Thomas Hielscher [aut],
Manuela Zucknick [aut],
Natalia Becker [aut],
Frederic Bertrand [cre] (ORCID:
<<https://orcid.org/0000-0002-0837-8281>>)

Repository CRAN

Date/Publication 2026-03-24 20:50:02 UTC

Contents

aggregation.auc	2
balancedFolds	4
coef.sum.intsearch	5
complexity.glmnet	6
EPSGO	7
fit.glmnet	11
PLL.coxnet	12
Plot.coef.glmnet	13
Plot.peperr.curves	14
plot.stabpath	16
plot.sum.intsearc	18
predictProb.coxnet	19
stabpath	20
stabsel	22
summary.intsearch	24
tune.glmnet.interval	25
Index	28

aggregation.auc	<i>Determine the area under the ROC curve for a fitted model</i>
-----------------	--

Description

Evaluate the area under the ROC curve for a fitted model on new data. To be used as argument aggregation.fun in peperr call.

Usage

```
aggregation.auc(
  full.data = NULL,
  response,
  x,
  model,
  cplx = NULL,
  type = c("apparent", "noinf"),
  fullsample.attr = NULL,
  ...
)
```

Arguments

full.data	passed from peperr, but not used for calculation.
response	vector of binary response.
x	n*p matrix of covariates.

model	model fitted as returned by a <code>fit.fun</code> , as used in a call to <code>peperr</code> .
cplx	passed from <code>peperr</code> , but not necessary for calculation.
type	character.
fullsample.attr	passed from <code>peperr</code> , but not necessary for calculation.
...	additional arguments, passed to <code>predict</code> function.

Details

Area under the ROC curve is calculated based on internal `glmnet::auc` function from package `glmnet`.

Value

Scalar, indicating the area under the ROC curve.

Author(s)

Thomas Hielscher <t.hielscher@dkfz.de>

See Also

[peperr](#)

Examples

```
## Not run:
# binomial model - classification

library(c060)
library(gridExtra)
library(ggplot2)

set.seed(0815)
x <- matrix(rnorm(100*20),100,20)
y <- sample(0:1,100,replace=TRUE)

peperr_obj <- peperr(response=y, x=x, fit.fun=fit.glmnet, args.fit=list(family="binomial"),
  complexity=complexity.glmnet, args.complexity=list(nfolds=10, family="binomial"),
  trace=F, RNG="fixed", seed=0815,
#   aggregation.fun=c060::aggregation.misclass,
#   aggregation.fun=c060::aggregation.brier,
  aggregation.fun=c060::aggregation.auc,
  indices=resample.indices(n=nrow(x), sample.n = 100, method = "sub632"))

tmp <- data.frame(grp="", error=unlist(peperr_obj$sample.error))
errs <- data.frame(error=c(perr(peperr_obj, "resample"),
  perr(peperr_obj, "632p"), perr(peperr_obj, "app"),
  perr(peperr_obj, "nullmodel")), col = c("red", "blue", "green", "brown"),
  row.names=c("mean\nout-of-bag", ".632plus", "apparent", "null model"))
```

```

p <- ggplot(tmp, aes(grp,error))
pg <- p + geom_boxplot(outlier.colour = rgb(0,0,0), outlier.size=0) +
  geom_jitter(position=position_jitter(width=.1)) +
  theme_bw() + scale_y_continuous("AUC") + scale_x_discrete("") +
  geom_hline(aes(yintercept=error, colour=col), data=errs, show_guide=T) +
  scale_colour_identity("error type", guide = "legend", breaks=errs$col,
  labels=rownames(errs)) +
  ggtitle("AUC \n in bootstrap samples ")

p2 <- ggplot(data.frame(complx=peperr_obj$sample.complexity), aes(x=complx))
pg2 <- p2 + geom_histogram(binwidth = 0.02, fill = "white", colour="black") +
  theme_bw()+ xlab(expression(lambda)) +
  ylab("frequency") +
  geom_vline(xintercept=peperr_obj$selected.complexity, colour="red") +
  ggtitle("Selected complexity \n in bootstrap samples") +
  ggplot2::annotate("text", x = 0.12, y = -0.5,
  label = "full data", colour="red", size=4)

grid.arrange(pg2, pg, ncol=2)

## End(Not run)

```

balancedFolds

Function producing stratified/ balanced folds for cross validation

Description

Get balanced folds for cross validation, which are used for tuning penalization parameters

Usage

```
balancedFolds(class.column.factor, cross.outer)
```

Arguments

```

class.column.factor      class labels of length n
cross.outer              number of folds

```

Value

```

permutated.cut  vector of length n, indicating the fold belongs to
model          model list

```

- alpha - optimal alpha
- lambda - optimal lambda
- nfolds - cross-validation's folds
- cvreg - cv.glmnet object for optimal alpha
- fit - glmnet object for optimal alpha and optimal lambda

Author(s)

Natalia Becker natalia.becker at dkfz.de

References

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

See Also

[EPSGO](#)

coef.sum.intsearch *Get coefficients for a model*

Description

Get coefficients for a model after applying interval search for tuning parameters

Usage

```
## S3 method for class 'sum.intsearch'  
coef(object, ...)
```

Arguments

object	an object as returned by the function <code>summary.intsearch</code> .
...	additional argument(s)

Value

named vector of non-zero coefficients for the optimal lambda

Author(s)

Natalia Becker \<natalia.becker@dkfz.de>

References

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

See Also

[EPSGO](#), [summary.intsearch](#), [plot.sum.intsearch](#)

complexity.glmnet	<i>Interface for determination of penalty lambda in penalized regression model via cross-validation</i>
-------------------	---

Description

Determines the amount of shrinkage for a penalized regression model fitted by glmnet via cross-validation, conforming to the calling convention required by argument complexity in peperr call.

Usage

```
complexity.glmnet(response, x, full.data, ...)
```

Arguments

response	a survival object (with Surv(time, status), or a binary vector with entries 0 and 1).
x	n*p matrix of covariates.
full.data	data frame containing response and covariates of the full data set.
...	additional arguments passed to cv.glmnet call such as family.

Details

Function is basically a wrapper for cv.glmnet of package glmnet. A n-fold cross-validation (default n=10) is performed to determine the optimal penalty lambda. For Cox PH regression models the deviance based on penalized partial log-likelihood is used as loss function. For binary endpoints other loss functions are available as well (see type.measure). Deviance is default. Calling peperr, the default arguments of cv.glmnet can be changed by passing a named list containing these as argument args.complexity. Note that only penalized Cox PH (family="cox") and logistic regression models (family="binomial") are sensible for prediction error evaluation with package peperr.

Value

Scalar value giving the optimal lambda.

Author(s)

Thomas Hielscher <t.hielscher@dkfz.de>

References

Friedman, J., Hastie, T. and Tibshirani, R. (2008) *Regularization Paths for Generalized Linear Models via Coordinate Descent*, <https://web.stanford.edu/~hastie/Papers/glmnet.pdf>
Journal of Statistical Software, Vol. 33(1), 1-22 Feb 2010
<https://www.jstatsoft.org/v33/i01/>

Simon, N., Friedman, J., Hastie, T., Tibshirani, R. (2011) *Regularization Paths for Cox's Proportional Hazards Model via Coordinate Descent*, *Journal of Statistical Software*, Vol. 39(5) 1-13

<https://www.jstatsoft.org/v39/i05/>

Porzelius, C., Binder, H., and Schumacher, M. (2009) *Parallelized prediction error estimation for evaluation of high-dimensional models*, *Bioinformatics*, Vol. 25(6), 827-829.

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

See Also

[peperr](#), [cv.glmnet](#)

EPSGO

Efficient Parameter Selection via Global Optimization

Description

Finds an optimal solution for the Q.func function.

Usage

```
EPSGO(
  Q.func,
  bounds,
  round.n = 5,
  parms.coding = "none",
  fminlower = 0,
  flag.find.one.min = FALSE,
  show = c("none", "final", "all"),
  N = NULL,
  maxevals = 500,
  pdf.name = NULL,
  pdf.width = 12,
  pdf.height = 12,
  my.mfrow = c(1, 1),
  verbose = TRUE,
  seed = 123,
  ...
)
```

Arguments

Q.func	name of the function to be minimized.
bounds	bounds for parameters
round.n	number of digits after comma, default: 5
parms.coding	parameters coding: none or log2, default: none.

<code>fminlower</code>	minimal value for the function <code>Q.func</code> , default is 0.
<code>flag.find.one.min</code>	do you want to find one min value and stop? Default: FALSE
<code>show</code>	show plots of DIRECT algorithm: none, final iteration, all iterations. Default: none
<code>N</code>	define the number of start points, see details.
<code>maxevals</code>	the maximum number of DIRECT function evaluations, default: 500.
<code>pdf.name</code>	pdf name
<code>pdf.width</code>	default: 12
<code>pdf.height</code>	default: 12
<code>my.mfrow</code>	default: <code>c(1,1)</code>
<code>verbose</code>	verbose? default: TRUE.
<code>seed</code>	seed
<code>...</code>	additional argument(s)

Details

if the number of start points (N) is not defined by the user, it will be defined dependent on the dimensionality of the parameter space. $N=10D+1$, where D is the number of parameters, but for high dimensional parameter space with more than 6 dimensions, the initial set is restricted to 65. However for one-dimensional parameter space the N is set to 21 due to stability reasons.

The idea of EPSGO (Efficient Parameter Selection via Global Optimization): Beginning from an initial Latin hypercube sampling containing N starting points we train an Online GP, look for the point with the maximal expected improvement, sample there and update the Gaussian Process(GP). Thereby it is not so important that GP really correctly models the error surface of the SVM in parameter space, but that it can give us information about potentially interesting points in parameter space where we should sample next. We continue with sampling points until some convergence criterion is met.

DIRECT is a sampling algorithm which requires no knowledge of the objective function gradient. Instead, the algorithm samples points in the domain, and uses the information it has obtained to decide where to search next. The DIRECT algorithm will globally converge to the maximal value of the objective function. The name DIRECT comes from the shortening of the phrase 'Dividing RECTangles', which describes the way the algorithm moves towards the optimum.

The code source was adopted from MATLAB originals, special thanks to Holger Froehlich.

Value

<code>fmin</code>	minimal value of <code>Q.func</code> on the interval defined by bounds.
<code>xmin</code>	corresponding parameters for the minimum
<code>iter</code>	number of iterations
<code>neval</code>	number of visited points
<code>maxevals</code>	the maximum number of DIRECT function evaluations
<code>seed</code>	seed

bounds	bounds for parameters
Q.func	name of the function to be minimized.
points.fmin	the set of points with the same fmin
Xtrain	visited points
Ytrain	the output of Q.func at visited points Xtrain
gp.seed	seed for Gaussian Process
model.list	detailed information of the search process

Author(s)

Natalia Becker natalia.becker at dkfz.de

References

Froehlich, H. and Zell, A. (2005) "Efficient parameter selection for support vector machines in classification and regression via model-based global optimization" *In Proc. Int. Joint Conf. Neural Networks, 1431-1438*.

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models, Journal of Statistical Software, Volume 62(5), pages 1–22.* <https://doi.org/10.18637/jss.v062.i05>.

Examples

```

set.seed(1010)
n=1000;p=100
nzc=trunc(p/10)
x=matrix(rnorm(n*p),n,p)
beta=rnorm(nzc)
fx= x[,seq(nzc)] %*% beta
eps=rnorm(n)*5
y=drop(fx+eps)
px=exp(fx)
px=px/(1+px)
ly=rbinom(n=length(px),prob=px,size=1)
set.seed(1011)

# y - binomial
y.classes<-ifelse(y>= median(y),1, 0)
set.seed(1234)
nfolds = 10
foldid <- balancedFolds(class.column.factor=y.classes, cross.outer=nfolds)
bounds <- t(data.frame(alpha=c(0, 1)))
colnames(bounds)<-c("lower", "upper")

fit <- EPSGO(Q.func="tune.glmnet.interval",
             bounds=bounds,
             parms.coding="none",

```

```

        seed = 1234,
        show="none",
        fminlower = -100,
        x = x, y = y.classes, family = "binomial",
        foldid = foldid,
        type.min = "lambda.1se",
        type.measure = "mse")
summary(fit)

## Not run:
# y - multinomial: low - low 25%, middle - (25,75)-quantiles, high - larger 75%.
y.classes<-ifelse(y <= quantile(y,0.25),1, ifelse(y >= quantile(y,0.75),3, 2))
set.seed(1234)
nfolds = 10
foldid <- balancedFolds(class.column.factor=y.classes, cross.outer=nfolds)
bounds <- t(data.frame(alpha=c(0, 1)))
colnames(bounds)<-c("lower", "upper")

fit <- EPSGO(Q.func="tune.glmnet.interval",
            bounds=bounds,
            parms.coding="none",
            seed = 1234,
            show="none",
            fminlower = -100,
            x = x, y = y.classes, family = "multinomial",
            foldid = foldid,
            type.min = "lambda.1se",
            type.measure = "mse")
summary(fit)

## End(Not run)

## Not run:
##poisson
N=500; p=20
nzc=5
x=matrix(rnorm(N*p),N,p)
beta=rnorm(nzc)
f = x[,seq(nzc)]%*%beta
mu=exp(f)
y.classes=rpois(N,mu)

nfolds = 10
set.seed(1234)
foldid <- balancedFolds(class.column.factor=y.classes, cross.outer=nfolds)

fit <- EPSGO(Q.func="tune.glmnet.interval",
            bounds=bounds,
            parms.coding="none",
            seed = 1234,
            show="none",
            fminlower = -100,

```

```

        x = x, y = y.classes, family = "poisson",
        foldid = foldid,
        type.min = "lambda.1se",
        type.measure = "mse")
summary(fit)

## End(Not run)

## Not run:
#gaussian
set.seed(1234)
x=matrix(rnorm(100*1000,0,1),100,1000)
y <- x[1:100,1:1000]*%*%c(rep(2,5),rep(-2,5),rep(.1,990))

foldid <- rep(1:10,each=10)

fit <- EPSGO(Q.func="tune.glmnet.interval",
            bounds=bounds,
            parms.coding="none",
            seed = 1234,
            show="none",
            fminlower = -100,
            x = x, y = y, family = "gaussian",
            foldid = foldid,
            type.min = "lambda.1se",
            type.measure = "mse")
summary(fit)

## End(Not run)

# y - cox in vignette

```

fit.glmnet

Interface function for fitting a penalized regression model with glmnet

Description

Interface for fitting penalized regression models for binary or survival endpoint using glmnet, conforming to the requirements for argument fit.fun in peperr call.

Usage

```
fit.glmnet(response, x, cplx, ...)
```

Arguments

response a survival object (with Surv(time, status), or a binary vector with entries 0 and 1).

x n*p matrix of covariates.
 cplx lambda penalty value.
 ... additional arguments passed to glmnet call such as family.

Details

Function is basically a wrapper for glmnet of package **glmnet**. Note that only penalized Cox PH (family="cox") and logistic regression models (family="binomial") are sensible for prediction error evaluation with package peperr.

Value

glmnet object

Author(s)

Thomas Hielscher <t.hielscher@dkfz.de>

References

Friedman, J., Hastie, T. and Tibshirani, R. (2008) *Regularization Paths for Generalized Linear Models via Coordinate Descent*, <https://web.stanford.edu/~hastie/Papers/glmnet.pdf>
Journal of Statistical Software, Vol. 33(1), 1-22 Feb 2010
<https://www.jstatsoft.org/v33/i01/>

Simon, N., Friedman, J., Hastie, T., Tibshirani, R. (2011) *Regularization Paths for Cox's Proportional Hazards Model via Coordinate Descent*, *Journal of Statistical Software*, Vol. 39(5) 1-13
<https://www.jstatsoft.org/v39/i05/>

Porzelius, C., Binder, H., and Schumacher, M. (2009) *Parallelized prediction error estimation for evaluation of high-dimensional models*, *Bioinformatics*, Vol. 25(6), 827-829.

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

See Also

[peperr](#), [glmnet](#)

 PLL.coxnet

Predictive partial log-likelihood for glmnet Cox PH model fit

Description

Extracts the predictive partial log-likelihood from a glmnet Cox PH model fit.

Usage

```
## S3 method for class 'coxnet'
PLL(object, newdata, newtime, newstatus, complexity, ...)
```

Arguments

object	fitted model of class coxnet.
newdata	n_new*p matrix of covariates.
newtime	n_new-vector of censored survival times.
newstatus	n_new-vector of survival status, coded with 0 and .1
complexity	lambda penalty value.
...	additional arguments, not used.

Details

Used by function peperr, if function fit.glmnet and family="cox" is used for model fit, which gives a class coxnet object. This is basically a wrapper based on the coxnet.deviance function from package glmnet.

Value

Vector of length n_new

Author(s)

Thomas Hielscher <t.hielscher@dkfz.de>

References

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

Plot.coef.glmnet	<i>function to highlight the path of a pre-specified set of variables within the coefficient path</i>
------------------	---

Description

Creates several plots showing the coefficient path for the final model of a cv.glmnet fit and highlights the path of a pre-specified set of variables within the coefficient path.

Usage

```
Plot.coef.glmnet(cvfit, betas)
```

Arguments

cvfit	an object of class "cv.glmnet" as returned by the function cv.glmnet.
betas	a vector of names of variables; must be a subset of rownames(coef(cvfit)).

Value

a list of four objects

stable	a vector giving the positions of the estimated stable variables
lambda	the penalization parameter used for the stability selection
lpos	the position of the penalization parameter in the regularization path
error	the desired type I error level w.r.t. to the chosen type I error rate
type	the type I error rate

Author(s)

Manuela Zucknick \<m.zucknick@dkfz-heidelberg.de>

References

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

Examples

```
## Not run:
set.seed(1010)
n=1000;p=100
nzc=trunc(p/10)
x=matrix(rnorm(n*p),n,p)
beta=rnorm(nzc)
fx= x[,seq(nzc)] %*% beta
eps=rnorm(n)*5
y=drop(fx+eps)
px=exp(fx)
px=px/(1+px)
ly=rbinom(n=length(px),prob=px,size=1)
set.seed(1011)
cvob1=cv.glmnet(x,y)
Plot.coef.glmnet(cvob1, c("V1","V100"))

## End(Not run)
```

Plot.peperr.curves *Plot method for prediction error curves of a peperr object*

Description

Plots individual and aggregated prediction error estimates based on bootstrap samples.

Usage

```
Plot.peperr.curves(
  x,
  at.risk = TRUE,
  allErrors = FALSE,
  bootRuns = FALSE,
  bootQuants = TRUE,
  bootQuants.level = 0.95,
  leg.cex = 0.7,
  ...
)
```

Arguments

x	peperr object.
at.risk	number at risk to be display. default is TRUE.
allErrors	Display .632, no information and average out-of-bag error in addition. default is FALSE.
bootRuns	Display individual out-of-bag bootstrap samples. default is FALSE.
bootQuants	Display pointwise out-of-bag bootstrap quantiles as shaded area. default is TRUE.
bootQuants.level	Quantile probabilities for pointwise out-of-bag bootstrap quantiles. default is 0.95, i.e. 2.5% and 97.5% quantiles.
leg.cex	size of legend text
...	additional arguments, not used.

Details

This function is literally taken from `plot.peperr` in the `peperr` package. The display of prediction error curves is adapted to allow for numbers at risk and pointwise bootstrap quantiles.

Author(s)

Thomas Hielscher <t.hielscher@dkfz.de>

References

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

See Also

[peperr](#)

Examples

```
## Not run:

# example from glmnet package
set.seed(10101)
library(glmnet)
library(survival)
library(peperr)

N=1000;p=30
nzc=p/3
x=matrix(rnorm(N*p),N,p)
beta=rnorm(nzc)
fx=x[,seq(nzc)]%*%beta/3
hx=exp(fx)
ty=rexp(N,hx)
tcens=rbinom(n=N,prob=.3,size=1)# censoring indicator
y=Surv(ty,1-tcens)

peperr.object <- peperr(response=y, x=x,
                       fit.fun=fit.glmnet, args.fit=list(family="cox"),
                       complexity=complexity.glmnet,
                       args.complexity=list(family="cox",nfolds=10),
                       indices=resample.indices(n=N, method="sub632", sample.n=10))

# pointwise bootstrap quantiles and all error types
Plot.peperr.curves(peperr.object, allErrors=TRUE)

# individual bootstrap runs and selected error types
Plot.peperr.curves(peperr.object, allErrors=FALSE, bootRuns=TRUE)

## End(Not run)
```

plot.stabpath *function to plot a stability path*

Description

Given a desired family-wise error rate (FWER) and a stability path calculated with `stability.path` the function selects an stable set of features and plots the stability path and the corresponding regularization path.

Usage

```
## S3 method for class 'stabpath'
plot(
  x,
  error = 0.05,
```

```

    type = c("pfer", "pcer"),
    pi_thr = 0.6,
    xvar = c("lambda", "norm", "dev"),
    col.all = "black",
    col.sel = "red",
    ...
)

```

Arguments

x	an object of class "stabpath" as returned by the function stabpath.
error	the desired type I error level w.r.t. to the chosen type I error rate.
type	The type I error rate used for controlling the number falsely selected variables. If type="pfer" the per-family error rate is controlled and error corresponds to the expected number of type I errors. Selecting type="pfer" and error in the range of $0 > \text{error} < 1$ will control the family-wise error rate, i.e. the probability that at least one variable in the estimated stable set has been falsely selected. If type="pcer" the per-comparison error rate is controlled and error corresponds to the expected number of type I errors divided by the number variables.
pi_thr	the threshold used for the stability selection, should be in the range of $0.5 > \text{pi_thr} < 1$.
xvar	the variable used for the xaxis, e.g. for "lambda" the selection probabilities are plotted along the log of the penalization parameters, for "norm" along the L1-norm and for "dev" along the fraction of explained deviance.
col.all	the color used for the variables that are not in the estimated stable set
col.sel	the color used for the variables in the estimated stable set
...	further arguments that are passed to matplot

Value

a list of four objects

stable	a vector giving the positions of the estimated stable variables
lambda	the penalization parameter used for the stability selection
lpos	the position of the penalization parameter in the regularization path
error	the desired type I error level w.r.t. to the chosen type I error rate
type	the type I error rate

Author(s)

Martin Sill \<m.sill@dkfz.de>

References

- Meinshausen N. and Bühlmann P. (2010), Stability Selection, *Journal of the Royal Statistical Society: Series B (Statistical Methodology)* Volume 72, Issue 4, pages 417-473.
- Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

See Also

[stabsel](#), [stabpath](#)

Examples

```
## Not run:
#gaussian
set.seed(1234)
x=matrix(rnorm(100*1000,0,1),100,1000)
y <- x[1:100,1:1000]%%c(rep(2,5),rep(-2,5),rep(.1,990))
res <- stabpath(y,x,weakness=1,mc.cores=2)
plot(res,error=.5,type='pfer')

## End(Not run)
```

plot.sum.intsearch *Plot Summary object for interval search models*

Description

Produces a plot for summary object of a fitted interval search model. Plot 'visited' points against iteration steps. start.N points are initial points selected before interval search starts.

Usage

```
## S3 method for class 'sum.intsearch'
plot(x, type = "summary", startN = 21, ...)
```

Arguments

x	an object of class <code>sum.intsearch</code> as returned by the function summary.intsearch .
type	type of plot to be drawn, <code>type="summary"</code> will plot the partial log likelihood deviance as a function of both tuning parameters α and $\log \lambda$. The final solution will be highlighted by solid red line. Alternatively, <code>type="points"</code> will draw the distribution of initial and visited points of the interval search plotted in chronological order.
startN	number of initial points. Needed if <code>type="points"</code>
...	additional argument(s)

Author(s)

Natalia Becker \<natalia.becker@dkfz.de>

References

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

See Also

[EPSGO](#), [summary.intsearch](#)

predictProb.coxnet *Extract predicted survival probabilities from a glmnet fit*

Description

Extracts predicted survival probabilities from survival model fitted by glmnet, providing an interface as required by pmpec.

Usage

```
## S3 method for class 'coxnet'  
predictProb(object, response, x, times, complexity, ...)
```

Arguments

object	a fitted model of class glmnet
response	a two-column matrix with columns named 'time' and 'status'. The latter is a binary variable, with '1' indicating death, and '0' indicating right censored. The function Surv() in package survival produces such a matrix
x	n*p matrix of covariates.
times	vector of evaluation time points.
complexity	lambda penalty value.
...	additional arguments, currently not used.

Value

Matrix with probabilities for each evaluation time point in times (columns) and each new observation (rows).

Author(s)

Thomas Hielscher <t.hielscher@dkfz.de>

References

- Friedman, J., Hastie, T. and Tibshirani, R. (2008) *Regularization Paths for Generalized Linear Models via Coordinate Descent*, <https://web.stanford.edu/~hastie/Papers/glmnet.pdf>
Journal of Statistical Software, Vol. 33(1), 1-22 Feb 2010
<https://www.jstatsoft.org/v33/i01/>
- Simon, N., Friedman, J., Hastie, T., Tibshirani, R. (2011) *Regularization Paths for Cox's Proportional Hazards Model via Coordinate Descent*, *Journal of Statistical Software*, Vol. 39(5) 1-13
<https://www.jstatsoft.org/v39/i05/>
- Porzelius, C., Binder, H., and Schumacher, M. (2009) *Parallelized prediction error estimation for evaluation of high-dimensional models*, *Bioinformatics*, Vol. 25(6), 827-829.
- Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

See Also

[predictProb.glmnet](#), [peperr](#), [glmnet](#)

stabpath	<i>Stability path for glmnet models</i>
----------	---

Description

The function calculates the stability path for glmnet models, e.g. the selection probabilities of the features along the range of regularization parameters.

Usage

```
stabpath(
  y,
  x,
  size = 0.632,
  steps = 100,
  weakness = 1,
  mc.cores = getOption("mc.cores", 2L),
  ...
)
```

Arguments

y response variable. Like for the `glmnet` function: Quantitative for `family="gaussian"` or `family="poisson"` (non-negative counts). For `family="binomial"` should be either a factor with two levels, or a two-column matrix of counts or proportions. For `family="multinomial"`, can be a `nc >= 2` level factor, or a matrix with `nc` columns of counts or proportions. For `family="cox"`, `y` should be a two-column matrix with columns named `'time'` and `'status'`. The latter is a binary variable, with `'1'` indicating death, and `'0'` indicating right censored. The function `Surv()` in package `survival` produces such a matrix

x	input matrix. Like for the glmnet function: of dimension nobs x nvars; each row is an observation vector. Can be in sparse matrix format (inherit from class "sparseMatrix" as in package Matrix; not yet available for family="cox")
size	proportion of samples drawn in every subsample used for the stability selection.
steps	number of subsamples used for the stability selection.
weakness	weakness parameter used for the randomised lasso as described in Meinshausen and Bühlmann (2010). For each subsample the features are reweighted by a random weight uniformly sampled in [weakness,1]. This additional randomisation leads to a more consistent estimation of the stable set of features.
mc.cores	number of cores used for the parallelization. For unix like system the parallelization is done by forking using the function mclapply. For windows systems socket cluster are used.
...	further arguments that are passed to the glmnet function.

Value

	an object of class "stabpath", which is a list of three objects
fit	the fit object of class "glmnet" as returned from the glmnet function when applied to the complete data set.
stabpath	a matrix which represents the stability path.
qs	a vector holding the values of the average number of non-zero coefficients w.r.t to the lambdas in the regularization path.

Author(s)

Martin Sill <m.sill@dkfz.de>

References

Meinshausen N. and Bühlmann P. (2010), *Stability Selection*, *Journal of the Royal Statistical Society: Series B (Statistical Methodology)* Volume 72, Issue 4, pages 417–473.

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

See Also

[glmnet](#), [stabsel](#), [plot.stabpath](#)

Examples

```
## Not run:
#gaussian
set.seed(1234)
x <- matrix(rnorm(100*1000,0,1),100,1000)
y <- x[1:100,1:1000]%% c(rep(2,5),rep(-2,5),rep(.1,990))
```

```

res <- stabpath(y,x,weakness=1,mc.cores=2)
plot(res)

#binomial
y=sample(1:2,100,replace=TRUE)
res <- stabpath(y,x,weakness=1,mc.cores=2,family="binomial")
plot(res)

#multinomial
y=sample(1:4,100,replace=TRUE)
res <- stabpath(y,x,weakness=1,mc.cores=2,family="multinomial")
plot(res)

#poisson
N=100; p=1000
nzc=5
x=matrix(rnorm(N*p),N,p)
beta=rnorm(nzc)
f = x[,seq(nzc)]%*%beta
mu=exp(f)
y=rpois(N,mu)
res <- stabpath(y,x,weakness=1,mc.cores=2,family="poisson")
plot(res)

#Cox
library(survival)
set.seed(10101)
N=100;p=1000
nzc=p/3
x=matrix(rnorm(N*p),N,p)
beta=rnorm(nzc)
fx=x[,seq(nzc)]%*%beta/3
hx=exp(fx)
ty=rexp(N,hx)
tcens=rbinom(n=N,prob=.3,size=1)
y=cbind(time=ty,status=1-tcens)
res <- stabpath(y,x,weakness=1,mc.cores=2,family="cox")
plot(res)

## End(Not run)

```

stabsel

function to estimate a stable set of variables

Description

Given a desired type I error rate and a stability path calculated with `stability.path` the function selects a stable set of variables.

Usage

```
stabsel(x, error = 0.05, type = c("pfer", "pcer"), pi_thr = 0.6)
```

Arguments

x	an object of class "stabpath" as returned by the function stabpath.
error	the desired type I error level w.r.t. to the chosen type I error rate.
type	The type I error rate used for controlling the number falsely selected variables. If type="pfer" the per-family error rate is controlled and error corresponds to the expected number of type I errors. Selecting type="pfer" and error in the range of $0 > \text{error} < 1$ will control the family-wise error rate, i.e. the probability that at least one variable in the estimated stable set has been falsely selected. If type="pcer" the per-comparison error rate is controlled and error corresponds to the expected number of type I errors divided by the number variables.
pi_thr	the threshold used for the stability selection, should be in the range of $0.5 > \text{pi_thr} < 1$.

Value

a list of four objects	
stable	a vector giving the positions of the estimated stable variables
lambda	the penalization parameter used for the stability selection
lpos	the position of the penalization parameter in the regularization path
error	the desired type I error level w.r.t. to the chosen type I error rate
type	the type I error rate

Author(s)

Martin Sill \ <m.sill@dkfz.de>

References

Meinshausen N. and Bühlmann P. (2010), *Stability Selection*, *Journal of the Royal Statistical Society: Series B (Statistical Methodology)* Volume 72, Issue 4, pages 417–473.

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

See Also

[plot.stabpath](#), [stabpath](#)

Examples

```
## Not run:
#gaussian
set.seed(1234)
x=matrix(rnorm(100*1000,0,1),100,1000)
y <- x[1:100,1:1000]%*%c(rep(2,5),rep(-2,5),rep(.1,990))
res <- stabpath(y,x,weakness=1,mc.cores=2)
stabsel(res,error=0.05,type="pfer")

## End(Not run)
```

summary.intsearch	<i>Summary method for interval search models</i>
-------------------	--

Description

Produces a summary of a fitted interval search model

Usage

```
## S3 method for class 'intsearch'
summary(
  object,
  digits = max(3, getOption("digits") - 3),
  verbose = TRUE,
  first.n = 5,
  ...
)
```

Arguments

object	an object of class intsearch as returned by the function EPSGO.
digits	digits after the comma
verbose	default set to TRUE.
first.n	show first.n entries , default 5.
...	additional argument(s)

Value

A list of following elements

info	a data frame of four objects for optimal models <ul style="list-style-type: none"> • alpha - a vector of alphas • lambda - a vector of penalization parameter lambda • deviances - a vector of deviances
------	---

	• n.features -a vector of number of features selected in each optimal model
opt.alpha	an optimal value for alpha
opt.lambda	an optimal value for lambda
opt.error	an optimal value for error, hier minimal deviance
opt.models	a list of optimal models with the same optimal error

Author(s)

Natalia Becker \<natalia.becker@dkfz.de>

References

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

See Also

[EPSGO,plot.sum.intsearch](#)

tune.glmnet.interval *Wrapper function for glmnet objects.*

Description

Wrapper function for glmnet objects used by EPSGO function. This function is mainly used within the function [EPSGO](#)

Usage

```
tune.glmnet.interval(
  parms,
  x,
  y,
  weights,
  offset = NULL,
  lambda = NULL,
  type.measure = c("mse", "deviance", "class", "auc", "mae"),
  seed = 12345,
  nfolds = 10,
  foldid = NULL,
  grouped = TRUE,
  type.min = c("lambda.min", "lambda.1se"),
  family,
  verbose = FALSE,
  ...
)
```

Arguments

parms	tuning parameter alpha for glmnet object
x, y	x is a matrix where each row refers to a sample and each column refers to a gene; y is a factor which includes the class for each sample
weights	observation weights. Can be total counts if responses are proportion matrices. Default is 1 for each observation
offset	A vector of length nobs that is included in the linear predictor (a nobs x nvars matrix for the "multinomial" family). Useful for the "poisson" family (e.g. log of exposure time), or for refining a model by starting at a current fit. Default is NULL. If supplied, then values must also be supplied to the predict function.
lambda	A user supplied lambda sequence. Typical usage is to have the program compute its own lambda sequence based on nlambda and lambda.min.ratio. Supplying a value of lambda overrides this. WARNING: use with care. Do not supply a single value for lambda (for predictions after CV use predict() instead). Supply instead a decreasing sequence of lambda values. glmnet relies on its warm starts for speed, and it's often faster to fit a whole path than compute a single fit.
type.measure	loss to use for cross-validation. Currently five options, not all available for all models. The default is type.measure="deviance", which uses squared-error for gaussian models (a.k.a type.measure="mse" there), deviance for logistic and poisson regression, and partial-likelihood for the Cox model. type.measure="class" applies to binomial and multinomial logistic regression only, and gives misclassification error. type.measure="auc" is for two-class logistic regression only, and gives area under the ROC curve. type.measure="mse" or type.measure="mae" (mean absolute error) can be used by all models except the "cox"; they measure the deviation from the fitted mean to the response.
seed	seed
nfolds	number of cross-validation's folds, default 10.
foldid	an optional vector of values between 1 and nfolds identifying what fold each observation is in. If supplied, nfolds can be missing.
grouped	This is an experimental argument, with default TRUE, and can be ignored by most users. For all models except the "cox", this refers to computing nfolds separate statistics, and then using their mean and estimated standard error to describe the CV curve. If grouped=FALSE, an error matrix is built up at the observation level from the predictions from the nfolds fits, and then summarized (does not apply to type.measure="auc"). For the "cox" family, grouped=TRUE obtains the CV partial likelihood for the Kth fold by subtraction; by subtracting the log partial likelihood evaluated on the full dataset from that evaluated on the (K-1)/K dataset. This makes more efficient use of risk sets. With grouped=FALSE the log partial likelihood is computed only on the Kth fold
type.min	parameter for choosing optimal model: 'lambda.min' - value of lambda that gives minimum mean cross-validated error (cvm). 'lambda.1se' - largest value of lambda such that error is within one standard error of the minimum.
family	family of the model, i.e. cox, glm,...
verbose	verbose
...	Further parameters

Value

q.val	minimal value of Q.func on the interval defined by bounds. Here, q.val is minimum mean cross-validated error (cvm)
model	model list <ul style="list-style-type: none">• alpha - optimal alpha• lambda - optimal lambda• nfolds - cross-validation's folds• cvreg - cv.glmnet object for optimal alpha• fit - glmnet object for optimal alpha and optimal lambda

Author(s)

Natalia Becker natalia.becker at dkfz.de

References

Sill M., Hielscher T., Becker N. and Zucknick M. (2014), *c060: Extended Inference with Lasso and Elastic-Net Regularized Cox and Generalized Linear Models*, *Journal of Statistical Software*, Volume 62(5), pages 1–22. <https://doi.org/10.18637/jss.v062.i05>.

See Also

[EPSGO](#)

Index

- * **classification**
 - aggregation.auc, 2
 - * **coefficient**
 - Plot.coef.glmnet, 13
 - * **graphs**
 - EPSGO, 7
 - * **iteration**
 - balancedFolds, 4
 - EPSGO, 7
 - tune.glmnet.interval, 25
 - * **models**
 - aggregation.auc, 2
 - balancedFolds, 4
 - complexity.glmnet, 6
 - EPSGO, 7
 - fit.glmnet, 11
 - PLL.coxnet, 12
 - Plot.peperr.curves, 14
 - predictProb.coxnet, 19
 - tune.glmnet.interval, 25
 - * **multivariate**
 - balancedFolds, 4
 - EPSGO, 7
 - tune.glmnet.interval, 25
 - * **optimize**
 - balancedFolds, 4
 - EPSGO, 7
 - tune.glmnet.interval, 25
 - * **path**
 - Plot.coef.glmnet, 13
 - * **penalized**
 - complexity.glmnet, 6
 - fit.glmnet, 11
 - PLL.coxnet, 12
 - predictProb.coxnet, 19
 - * **plot**
 - plot.sum.intsearc, 18
 - * **regression**
 - aggregation.auc, 2
 - complexity.glmnet, 6
 - fit.glmnet, 11
 - PLL.coxnet, 12
 - Plot.peperr.curves, 14
 - predictProb.coxnet, 19
 - * **selection**
 - plot.stabpath, 16
 - stabpath, 20
 - stabsel, 22
 - * **stability**
 - plot.stabpath, 16
 - stabpath, 20
 - stabsel, 22
 - * **summary**
 - summary.intsearch, 24
 - * **survival**
 - PLL.coxnet, 12
 - Plot.peperr.curves, 14
 - predictProb.coxnet, 19
 - * **system**
 - coef.sum.intsearch, 5
- aggregation.auc, 2
- balancedFolds, 4
- coef.sum.intsearch, 5
- complexity.glmnet, 6
- cv.glmnet, 7
- EPSGO, 5, 7, 19, 25, 27
- fit.glmnet, 11
- glmnet, 12, 20, 21
- peperr, 3, 7, 12, 15, 20
- PLL.coxnet, 12
- Plot.coef.glmnet, 13
- Plot.peperr.curves, 14
- plot.stabpath, 16, 21, 23

plot.sum.intsearc, [18](#)
plot.sum.intsearch, [5](#), [25](#)
plot.sum.intsearch(plot.sum.intsearc),
 [18](#)
predictProb.coxnet, [19](#)
predictProb.glmnet, [20](#)
predictProb.glmnet
 (predictProb.coxnet), [19](#)

stabpath, [18](#), [20](#), [23](#)
stabsel, [18](#), [21](#), [22](#)
summary.intsearch, [5](#), [18](#), [19](#), [24](#)

tune.glmnet.interval, [25](#)