

Package ‘salmonMSE’

March 21, 2026

Title Management Strategy Evaluation for Salmon Species

Version 1.0.0

Date 2026-03-20

Maintainer Quang Huynh <quang@bluematterscience.com>

Description Simulation tools to evaluate the long-term effects of salmon management strategies, including a combination of habitat, harvest, and habitat actions. The stochastic age-structured operating model accommodates complex life histories, including freshwater survival across early life stages, juvenile survival and fishery exploitation in the marine life stage, partial maturity by age class, and fitness impacts of hatchery programs on natural spawning populations. 'salmonMSE' also provides an age-structured conditioning model to develop operating models fitted to data.

License GPL (>= 3)

Depends R (>= 3.5.0)

Imports abind, MSEtool (>= 3.7.2), RTMB (>= 1.9), dplyr, ggplot2, grDevices, gsl, methods, reshape2, rlang, rmarkdown, stats, utils

Suggests ggrepel, rstan, scales, testthat (>= 3.0.0), tmbstan

Encoding UTF-8

LazyData yes

LazyLoad yes

RoxygenNote 7.3.3

URL <https://docs.salmonmse.com/>,
<https://github.com/Blue-Matter/salmonMSE>

BugReports <https://github.com/Blue-Matter/salmonMSE/issues>

NeedsCompilation no

Author Quang Huynh [aut, cre] (ORCID: <<https://orcid.org/0000-0001-7835-4376>>)

Repository CRAN

Date/Publication 2026-03-21 00:40:03 UTC

Contents

AHA	2
Bio-class	3
calc_ref	4
calc_smolt	7
calc_Smsy_Ricker	8
calc_SRR	8
calc_SRRpars	9
check_SOM	10
CM2SOM	11
compare	12
compare_spawnners	13
compare_statevar_ts	14
fit_CM	15
get_report	21
glossary	24
Habitat-class	25
Harvest-class	26
Hatchery-class	27
Historical-class	29
make_Harvest_MMP	30
plot_decision_table	32
plot_LHG	33
plot_statevar_ts	34
plot_tradeoff	36
PNI50	38
report	39
report_CM	40
salmonMSE	41
salmonMSE_env	42
SHist-class	42
SMSE-class	44
SOM-class	47
Index	48

 AHA

All-H Analyzer

Description

Wrapper function for an implementation of All-H Analyzer ([AHA](#)) in R. Can be used to compare outputs between AHA and salmonMSE.

Usage

```
AHA(SOM, ngen = 100, silent = FALSE)
```

Arguments

SOM	An object of class SOM
ngen	Integer, the number of generations for which to run the simulation
silent	Logical, indicates whether to silence messages to the R console

Value

A named list containing vectors of state variables (by simulation, population, and generation). See [SMSE](#) object description.

References

Hatchery Scientific Review Group. 2020. All-H Analyzer Tool Guide and Documentation. May 2020.

Bio-class	<i>Class "Bio"</i>
-----------	--------------------

Description

The component of the operating model that controls biological dynamics, i.e., natural production.

Details

Various parameters can be stochastic (length `nsim`) or input as a single numeric (value identical across all simulations).

Slots

Name Character. Identifying name

maxage Integer. The maximum age of the population age structure.

n_g Integer. Number of life history groups within a cohort. Life history groups (LHGs) are sub-units of a cohort that have different biological parameters, e.g., survival, but the egg production and smolt production in the next generation is calculated from the sum across life history groups. Default is 1.

p_LHG The proportion of the total egg production assigned to each life history group within a cohort. For example, if `Bio@n_g <- 2`, then `Bio@p_LHG <- c(0.9, 0.1)`, then 90 percent of the egg production in the first population is assigned to the first life history group and ten percent to the second LHG. Default is `rep(1/Bio@n_g, Bio@n_g)`

p_mature Either vector by age (length `maxage`) or an array with dimension `[nsim, maxage, proyears]`. The proportion mature by age.

SRrel Character, stock-recruit relationship for density-dependent smolt production from fry. Either "BH" (Beverton-Holt) or "Ricker". Not used if habitat component is used. See `Habitat` object.

- capacity** Vector length *nsim*. The asymptote of the Beverton-Holt stock-recruit function, or the Ricker maximum for density-dependent natural smolt production from egg production. **Units of smolts.** Not used if habitat component is used.
- kappa** Vector length *nsim*. The adult productivity ratio for the stock-recruit function. **Units of recruits per spawner.** Natural per-capita production of recruits as the population approaches zero (density-independent component). In stage-based models, equivalent to the product of smolt productivity (smolts per spawner) and marine survival. Not used if habitat component is used.
- Smax** Vector length *nsim*. The egg production that maximizes smolt production in the Ricker stock-recruit function. **Units of eggs.** Equivalent to units of spawners if *fec* = 1 for all spawners. Not used if habitat component is used.
- phi** Optional parameter, vector length *nsim*. Egg production per smolt at unfished replacement. **Units of egg per smolt.** The alpha parameter of the stock-recruit function will be the ratio of kappa and phi. In stage-based models, this is the product of marine survival, fecundity, and proportion female. If not provided, phi will be calculated from *Mjuv_NOS*, *p_mature*, *s_enroute*, *p_female*, *fec*, and *p_LHG* corresponding to the first year and weighted by life history groups. Not used if habitat component is used.
- Mjuv_NOS** Either vector by age (length *maxage-1*) or an array with dimension [*nsim*, *maxage-1*, *proyears*, *n_g*]. Natural mortality of immature natural origin fish, the value for the first age represents natural mortality from age 1 to 2, second age is mortality from age 2 to 3, and so on. To replicate the SAR parameter of a stage-specific model, set *Mjuv_NOS*[*a*] = $-\log(\text{SAR})$ where *a* is the age class prior to maturation (and zero for all other ages).
- fec** Vector by age (length *maxage*) or an array with dimension [*nsim*, *maxage*, *proyears*]. Female fecundity of natural origin spawners.
- p_female** Numeric. The proportion of females in the spawning population. Default is 0.5. Can also be a vector [*maxage*] (for situations where older spawners are predominantly female)
- s_enroute** Numeric. Survival of escapement to the spawning grounds (for spawning and for broodtake). Default is 1.

Creating Object

Objects can be created by calls of the form `new("Bio")`

Examples

```
showClass("Bio")
```

Description

Calculate MSY and Sgen reference points for the operating model. Uses the biological parameters (maturity, natural mortality) in the last year of the projection.

- `calc_MSU()` calculates the MSY reference points from a set of biological and fishery parameters
- `calc_Sgen()` calculates the Sgen, the spawner abundance that would reach the spawner abundance at MSY after one generation without fishing
- `calc_ref()` is a wrapper function that calculates MSY and Sgen for an operating model

Usage

```
calc_ref(SOM, rel_F, check = TRUE, maximize = c("MSY", "MER"))
```

```
calc_MSU(  
  Mjuv,  
  fec,  
  p_female,  
  rel_F,  
  vulPT,  
  vult,  
  p_mature,  
  s_enroute,  
  n_g = 1,  
  p_LHG = 1,  
  SRRpars,  
  maximize = c("MSY", "MER"),  
  F_search = c(1e-08, 5)  
)
```

```
calc_Sgen(  
  Mjuv,  
  fec,  
  p_female,  
  rel_F,  
  vulPT,  
  vult,  
  p_mature,  
  s_enroute,  
  n_g = 1,  
  p_LHG = 1,  
  SRRpars,  
  SMSY,  
  F_search = c(1e-08, 100),  
  nyears  
)
```

Arguments

SOM	An object of class SOM
rel_F	Numeric length 2, indicates the relative effort in the preterminal and terminal fisheries, with a maximum value of 1. The default is $c(0, 1)$ which indicates a yield calculation with only the terminal fishery.
check	Logical, whether to check the SOM object using check_SOM()
maximize	Character, whether the MSY calculation is the optimum that maximizes catch ("MSY") or excess recruitment ("MER"). The two methods should be equivalent when $rel_F = c(0, 1)$.
Mjuv	Numeric maxage for juvenile natural mortality. Can be a matrix [maxage, n_g].
fec	Numeric maxage for fecundity. Can be a matrix [maxage, n_g].
p_female	Numeric for proportion female spawners
vu1PT	Numeric maxage for preterminal vulnerability at age
vu1T	Numeric maxage for terminal vulnerability at age
p_mature	Numeric maxage for maturity proportions at age. Can be a matrix [maxage, n_g].
s_enroute	Numeric for en-route survival of escapement to spawning grounds
n_g	Integer, number of life history groups within a cohort
p_LHG	Numeric n_g for proportion of the total egg production assigned to each life history group within a cohort
SRRpars	Data frame, one row, that contains the stock recruit parameters that predicts density-dependent survival at the egg-smolt life stage
F_search	Numeric, length 2 for the range of F values to search for the instantaneous fishing mortality that produces MSY
SMSY	Numeric, spawning abundance at MSY
nyears	Integer, number of years to project the population with no fishing to reach SMSY. Default is the minimum age of maturity.

Value

- `calc_MSY` returns a vector of various state variables (catch, exploitation rate, egg production, spawners) at MSY
- `calc_Sgen` returns a numeric
- `calc_ref` returns a list by stock, each containing a matrix of MSY state variables and Sgen by simulation

See Also

[calc_Smsy_Ricker\(\)](#)

calc_smolt	<i>Smolt production</i>
------------	-------------------------

Description

Calculate smolt production from base stock-recruit parameters and fitness loss

Usage

```
calc_smolt(
  N1,
  N2 = N1,
  kappa,
  capacity,
  Smax,
  phi = 1,
  fitness_loss = 1,
  SRrel = c("BH", "Ricker"),
  per_recruit = FALSE
)
```

Arguments

N1	Egg production for the density-independent component of the stock-recruit relationship. Can be the number of spawners if $\phi = 1$ and Smax is in units of spawners.
N2	Egg production for the density-dependent component of the stock-recruit relationship (only used if per_recruit = FALSE)
kappa	Base productivity parameter
capacity	Base capacity parameter if SRrel = "BH"
Smax	Base Smax parameter if SRrel = "Ricker"
phi	Unfished egg per smolt ($1/\phi$ is the replacement line)
fitness_loss	Survival term to reduce smolt production due to fitness, between 0-1
SRrel	Character for the stock-recruit function
per_recruit	Logical, whether N1 is a per recruit quantity (TRUE) or in absolute numbers (FALSE)

Value

Numeric

calc_Smsy_Ricker *Ricker reference points*

Description

Compute reference points (Umsy, Smsy, and Sgen) from Ricker stock-recruit function based on Scheuerell (2016).

Usage

```
calc_Smsy_Ricker(loga, b)
```

```
calc_Umsy_Ricker(loga)
```

```
calc_Sgen_Ricker(loga, b)
```

Arguments

loga	Numeric, alpha parameter (returns per spawner) in the Ricker function: $R = S \exp(\log(a) - bS)$ where S is the number of spawners and R is the return
b	Numeric, beta parameter

Value

All three functions return a numeric

References

Scheuerell, M.D. 2016. An explicit solution for calculating optimum spawning stock size from Ricker's stock recruitment model. PeerJ 4:e1623. doi:10.7717/peerj.1623

See Also

[calc_ref\(\)](#)

calc_SRR *Calculate abundance from density-dependent mortality*

Description

Calculates the abundance of survivors after applying either a Beverton-Holt or Ricker stock-recruit relationship.

Usage

```
calc_SRR(N1, N2 = N1, p, capacity, type = c("BH", "Ricker", "HS"))
```

Arguments

N1	Numeric, the initial abundance that scales the density-independent survival term
N2	Numeric, the initial abundance that scales the density-dependent survival term
p	Numeric, the productivity parameter that sets the maximum survival as the initial abundance approaches zero
capacity	Numeric, the capacity parameter that set the maximum survivors
type	Character, the functional form of the stock-recruit relationship

Details

The Beverton-Holt stock recruit relationship is of the following form:

$$\text{Smolt} = \frac{\alpha N_1}{1 + \beta N_2}$$

where $\alpha = P$, $\beta = P/C$.

The Ricker stock recruit relationship is of the following form:

$$\text{Smolt} = \alpha N_1 \exp(-\beta N_2)$$

where $\alpha = P$, $\beta = P/(Ce)$, e is Euler's number.

Productivity P is in terms of abundance per unit of N_1 and N_2 .

The hockey stick is of the following form:

$$\text{Smolt} = \begin{cases} pN_1 & , N_1 \leq \frac{N_1}{N_2} \times C \\ \frac{N_1}{N_2} \times C & , \text{otherwise} \end{cases}$$

Value

Numeric, the abundance of survivors

See Also

[calc_SRRpars\(\)](#)

calc_SRRpars

Convert density-dependent survival parameters

Description

Converts from capacity/productivity parameters to alpha/beta stock-recruit parameters where productivity is in terms of smolts per spawner and alpha is terms of smolts per egg.

Usage

```
calc_SRRpars(p, capacity, f = 1, p_female = 1, type = c("BH", "Ricker", "HS"))
```

Arguments

p	Numeric, the productivity parameter that sets the maximum survival as the initial abundance approaches zero
capacity	Numeric, the capacity parameter that set the maximum survivors
f	Fecundity, the spawning output per mature female
p_female	The proportion of females per spawner
type	Character, the functional form of the stock-recruit relationship

Details

$$\alpha = \frac{P}{f \times p_{female}}$$

For the Beverton-Holt stock recruit relationship:

$$\beta = \frac{\alpha}{C}$$

For the Ricker stock recruit relationship:

$$\beta = \frac{\alpha}{C e}$$

, e is Euler's number.

Value

Numeric vector length 2 for alpha and beta value, respectively

See Also

[calc_SRR\(\)](#)

check_SOM

Check inputs to SOM object

Description

Ensures that the slots in the [SOM](#) object have the correct dimensions. Function will update some slots to their full dimensions.

Usage

```
check_SOM(SOM, silent = FALSE)
```

Arguments

SOM	SOM object
silent	Logical, whether to report progress in console

Value

Updated SOM object with full dimensions in various slots

CM2SOM	<i>Convert conditioning model to operating model</i>
--------	--

Description

Creates an operating model from MCMC samples and data inputs of the conditioning model. Management actions for habitat, hatchery production, and harvest still need to be specified in the operating model.

Note: the function assumes the maturity values in the last conditioning year for the projection, which are likely not well informed by CWT data. Consider updating the maturity using some historical average (e.g., across most recent completed brood years).

Usage

```
CM2SOM(stanfit, sims, nsim = 2, seed = 1, proyears = 40)
```

Arguments

stanfit	Output from <code>sample_CM()</code>
sims	Optional, a vector of integers indicating the MCMC iterations to convert to operating model simulations. Otherwise, use argument <code>nsim</code> in order to sample a subset of the MCMC.
nsim	Integer, total number of simulations in the operating model. Only used if <code>sims</code> is missing.
seed	Integer, seed for sampling the MCMC output. Only used if <code>sims</code> is missing.
proyears	Integer, the number of projection years in the operating model

Value

SOM object.

`compare`*Compare scenarios in markdown*

Description

Generate a markdown report for multiple model runs to compare scenarios. 3-5 is likely the ideal number of scenarios for comparison.

Usage

```
compare(  
  SMSE_list,  
  names,  
  col_vec,  
  filename = "SMSEcompare",  
  dir = tempdir(),  
  open_file = TRUE,  
  render_args = list(),  
  ...  
)
```

Arguments

<code>SMSE_list</code>	List of SMSE objects
<code>names</code>	Character vector length(<code>SMSE_list</code>) to label individual model runs
<code>col_vec</code>	Character vector length(<code>SMSE_list</code>) for custom colour schemes for comparing across model scenarios in figures
<code>filename</code>	Character string for the name of the markdown and HTML files.
<code>dir</code>	The directory in which the markdown and HTML files will be saved.
<code>open_file</code>	Logical, whether the HTML document is opened after it is rendered.
<code>render_args</code>	List of arguments to pass to rmarkdown::render() .
<code>...</code>	Additional arguments (not used)

Value

Returns invisibly the output of [rmarkdown::render\(\)](#), typically the path of the output file

See Also

[report\(\)](#)

compare_spawnners	<i>Compare simulation runs</i>
-------------------	--------------------------------

Description

Create figures that compare results across two dimensions

Usage

```
compare_spawnners(SMSE_list, Design, prop = FALSE, FUN = median)
```

```
compare_fitness(SMSE_list, Design, FUN = median)
```

```
compare_escapement(SMSE_list, Design, FUN = median)
```

Arguments

SMSE_list A list of SMSE objects returned by [salmonMSE\(\)](#)

Design A data frame with two columns that describes the factorial design of the simulations. Used to label the figure. Rows correspond to each object in SMSE_list. There two columns are variables against which to plot the result. See example in <https://docs.salmonmse.com/articles/decision-table.html>.

prop Logical, whether to plot absolute numbers over proportions

FUN Summarizing function across simulations, typically `stats::median()` or `base::mean()`

Details

- [compare_spawnners\(\)](#) generates a time series of the composition of spawners
- [compare_fitness\(\)](#) generates a time series of metrics (fitness, PNI, pHOS, and pWILD) related to hatchery production
- [compare_escapement\(\)](#) generates a time series of the proportion of spawners and broodtake to escapement

Value

A ggplot object

compare_statevar_ts *Compare state variables from simulation runs*

Description

Compare outputs from multiple simulations to evaluate performance across states of nature and/or management levers (identified by colour):

- `compare_statevar_ts()` produces a time series for all simulations, or with medians and 95th percentile intervals
- `compare_statevar_hist()` produces a histogram or density plot across all simulations for a particular year

Usage

```
compare_statevar_ts(  
  SMSE_list,  
  var = "PNI",  
  s = 1,  
  figure = TRUE,  
  xlab = "Projection Year",  
  quant = FALSE,  
  ylab = var,  
  ylim,  
  agg.fun = sum,  
  names,  
  col_vec,  
  ...  
)  
  
compare_statevar_hist(  
  SMSE_list,  
  var = "PNI",  
  s = 1,  
  y,  
  figure = TRUE,  
  xlab = var,  
  names,  
  col_vec,  
  type = c("density", "hist"),  
  ...  
)
```

Arguments

`SMSE_list` List of SMSE objects for multiple model runs returned by `salmonMSE()`

var	Character. Slot for the state variable in SMSE object. See <code>slotNames(SMSE)</code> for options. Additional supported options are: "ESS" (egg-smolt survival), "pbrood" (broodtake to escapement ratio), "pNOSesc" (NOS/natural escapement), "pHOSesc" (HOS/hatchery escapement), Total Spawners (NOS + HOS), NOS/SMSY, S/SMSY, and NOS/Sgen.
s	Integer. Population index for multi-population model (e.g., $s = 1$ is the first population in the model)
figure	Logical, whether to generate a figure (set to FALSE if only using the function to return the data matrix)
xlab	Character. Name of time variable for the figure
quant	Logical, whether to plot individual simulations (FALSE) or the median with 95 percent confidence intervals (TRUE)
ylab	Character. Name of the state variable for the figure
ylim	Vector. Y-axis limits
agg.fun	Function. Defines how to aggregate state variables that are reported by age. Typically, <code>sum</code> is used but <code>max</code> is also possible for reporting apical exploitation rates.
names	Character vector <code>length(SMSE_list)</code> to label individual model runs
col_vec	Character vector <code>length(SMSE_list)</code> for custom colour schemes for comparing across model scenarios in figures
...	Additional arguments to base plot function
y	Integer. Projection year for the state variable to plot the histogram. If missing, the last projection year is used.
type	Character, whether to generate a density figure or histogram

Value

An array invisibly. Also generates base graphics if `figure = TRUE`

See Also

[plot_statevar_ts\(\)](#) [compare\(\)](#)

fit_CM

Fit conditioning model to historical data

Description

Bayesian stock reconstruction model of natural and hatchery origin fish population. Maturity and age-1 natural mortality are estimated from coded wire tag catch and escapement at age. A separate series of observed escapement, and hatchery releases reconstructs the population of interest, informed by natural mortality and maturity from CWT (Korman and Walters 2024). The model estimates time-varying maturity rate as well as time-varying ocean survival as a linear model of

covariates (separate covariates for age 1 vs. ages 2+). The model can include either a preterminal juvenile fishery, terminal return fishery, or both (see Data and start sections of the documentation).

fit_CM() generates the RTMB model from data which can then be passed to sample_CM() to run the MCMC in Stan. Generate a markdown report with report_CM().

More information is available on the [salmonMSE](#) website

Usage

```
fit_CM(
  data,
  start = list(),
  map = list(),
  lower = list(),
  upper = list(),
  do_fit = TRUE,
  silent = TRUE,
  control = list(eval.max = 1e+05, iter.max = 1e+05),
  ...
)

sample_CM(fit, ...)
```

Arguments

data	A list containing data inputs. See details.
start	An optional list containing parameter starting values. See details.
map	An optional list that describes how parameters are fixed in the model. See TMB::MakeADFun() .
lower	Named list containing lower bounds for parameters. See details.
upper	Named list containing upper bounds for parameters. See details.
do_fit	Logical, whether to do the fit and estimate the Hessian.
silent	Logical, whether to silence output from RTMB to the console.
control	List, control argument to pass to stats::nlminb() .
...	For fit_CM, arguments to RTMB::MakeADFun() . For sample_CM, arguments to rstan::sampling()
fit	List of output from fit_CM()

Value

- fit_CM() returns a named list containing the RTMB model (obj), nlminb output (opt), standard errors (SD), and parameter bounds (lower and upper)
- sample_CM() returns a stanfit object containing the MCMC chains

Data

Data should be passed through a named list with the following entries.

- Nages Integer, number of age classes in the model
- Ldyr Integer, number of years in the model
- lht Integer, life history type. Should be 1 for now
- n_r Integer, number of release strategies for CWT, subset of a hatchery-origin brood year that differ in maturity rate. Default is 1.
- cwtrelease Matrix [Ldyr, n_r], coded wire tag (CWT) releases by **release year and release strategy**
- cwtesc Array [Ldyr, Nages, n_r]. CWT escapement by **release year, age, and release strategy** (assumes broodyear is release year minus 1). Poisson likelihood.
- cwtcatPT Array [Ldyr, Nages, n_r]. CWT preterminal catch (juvenile fish), by **release year, age, and release strategy**. Poisson likelihood. Set all values to zero to turn off parameters related to the preterminal fishery.
- cwtcatT Array [Ldyr, Nages, n_r]. CWT terminal catch (returning, mature fish), by **release year, age, and release strategy**. Poisson likelihood. Set all values to zero to turn off parameters related to the terminal fishery.
- bvulPT Vector length Nages. Prior mean for the vulnerability at age to the preterminal fishery.
- bvulT Vector length Nages. Prior mean for the vulnerability at age to the terminal fishery.
- RelRegFPT Vector Ldyr. Trend in relative regional preterminal fishing mortality. Fishing mortality is estimated by estimating a scaling coefficient and annual deviations from this vector. Default is $\text{rep}(1, d\$Ldyr)$ (no prior trend) if cwtcatPT is provided, otherwise zero.
- RelRegFT Vector Ldyr. Trend in relative regional terminal fishing mortality. Default is $\text{rep}(1, d\$Ldyr)$ (no prior trend) if cwtcatT is provided, otherwise zero.
- bmat t Vector length Nages. Proportion maturity at age, base values for calculating the unfished replacement line. Also the prior means if year-specific maturity rates are estimated.
- mobase. Vector length Nages. Natural mortality at age, base values for calculating the unfished replacement line and the equilibrium spawners at age.
- covariate1 *Optional*. Matrix Ldyr, ncov1 of linear covariates that predict natural mortality for age 1.
- covariate *Optional*. Matrix Ldyr, ncov of linear covariates that predict natural mortality for ages 2+.
- hatchsurv Numeric, survival of hatchery releases into the smolt life stage. Density-independent. Default is 1. If less than 1, then hatchery origin fish have lower survival to age 2 (after first year of marine life stage) compared to natural origin fish.
- gamma *Optional*. Numeric, the relative spawning success of hatchery origin spawners. Default is 1.
- ssum Numeric, proportion of spawners that is female. Can also be a vector Nages
- fec Vector length Nages. Fecundity, egg production at age
- r_mat t Integer, the release strategy for which to use maturity parameter for the natural system. Default is 1.

- obsescape Vector length L_{dyr} by **return year**, total observed escapement from fisheries, i.e., return to river (all ages and both hatchery/natural fish). Lognormal likelihood.
- propwildspawn Vector length L_{dyr} by **return year**, proportion of the escapement that spawn (accounts for en-route mortality and broodtake)
- hatchrelease Vector length L_{dyr}+1 by **release year**, number of hatchery releases for the population. Default is zero.
- obs_pHOS *Optional*. Vector length L_{dyr} by **return year**, observations of proportion of hatchery origin spawners (census) (between 0-1) by *brood year*. Fitted to model with logistic-normal likelihood.
- pHOS_sd Numeric, logistic-normal standard deviation of pHOS observations. Default is 1.
- pHOS_init Numeric, initial pHOS for equilibrium abundance in the first year of the model. Default is 0.
- s_enroute Numeric, survival of escapement to spawning grounds. Default is 1.
- so_mu Numeric, the prior mean for spawners at unfished replacement in logspace. Default is $\log(3 * \max(\text{data\$obsescape}))$.
- so_sd Numeric, the prior standard deviation for spawners at unfished replacement in logspace. Default is 0.5.
- finitPT Numeric, initial preterminal fishing mortality for calculating the equilibrium juvenile proportions at age in the first year of the model. Default is 0. Set to "estimate" to allow the model to estimate the equilibrium condition.
- finitT Numeric, initial terminal fishing mortality for calculating the equilibrium juvenile proportions at age in the first year of the model. Default is 0. Set to "estimate" to allow the model to estimate the equilibrium condition.
- spawn_init Numeric, initial spawners to calculate equilibrium abundance in the first year of the model. Default is obsescape[1].
- cwtExp Numeric, the CWT expansion factor, typically the reciprocal of the catch sampling rate (higher factors for lower sampling rate). The model scales down the CWT predictions to match the observations. In other words, the model assumes that the CWT catch and escapement are not expanded. For example, cwtExp = 10 divides the CWT predictions by 10 for the likelihood. Default is 1. The Poisson distribution is used for the likelihood of the CWT observations, and the expansion parameter can be used to downweight the CWT likelihood relative to the escapement time series. However it requires adjustments of the CWT catches prior to fitting to ensure the proper population scale. If the expanded catch is 100, then the input CWT catch should be 10 and 50 with cwtExp of 10 and 2, respectively, to maintain the same population scale. The Poisson variance scales with the mean and is higher with cwtExp = 2.
- fitness Logical, whether to calculate fitness effects on survival. Default is FALSE.
- theta Vector length 2, the optimum phenotype value for the natural and hatchery environments. Default is 100 and 80, respectively. See [online article](#) for more information.
- rel_loss Vector length 3, the loss in fitness apportioned between the egg, fry (both prior to density-dependence), and smolt (after density-dependence) life stage. The three values should sum to 1.
- zbar_start Vector length 2, the mean phenotype of the spawners and broodtake in the natural and hatchery environment, respectively, at the start of the model. Default values of 100 and 100, implying maximum fitness at for the natural environment at the start of the model.

- `fitness_variance` Numeric. The variance (omega-squared) of the fitness function. Assumed identical between the natural and hatchery environments. Default is 100.
- `phenotype_variance` Numeric. The variance (sigma-squared) of the phenotypic trait (with optimum theta). Assumed identical between the natural and hatchery environments. Default is 10.
- `heritability` Numeric. The heritability (h-squared) of the phenotypic trait. Between 0-1. Default is 0.5.
- `fitness_floor` Numeric. The minimum fitness value in the natural and hatchery environments. Default is 0.5.

start

Starting values for parameters can be provided through a named list:

- `log_cr` Numeric, log of the compensation ratio (productivity). Default is 3.
- `log_so` Numeric, unfished spawners in logspace. Default is $\log(3 * \max(\text{data}\$obsescape))$.
- `moadd` Numeric, additive term to base natural mortality rate for age 1 juveniles. Default is zero.
- `wt` Vector Ldyr. Annual deviates in natural mortality during the freshwater life stage (affects egg to smolt survival). Estimated with normal prior with mean zero and standard deviation `p$wt_sd`. Default is zero.
- `wto` Vector Ldyr. Annual deviates in natural mortality for age 1 juveniles (marine life stage). Estimated with normal prior with mean zero and standard deviation `p$wto_sd`. Default is zero.
- `log_FbasePT` Numeric, scaling coefficient to estimate preterminal fishing mortality from `data$RelRegFPT`. Default is $\log(0.1)$.
- `log_FbaseT` Numeric, scaling coefficient to estimate preterminal fishing mortality from `data$RelRegFT`. Default is $\log(0.1)$.
- `log_fanomalyPT` Vector Ldyr. Annual lognormal deviates from $\exp(\log_FbasePT) * \text{data}\$RelRegFPT$ to estimate preterminal fishing mortality. Estimated with normal prior with mean zero and standard deviation `p$fanomaly_sd`. Default is zero.
- `log_fanomalyT` Vector Ldyr. Annual lognormal deviates from $\exp(\log_FbaseT) * \text{data}\$RelRegFT$ to estimate terminal fishing mortality. Estimated with normal prior with mean zero and standard deviation `p$fanomalyPT_sd`. Default is zero.
- `lnE_sd` Numeric, lognormal standard deviation of the observed escapement. Estimated with hierarchical $\text{gamma}(2, 5)$ prior. Default is 0.1.
- `wt_sd` Numeric, lognormal standard deviation of the egg to smolt (freshwater) natural mortality deviates. Estimated with hierarchical $\text{gamma}(2, 5)$ prior. Default is 1.
- `wto_sd` Numeric, lognormal standard deviation of the age 1 (marine) natural mortality deviates. Estimated with hierarchical $\text{gamma}(2, 5)$ prior. Default is 1.
- `fanomalyPT_sd` Numeric, lognormal standard deviation of `fanomalyPT`. Estimated with hierarchical $\text{gamma}(2, 5)$ prior. Default is 1.
- `fanomalyT_sd` Numeric, lognormal standard deviation of `fanomalyT`. Estimated with hierarchical $\text{gamma}(2, 5)$ prior. Default is 1.

- `logit_vulPT` Vector Nages-2 of preterminal vulnerability at age in logit space. Fixed to zero and one at age 1 and the maximum age, respectively. Default is `qlogis(data$bvul_PT[-c(1, data$Nages)])`.
- `logit_vulT` Vector Nages-2 of terminal vulnerability at age in logit space. Fixed to zero and one at age 1 and the maximum age, respectively. Default is `qlogis(data$bvul_T[-c(1, data$Nages)])`.
- `logit_matt` Matrix Ldyr, Nages-2 maturity by year and age in logit space. Maturity is fixed to zero and one at age 1 and the maximum age, respectively. Default is `matrix(qlogis(data$bmatt[-c(1, data$Nages)]), data$Ldyr, data$Nages-2, byrow = TRUE)`.
- `sd_matt` Vector Nages-2. Logit standard deviation of maturity (`logit_matt`) by age class. Default is 0.5.
- `b1` Vector `ncov1` of coefficients for linear covariates that predict natural mortality for age 1. Default is zero.
- `b` Vector `ncov` of coefficients for linear covariates that predict natural mortality for ages 2+. Default is zero.

Bounds

By default, the standard deviation parameters and parameters in normal space (e.g., `FbasePT`, `Fbase_T`) have a lower bound of zero. `moadd` has a lower bound of zero by default, but it is feasible that this parameter can be negative as well. Deviation parameters centred around zero are bounded between -3 to 3. The `log_cr` parameter has a lower bound of zero.

All other parameters are unbounded.

Covariates on natural mortality

Natural mortality is modeled as the sum of a base value M^{base} , additional scaling factor for age 1 M^{add} , a linear system of covariates X and coefficients b :

$$M_{y,a} = \begin{cases} M_a^{\text{base}} + M^{\text{add}} + \sum_j b_j^1 X_{y,j}^1 & a = 1 \\ M_a^{\text{base}} + \sum_j b_j X_{y,j} & a = 2, \dots, A \end{cases}$$

Author(s)

Q. Huynh from Stan code provided by J. Korman and C. Walters

References

Korman, J. and Walters, C. 2024. A life cycle model for Chinook salmon population dynamics. Canadian Contractor Report of Hydrography and Ocean Sciences 62: vi + 60 p.

See Also

[report_CM\(\)](#)

[CM2SOM\(\)](#)

get_report

Figures for conditioning model results

Description

Functions used by the markdown report to generate summary figures from the age-structured conditioning model

Usage

```

get_report(stanfit, sims, inc_warmup = FALSE)

get_CMdata(fit)

CM_trace(stanfit, vars, inc_warmup = FALSE)

CM_pairs(stanfit, vars = c("log_so", "log_cr"), inc_warmup = FALSE)

CM_fit_esc(report, d, year)

CM_fit_pHOS(report, d, year)

CM_fit_CWTesc(report, d, year1 = 1, rs_names)

CM_fit_CWTcatch(report, d, PT = TRUE, year1 = 1, rs_names)

CM_maturity(
  report,
  d,
  year1 = 1,
  r = 1,
  brood = TRUE,
  annual = FALSE,
  rs_names
)

CM_vul(report, type = c("vulPT", "vulT"))

CM_SRR(report, year1 = 1)

CM_prod(report, d, year1 = 1)

CM_Srep(report, d, year1 = 1, type = c("spawner", "egg"))

CM_M(report, year1 = 1, ci = TRUE)

CM_Megg(report, year1 = 1, ci = TRUE, surv = FALSE)

```

```

CM_Njuv(report, year1 = 1, ci = TRUE)
CM_recr(report, year1 = 1, ci = TRUE)
CM_esc(report, year1 = 1, ci = TRUE)
CM_F(report, PT = TRUE, year1 = 1, ci = TRUE)
CM_surv(report, year1 = 1, ci = TRUE)
CM_wt(stanfit, year1 = 1, ci = TRUE)
CM_surv2(report, year1 = 1, ci = TRUE, ylab = "Survival to age 2")
CM_wto(stanfit, year1 = 1, ci = TRUE)

CM_ER(
  report,
  brood = TRUE,
  type = c("PT", "T", "all"),
  year1 = 1,
  ci = TRUE,
  at_age = TRUE,
  r = 1
)

CM_CWT_ER(
  report,
  brood = TRUE,
  type = c("PT", "T", "all"),
  year1 = 1,
  ci = TRUE,
  rs_names
)

CM_covariate(x, names, year1 = 1, b, ylab = "Covariate")

```

Arguments

stanfit	Output from sample_CM()
sims	Optional integer vector for subset of MCMC iterations
inc_warmup	Logical, whether to include warmup MCMC samples
fit	Output from <code>[fit_CM()]</code>
vars	Character vector for variable names (see <code>names(stanfit@sim\$samples[[1]])</code>). Regex and partial matching supported because it is passed to the pattern argument of grepl()

report	List, output of state variables from individual MCMC samples, obtained with <code>get_report()</code>
d	List of data variables, obtained with <code>get_CMdata()</code>
year	Vector of years
year1	Numeric, first year of model
rs_names	Character vector of hatchery release strategies
PT	Logical, whether to plot preterminal catch, otherwise (plot terminal catch)
r	Integer, the release strategy for the figure (only if <code>annual = FALSE</code>)
brood	Logical, whether to show results by brood year or return year (<code>FALSE</code>)
annual	Logical, whether to show panel figure by individual year (<code>TRUE</code>) or a single time series figure
type	Character, indicates type of variable to plot
ci	Logical whether to show posterior intervals in addition to posterior median
surv	Logical, whether to plot survival (values between 0 - 1) or instantaneous mortality rates
ylab	Character y axis label
at_age	Logical, whether to make figure by individual age
x	Matrix of covariates by year x covariate
names	Character of covariate names
b	Matrix of fixed effect coefficients by simulation x covariate. If missing only the covariates (x) are plotted, otherwise, the dot product $\text{sum}(x * b)$ is calculated by individual simulation and quantiles are plotted

Value

- `get_report()` returns the list of state variables by individual MCMC samples
- `get_CMdata()` returns the list of data variables used in the conditioning model
- `CM_trace()` returns a `ggplot` showing the MCMC trace plot (aka wormplot)
- `CM_pairs()` returns output from `graphics::pairs()`, a matrix of scatterplots of MCMC posterior samples
- `CM_fit_esc()` returns base graphics with fit to total escapement time series
- `CM_fit_pHOS()` returns base graphics with fit to pHOS (census) observations
- `CM_fit_CWTesc()` returns `ggplot` of fit to CWT escapement at age
- `CM_fit_CWTcatch()` returns `ggplot` of fit to CWT catch at age
- `CM_maturity()` returns `ggplot` of estimated maturity at age
- `CM_vul()` returns `ggplot` of estimated fishery vulnerability at age

- `CM_SRR()` returns ggplot of estimated stock-recruit relationship (density-dependent juvenile production from egg production) with average relationship and realized annual values. Years correspond to return years of egg production (predicts juvenile production of the following calendar year).
- `CM_prod()` returns ggplot of realized productivity in the absence of fishery harvest, annual values are based on natural mortality and maturity at age
- `CM_Srep()` returns ggplot of realized spawner or egg production at replacement, annual values are based on natural mortality and maturity at age
- `CM_M()` returns ggplot of estimated natural mortality time series by age (marine stage)
- `CM_Megg()` returns ggplot of egg-juvenile mortality time series
- `CM_Njuv()` returns ggplot of juvenile abundance
- `CM_recr()` returns ggplot of recruitment (mature return)
- `CM_esc()` returns ggplot of escapement (after terminal harvest)
- `CM_F()` returns ggplot of instantaneous fishing mortality
- `CM_surv()` returns ggplot of natural survival (converting from instantaneous units of natural mortality)
- `CM_wt()` returns ggplot of annual deviations in egg-juvenile mortality from the Ricker function
- `CM_surv2()` returns ggplot of annual survival to age 2, which includes age-1 mortality (marine life stage) for both natural and hatchery origin fish. Hatchery fish experience additional mortality specified by release mortality.
- `CM_wt()` returns ggplot of annual deviations in age 1 natural mortality (first year in marine life stage, deviations from time series average)
- `CM_ER()` returns ggplot of exploitation rate either by individual age or aggregate values using adult equivalents
- `CM_CWT_ER()` returns ggplot of CWT exploitation rate (by release strategy)
- `CM_covariate()` returns ggplot of mortality covariates

glossary

salmonMSE glossary

Description

Glossary of terms and parameters used in salmonMSE

Examples

```
data(glossary)
glossary[1:2, ]
```

Habitat-class	Class "Habitat"
---------------	-----------------

Description

The component of the operating model that controls survival in the freshwater environment. Includes changes in survival from either environmental/climate effects or habitat mitigation.

Slots

Name Character. Identifying name

use_habitat Logical. If TRUE, utilize stage-specific density-dependent functions from egg production from incubation mortality, egg-to-fry production, and fry-to-smolt production with annual deviations. Otherwise, the density-dependence is modeled for egg-to-smolt survival. See Bio object.

prespawn_rel Character, density-dependent function for pre-spawn mortality, e.g., for spawners to reach spawning sites. Choices are "BH" (Beverton-Holt) or "HS" (hockey stick). Default is "BH".

prespawn_prod Numeric, productivity for pre-spawn mortality. Default is 1. Default if Inf.

prespawn_capacity Numeric, capacity for pre-spawn mortality. Default is Inf, i.e., density-independence. Default is Inf.

egg_rel Character, density-dependent function for egg production from total spawning output. Choices are "BH" (Beverton-Holt) or "HS" (hockey stick). Default is "BH".

egg_prod Numeric, productivity for egg production from total spawning output (incubation). Default is 1. Default if Inf.

egg_capacity Numeric, capacity for egg production from total spawning output (incubation). Default is Inf, i.e., density-independence. Default is Inf.

fry_rel Character, density-dependent function for egg-to-fry production. Choices are "BH" (Beverton-Holt) or "HS" (hockey stick). Default is "BH".

fry_prod Numeric between 0-1, productivity for egg production from total spawning output, i.e., maximum survival as egg production approaches zero. Default is 0.4.

fry_capacity Numeric, capacity for fry production from egg production. Default is Inf, i.e., for density-independence. Default is Inf.

fry_sdev Matrix [nsim, proyears], deviations from the density-dependent egg-fry survival. Can be utilized to incorporate time-varying environmental, climate, or habitat mitigation effects. Default is `matrix(1, nsim, proyears)`.

smolt_rel Character, density-dependent function for fry-to-smolt production. Choices are "BH" (Beverton-Holt) or "HS" (hockey stick). Default is "BH".

smolt_prod Numeric between 0-1, productivity for smolt production from fry, i.e., maximum survival as fry production approaches zero. Default is 1.

smolt_capacity Numeric, capacity for smolt production from fry production. Set to Inf for density-independence. Default is Inf.

smolt_sdev Matrix [nsim, proyears], deviations from the density-dependent fry-smolt survival. Can be utilized to incorporate time-varying environmental, climate, or habitat mitigation effects. Default is `matrix(1, nsim, proyears)`.

Creating Object

Objects can be created by calls of the form `new("Habitat")`

Examples

```
showClass("Habitat")
```

Harvest-class	Class "Harvest"
---------------	-----------------

Description

The component of the operating model that controls harvest.

Slots

Name Character. Identifying name

type_PT Character. Whether to manage preterminal fishery catch from exploitation rate ("u") or catch target ("catch"). Default is "u",

type_T Character. Whether to manage terminal fishery catch from exploitation rate ("u") or catch target ("catch"). Default is "u",

u_preterminal Numeric. If type_PT = "u", the exploitation rate of the immature stock in the pre-terminal fishery. This will be converted to an instantaneous fishing mortality rate, i.e., $F_{preterminal} = -\log(1 - u_{preterminal})$.

u_terminal Numeric. If type_T = "u", The exploitation rate of the return in the terminal fishery. This will be converted to an instantaneous fishing mortality rate, i.e., $F_{terminal} = -\log(1 - u_{terminal})$.

K_PT Numeric. If type_PT = "catch", the catch target of the immature stock in the pre-terminal fishery.

K_T Numeric. If type_T = "catch", the catch target of the return in the terminal fishery.

MSF_PT Logical. Whether to implement mark-selective fishing in the preterminal fishery, with no retention on unmarked fish.

MSF_T Logical. Whether to implement mark-selective fishing in the terminal fishery, with no retention on unmarked fish.

release_mort Vector length 2. The proportion of released fish that die after release, in the pre-terminal and terminal fishery. Implemented to model mark-selective fishing. Not used if either MSF_PT or MSF_T is FALSE.

vu1PT Vector length maxage or matrix [nsim, maxage]. Vulnerability schedule (between 0-1) in the preterminal fishery. Values indicate the proportion of fishing mortality experienced by each age class, where $F_{preterminal} = -\log(1 - u_{preterminal})$.

vu1T Vector length maxage or matrix [nsim, maxage]. Vulnerability schedule (between 0-1) in the terminal fishery. Values indicate the proportion of fishing mortality experienced by each age class, where $F_{terminal} = -\log(1 - u_{terminal})$.

Creating Object

Objects can be created by calls of the form `new("Harvest")`

Examples

```
showClass("Harvest")
```

Hatchery-class	<i>Class "Hatchery"</i>
----------------	-------------------------

Description

The component of the operating model that controls the hatchery management.

Details

Various parameters can be stochastic (length `nsim`) or input as a single numeric (value identical across all simulations).

A description of the fitness parameters and hatchery dynamics is available in the [online documentation](#).

Slots

`Name` Character. Identifying name

`n_r` Integer. Number of release strategies, sub-groups of fish with different survival schedules. Default is one.

`n_yearling` Vector length `n_r`. The target number of yearlings released by release strategy. No hatchery is modeled if $\text{sum}(n_yearling, n_subyearling) = 0$. are zero. Yearlings survival is density-independent after release. Default is zero.

`n_subyearling` Vector length `n_r`. The target number of subyearlings released. No hatchery is modeled if $\text{sum}(n_yearling, n_subyearling) = 0$ are zero. Subyearlings experience density-dependent survival in competition with natural origin young. Default is zero.

`s_prespawn` Numeric. The survival of broodtake prior to egg production. $1 - s_prespawn$ is the proportion of fish not used for hatchery purposes, e.g., mortality or other research purposes. Used to back-calculate the broodtake from `n_yearling` and `n_subyearling`. Default is 1.

`s_egg_smolt` Numeric. The survival of eggs to the smolt life stage (for yearling release). Used to back-calculate the broodtake from `n_yearling` and `n_subyearling`. Default is 1.

`s_egg_subyearling` Numeric. The survival of eggs to subyearling life stage (for subyearling release). Used to back-calculate the broodtake from `n_yearling` and `n_subyearling`. Default is 1.

`Mjuv_HOS` Either vector by age (length `maxage-1`) or an array with dimension `[nsim, maxage-1, proyears, n_r]`. Natural mortality of immature hatchery origin fish. To replicate the SAR parameter of a stage-specific model, set `Mjuv_HOS[a] = -log(SAR)` for the age class prior to maturation (and zero for all other ages).

- p_mature_HOS** Vector by age (length maxage) or an array with dimension [nsim, maxage, proyears, n_r] for the maturity of hatchery spawners. Default is set equal to Bio@p_mature for all release strategies.
- stray_external** Matrix by age (length maxage) and release strategy n_r that denotes the annual number of hatchery origin strays from other populations/systems not included in the operating model. Default is zero. External strays are added at the escapement life stage, assumed unmarked. For multi-population models with straying within the system, see also SOM@stray matrix.
- gamma** Numeric. The relative reproductive success of hatchery origin spawners (relative to natural origin spawners). Default is 1.
- m** Numeric. The mark rate of hatchery origin fish, which affects selective broodtake and fishery retention if mark-selective fishing is utilized. Set $m = 1$ for AHA compatibility with ptarget_NOB. Default is zero.
- f_brood** Function that calculates the natural origin brood and hatchery origin brood from the escapement (after en-route mortality). Function should be of the form `function(NO, HO, stray, m) {return(list(NO, HOB_marked, HOB_unmarked, HOB_stray))}`. Allows for bespoke rules for broodtake.
- brood_import** **Not used if f_brood is provided** Matrix by age (length maxage) for the number of annual imported hatchery origin broodstock. Egg production is weighted by fec_brood. To meet hatchery production target releases, imported brood and local marked brood are used indiscriminately. Default imported brood is zero.
- pmax_esc** **Not used if f_brood is provided** Numeric. The maximum proportion of total escapement (after en route mortality) that could be used as broodtake. Set to 1 for AHA compatibility. Default is 0.75.
- pmax_NOB** **Not used if f_brood is provided** Numeric. The maximum proportion of the natural origin escapement (after en route mortality and pmax_esc) to be used as broodtake. If broodstock is limited by $pmax_esc < 1$, then this parameter should be 1. Default is 1.
- ptarget_NOB** **Not used if f_brood is provided** Numeric. The target proportion of the natural origin broodtake relative to the overall broodtake, assuming the mark rate is 1 and natural origin fish can be identified in the hatchery. The realized proportion may be lower if there are insufficient natural origin escapement. If the mark rate < 1 , then this target proportion identifies the proportion of unmarked fished in the broodtake. If mark rate = 0, then pNOB is equal to the proportion in the escapement. Default is 0.9.
- phatchery** **Not used if f_brood is provided** Numeric. Optional parameter (default is NA). If set to a numeric between 0-1, this value is the proportion of the hatchery origin escapement that return to the hatchery, for example, by removal from spawning grounds or swim-in facilities. These fish are available for broodtake. None of these fish will spawn in the natural environment. With the default option, NA allows all hatchery origin escapement to be available for brood (the remainder go to the spawning grounds).
- premove_HOS** Numeric or function. The target proportion of the hatchery origin fish to be removed from the spawning grounds (in order to ensure a high proportion of NOS). The proportion of hatchery fish removed is discounted by the mark rate, i.e., $p = premove_HOS * m$. The removed hatchery-origin fish do not spawn and are not available for broodtake. A value less than one can represent imperfect implementation of weir removal. Default is zero. This slot can take a function that returns the proportion (p) based on hatchery-origin and natural-origin abundance

(after brood removal), thus allowing for bespoke rules for in-river harvest. The function should be of the form: `function(NO, HO, m) {return(p)}`.

`premove_NOS` Numeric or function. The target proportion of the natural origin fish to be removed from the spawning grounds, for example, through an in-river fishery. The proportion of natural fish removed is adjusted by the mark rate, i.e., $p = \text{premove_NOS} * (1-m)$. Default is zero. This slot can take a function that returns the proportion (p) based on hatchery-origin and natural-origin abundance (after brood removal), thus allowing for bespoke rules for in-river harvest. The function should be of the form: `function(NO, HO, m) {return(p)}`.

`fec_brood` Vector of length `maxage` or an array with dimension `[nsim, maxage, proyears]`. The fecundity schedule of broodtake to calculate the total egg production for the hatchery. If missing, uses `Bio@fec`.

`fitness_type` Character vector length 2. The fitness function to apply in the natural and hatchery environment, respectively. For each, either "Ford" or "none".

`theta` Vector length 2. The optimum phenotype value for the natural and hatchery environments.

`rel_loss` Vector length 3. The loss in fitness apportioned among the egg, fry, and smolt life stages which reduces survival. Theoretically, the three values should sum to 1. Alternatively, set to zero to set fitness loss to zero for that specific life stage (survival is one).

`zbar_start` Vector length 2. The mean phenotype value in the natural and hatchery populations at the start of the projection. Alternatively, an array by dimension `[nsim, maxage, 2]`, where the age slot corresponds to cohort.

`fitness_variance` Numeric. The variance (omega-squared) of the fitness function. Assumed identical between the natural and hatchery environments. Default is 100.

`phenotype_variance` Numeric. The variance (sigma-squared) of the phenotypic trait (theta). Assumed identical between the natural and hatchery environments. Default is 10.

`heritability` Numeric or vector length `[nsim]`. The heritability (h-squared) of the phenotypic trait. Between 0-1. Default is 0.5

`fitness_floor` Numeric. The minimum fitness value in the natural and hatchery environments, i.e., fitness cannot drop below this threshold. Default is 0.5.

Creating Object

Objects can be created by calls of the form `new("Hatchery")`

Examples

```
showClass("Hatchery")
```

Historical-class	Class "Historical"
------------------	--------------------

Description

Optional component of the operating model that specifies the historical dynamics. The default option starts the projection with 1000 natural-origin juveniles and 1000 hatchery-origin juveniles (if there is hatchery production) in the oldest age class, representing single-brood year returns since there is only one age class in the population. Specify the abundance in all age class to simulate multiple brood-year returns.

Slots

Name Character. Identifying name

InitNjuv_NOS Array by [nsim, maxage, n_g]. The abundance of immature natural origin fish at the beginning of the projection. Default assumes 1000 in the oldest age class, which creates a population with single brood year returns.

InitNjuv_HOS Array by [nsim, maxage, n_r]. The abundance of immature hatchery origin fish at the beginning of the projection. Default assumes 1000 in the oldest age class, which creates a population with single brood year returns.

Creating Object

Objects can be created by calls of the form `new("Historical")`

Examples

```
showClass("Historical")
```

make_Harvest_MMP	<i>Internal salmonMSE functions for converting operating model inputs and outputs</i>
------------------	---

Description

- `SOM2MOM()` converts a salmon operating model (SOM) to a multi-stock operating model (MSEtool::MOM)
- `make_Stock()` creates the `MSEtool::Stock` object (openMSE) corresponding to salmon life stage
- `make_Fleet()` creates the `MSEtool::Fleet` object (openMSE) corresponding to the fishery that interacts with the various salmon life stages
- `multiHist2SHist()` converts the openMSE historical reconstruction into a salmon Hist object (SHist)
- `MMSE2SMSE()` converts the openMSE projection output, along with additional state variables recorded in `salmonMSE_env`, into a salmon MSE object (SMSE)
- `make_Harvest_MMP()` creates a multi-stock management procedure for the harvest component of the operating model by specifying exploitation rates through updating the formal arguments for `Harvest_MMP()`

`salmonMSE()` is the wrapper function that coordinates the simulation and the output.

Usage

```

make_Harvest_MMP(SOM, check = TRUE)

MMSE2SMSE(MMSE, SOM, Harvest_MMP, N, stateN, Ford, H, stateH)

SOM2MOM(SOM, check = TRUE)

make_Stock(
  SOM,
  s = 1,
  g = 1,
  r = 1,
  NOS = TRUE,
  stage = c("immature", "return", "escapement")
)

make_Fleet(SOM, s, NOS = TRUE, stage = c("immature", "return", "escapement"))

multiHist2SHist(multiHist, SOM, check = TRUE)

```

Arguments

SOM	An object of class SOM
check	Logical, whether to check the SOM object using check_SOM()
MMSE	Object of class MSEtool::MMSE returned from MSEtool
Harvest_MMP	Optional harvest function created by make_Harvest_MMP()
N	Data frame of natural origin abundance at age saved in the salmonMSE_env environment during the simulation
stateN	Data frame of natural origin state variables saved in the salmonMSE_env environment during the simulation
Ford	Data frame of phenotypic trait values saved in the salmonMSE_env environment during the simulation
H	Data frame of hatchery origin abundance at age saved in the salmonMSE_env environment during the simulation
stateH	Data frame of hatchery origin state variables saved in the salmonMSE_env environment during the simulation
s	Integer, the population integer for which to create the Stock or Fleet object
g	Integer, the life history group for which to create the Stock object. Not relevant if NOS = FALSE
r	Integer, the hatchery release group for which to create the Stock object. Not relevant if NOS = TRUE
NOS	Logical, whether the Stock or Fleet object corresponds to natural origin or hatchery origin fish
stage	Character indicating the corresponding salmon life stage of the Stock or Fleet object
multiHist	Class multiHist object returned from MSEtool

Value

make_Harvest_MMP: Function of class "MMP" by updating the formal arguments for `Harvest_MMP()`

MMSE2SMSE: `SMSE` object

SOM2MOM: `MSEtool::MOM` object

make_Stock: List containing a `MSEtool::Stock` object and accompanying custom parameters list

make_Fleet: List containing a `MSEtool::Fleet` object and accompanying custom parameters list

multiHist2SHist: `SHist` object

plot_decision_table *Decision table of performance metrics*

Description

Generates a coloured table of a performance metric across two axes, which may be a population dynamics variable (e.g., productivity) or a management action (e.g., hatchery production levels or harvest strategy). See example at <https://docs.salmonmse.com/articles/decision-table.html>

Usage

```
plot_decision_table(
  x,
  y,
  z,
  title,
  xlab,
  ylab,
  scenario,
  ncol = NULL,
  dir = "v"
)
```

Arguments

x	Atomic, vector of values for the x axis (same length as z). Will be converted to factors
y	Atomic, vector of values for the y axis (same length as z). Will be converted to factors
z	Numeric, vector of values for the performance metric
title	Character, optional title of figure
xlab	Character, optional x-axis label
ylab	Character, optional y-axis label

scenario	Atomic, vector of faceting variables (same length as z) used to generate a grid of decision tables
ncol	Integer, number of columns for decision table grid, only used if scenario is provided
dir	Character, either "h" or "v" to describe how the grid of tables should be organized (horizontally or vertically)

Value

ggplot object

See Also

[plot_statevar_ts\(\)](#) [plot_tradeoff\(\)](#)

plot_LHG	<i>Plot life history groups and release strategies</i>
----------	--

Description

Plot the annual proportions of life history groups (natural origin fish) or release strategies (hatchery origin) at various life stages

Usage

```
plot_LHG(
  SMSE,
  var = "NOS",
  type = c("prop", "abs"),
  s = 1,
  FUN = median,
  figure = TRUE,
  xlab = "Projection Year",
  ylab,
  name,
  ylim
)
```

```
plot_RS(
  SMSE,
  var = "HOS",
  type = c("prop", "abs"),
  s = 1,
  FUN = median,
  figure = TRUE,
  xlab = "Projection Year",
  ylab,
```

```

    name,
    ylim
  )

```

Arguments

SMSE	Class SMSE object returned by salmonMSE()
var	Character. Slot for the state variables in <code>SMSE@Misc\$LHG[[1]]</code> or <code>SMSE@Misc\$RS[[1]]</code> .
type	Character to indicate whether to plot proportion or absolute numbers
s	Integer. Population index for multi-population model (e.g., <code>s = 1</code> is the first population in the model)
FUN	Summarizing function across simulations, typically median() or mean()
figure	Logical, whether to generate a figure (set to <code>FALSE</code> if only using the function to return the data matrix)
xlab	Character. Name of time variable for the figure
ylab	Character. Name of the state variable for the figure
name	Character. Vector of names for the life history groups or release strategies
ylim	Vector length 2, y-axis limits

Value

Base graphics figure, barplot of distribution or total numbers by LHG or RS. Returns invisibly the matrix of plotted values

See Also

[plot_statevar_ts\(\)](#)

plot_statevar_ts *Plot core output from salmonMSE*

Description

Various functions that plot the state variables from `salmonMSE` projections:

- `plot_statevar_ts()` produces a time series for all simulations, or with medians and 95th percentile intervals
- `plot_statevar_hist()` produces a histogram across all simulations for a particular year
- `plot_spawnners()` produces a summary barplot of spawners, including NOS, HOS, and wild spawners
- `plot_escaping()` produces a summary figure of the proportion of spawners and broodtake to escapement
- `plot_fitness()` produces a summary figure of metrics (fitness, PNI, pHOS, and pWILD) related to hatchery production
- `plot_fishery()` produces a summary figure of metrics related to the fishery, e.g., median catch, exploitation rate or harvest rate

Usage

```

plot_statevar_ts(
  SMSE,
  var = "PNI",
  s = 1,
  figure = TRUE,
  xlab = "Projection Year",
  quant = FALSE,
  ylab = var,
  ylim,
  agg.fun = sum,
  ...
)

plot_statevar_hist(SMSE, var = "PNI", s = 1, y, figure = TRUE, xlab = var, ...)

plot_spawnners(SMSE, s = 1, prop = TRUE, FUN = median, figure = TRUE, ylim)

plot_fitness(SMSE, s = 1, FUN = median, figure = TRUE, ylim)

plot_escapement(SMSE, s = 1, FUN = median, figure = TRUE, ylim)

plot_fishery(
  SMSE,
  s = 1,
  type = c("catch", "exploit", "harvest"),
  FUN = median,
  figure = TRUE,
  ylim,
  ylab,
  ...
)

plot_Kobe(
  SMSE,
  s = 1,
  FUN = median,
  figure = TRUE,
  xlim,
  ylim,
  xlab = expression(NOS/S[MSY]),
  ylab = expression(U/U[MSY]),
  type = c("T", "PT")
)

```

Arguments

SMSE Class [SMSE](#) object returned by [salmonMSE\(\)](#)

var	Character. Slot for the state variable in SMSE object. See <code>slotNames(SMSE)</code> for options. Additional supported options are: "ESS" (egg-smolt survival), "pbrood" (broodtake to escapement ratio), "pNOSesc" (NOS/natural escapement), "pHOSesc" (HOS/hatchery escapement), Total Spawners (NOS + HOS), NOS/SMSY, S/SMSY, and NOS/Sgen.
s	Integer. Population index for multi-population model (e.g., $s = 1$ is the first population in the model)
figure	Logical, whether to generate a figure (set to FALSE if only using the function to return the data matrix)
xlab	Character. Name of time variable for the figure
quant	Logical, whether to plot individual simulations (FALSE) or the median with 95 percent confidence intervals (TRUE)
ylab	Character. Name of the state variable for the figure
ylim	Vector. Y-axis limits
agg.fun	Function. Defines how to aggregate state variables that are reported by age. Typically, <code>sum</code> is used but <code>max</code> is also possible for reporting apical exploitation rates.
...	Additional arguments to base plot function
y	Integer. Projection year for the state variable to plot the histogram. If missing, the last projection year is used.
prop	Logical, whether to plot proportions or absolute numbers
FUN	Summarizing function across simulations, typically <code>median()</code> or <code>mean()</code>
type	For <code>plot_Kobe</code> , the fishery state variable to plot. Whether to plot the exploitation rate for the terminal (T) or pre-terminal fishery (PT).
xlim	Vector. X-axis limits

Value

Functions return the matrix of plotted values invisibly. Figure plotted from base graphics

See Also

[plot_decision_table\(\)](#) [plot_LHG\(\)](#) [compare_statevar_ts\(\)](#)

plot_tradeoff

Tradeoff figure

Description

Generates a tradeoff figure, a comparison between two performance metrics, across two variables which may represent a population dynamics variable (e.g., productivity) or a management action (e.g., hatchery production levels or harvest strategy). See example at <https://docs.salmonmse.com/articles/decision-table.html>

Usage

```
plot_tradeoff(  
  pm1,  
  pm2,  
  x1,  
  x2,  
  xlab,  
  ylab,  
  x1lab,  
  x2lab,  
  scenario,  
  ncol = NULL,  
  dir = "v"  
)
```

Arguments

pm1	Numeric or matrix. A vector of values for the first performance metric on the x-axis. Alternatively, provide a three column matrix corresponding to the lower bound, central tendency, and upper bound.
pm2	Numeric or matrix. A vector of values for the second performance metric on the y-axis (same length as pm1). Alternatively, provide a three column matrix corresponding to the lower bound, central tendency, and upper bound.
x1	Atomic, vector of values for the first grouping variable. Various levels are represented by colours. Same length as pm1.
x2	Numeric, vector of values for the second grouping variable. Various levels are represented by shapes. Same length as pm1.
xlab	Character, optional x-axis label
ylab	Character, optional y-axis label
x1lab	Character, optional label for the first grouping variable
x2lab	Character, optional label for the second grouping variable
scenario	Atomic, vector of faceting variables (same length as pm1, pm2) used to generate a grid of decision tables
ncol	Integer, number of columns for decision table grid, only used if scenario is provided
dir	Character, either "h" or "v" to describe how the grid of tables should be organized (horizontally or vertically) , only used if scenario is provided

Value

ggplot object

See Also

[plot_statevar_ts\(\)](#) [plot_decision_table\(\)](#)

PNI50

*Example performance metrics***Description**

Functions that evaluate return probabilities of outcomes from the simulations.

Usage

PNI50(SMSE, Ref = 0.5, Yrs = NULL)

PNI80(SMSE, Ref = 0.8, Yrs = NULL)

WILD50(SMSE, Ref = 0.5, Yrs = NULL)

SMSY85(SMSE, Ref = 0.85, Yrs = NULL)

Sgen100(SMSE, Ref = 1, Yrs = NULL)

Arguments

SMSE	SMSE object returned by salmonMSE()
Ref	Threshold for the performance metric, used to calculate the probability that the metric exceeds this value
Yrs	Numeric vector of length 2 to indicate the year range over which to summarize performance. If NULL, the performance is summarized over all projection years.

Details

- PNI50 calculates the probability that PNI exceeds 0.50 (threshold for an integrated-transition population, Withler et al. 2018)
- PNI80 calculates the probability that PNI exceeds 0.80 (threshold for an integrated-wild population, Withler et al. 2018)
- WILD50 calculates the probability that at least 50 percent of natural spawners are wild
- SMSY85 calculates the probability that NOS/SMSY exceeds 0.85
- Sgen100 calculates the probability that NOS/Sgen exceeds 1

Value

A vector of probabilities corresponding to population

References

Withler et al. 2018. Genetically Based Targets for Enhanced Contributions to Canadian Pacific Chinook Salmon Populations. DFO Can. Sci. Advis. Sec. Res. Doc. 2018/019. xii + 88 p.

report *Generate markdown reports*

Description

Generate a markdown report for outcomes from a single operating model projection

Usage

```
## S4 method for signature 'SMSE'  
report(  
  object,  
  name = object@Name,  
  filename = "SMSE",  
  dir = tempdir(),  
  open_file = TRUE,  
  render_args = list(),  
  ...  
)
```

Arguments

object	SMSE object
name	Character string for the model name to include in the report, e.g., model run number.
filename	Character string for the name of the markdown and HTML files.
dir	The directory in which the markdown and HTML files will be saved.
open_file	Logical, whether the HTML document is opened after it is rendered.
render_args	List of arguments to pass to rmarkdown::render() .
...	Additional arguments (not used)

Value

Returns invisibly the output of [rmarkdown::render\(\)](#), typically the path of the output file

See Also

[compare\(\)](#)

report_CM

*Conditioning model markdown report***Description**

Generate a markdown report to plot time series and MCMC posteriors of estimates from the conditioning model. See [get_report\(\)](#) for the various plotting functions used in the report.

Usage

```
report_CM(
  stanfit,
  year,
  cov1_names,
  cov_names,
  rs_names,
  name,
  filename = "CM",
  dir = tempdir(),
  open_file = TRUE,
  render_args = list(),
  ...
)
```

Arguments

stanfit	Output from sample_CM()
year	Optional vector of calendar years
cov1_names	Optional character vector for names of covariates that predict age-1 natural mortality
cov_names	Optional character vector for names of covariates that predict age-2+ natural mortality
rs_names	Optional character vector for names of hatchery release strategies
name	Optional character string for the model name to include in the report, e.g., model run number
filename	Character string for the name of the markdown and HTML files
dir	The directory in which the markdown and HTML files will be saved.
open_file	Logical, whether the HTML document is opened after it is rendered
render_args	List of arguments to pass to rmarkdown::render()
...	Additional arguments (not used)

Details

Report excludes MCMC values from warmup iterations

Value

Returns invisibly the output of `rmarkdown::render()`, typically the path of the output file

See Also

`fit_CM()` `get_report()`

salmonMSE

Run salmonMSE

Description

`salmonMSE()` runs a salmon management strategy evaluation through the following steps:

- Converts a salmon operating model (**SOM**) to a multi-stock operating model (**MSEtool::MOM**) via `SOM2MOM()`
- Creates a harvest management procedure specifying the harvest control rule
- Generates the historical reconstruction of the state variables
- Runs projection (if `Hist = FALSE`)
- Converts the openMSE output, along with additional state variables recorded in `salmonMSE_env`, into a salmon MSE object (SMSE) via `MMSE2SMSE()`

Usage

```
salmonMSE(SOM, Hist = FALSE, silent = FALSE, trace = FALSE, convert = TRUE)
```

Arguments

<code>SOM</code>	An object of class SOM
<code>Hist</code>	Logical, whether to stop the function stop after historical simulations?
<code>silent</code>	Logical, whether to report progress in console
<code>trace</code>	Logical, whether to report additional messages from openMSE
<code>convert</code>	Logical, whether to convert the output into a salmon MSE (SHist or SMSE, depending on <code>Hist</code>) object

Value

If `Hist = TRUE`: if `convert = TRUE`, a **SHist** object or if `convert = FALSE`, a multiHist object (list).

If `Hist = FALSE`: if `convert = TRUE`, a **SMSE** object or if `convert = FALSE`, a **MSEtool::MMSE** object.

salmonMSE_env	<i>Environment to store salmon specific variables, e.g, fitness, during the simulation</i>
---------------	--

Description

Environment to store salmon specific variables, e.g, fitness, during the simulation

Usage

salmonMSE_env

Format

An object of class environment of length 5.

SHist-class	<i>Class "SHist"</i>
-------------	----------------------

Description

Stores the outputs from the historical reconstruction of salmon operating models. Primarily used for development and debugging.

Slots

Name Character. Identifying name

nyears Integer, number of historical years

nsim Integer. The number of simulations

nstocks Integer. The number of stocks

Snames Character. Stock names

Egg_NOS Array [nsim, nstocks, nyears]. Spawning output, i.e., egg production, of natural origin spawners.

Egg_HOS Array [nsim, nstocks, nyears]. Spawning output of hatchery origin spawners.

Smolt Array [nsim, nstocks, nyears]. Natural smolt production (sum of offspring of natural and hatchery spawners).

Smolt_Rel Array [nsim, nstocks, proyears]. Smolts that are offspring of broodtake, i.e., hatchery releases.

Njuv_NOS Array [nsim, nstocks, nage, nyears]. Abundance of juvenile natural origin fish at the beginning of the year.

Njuv_HOS Array [nsim, nstocks, nage, nyears]. Abundance of juvenile hatchery origin fish at the beginning of the year.

Return_NOS Array [nsim, nstocks, nage, nyears]. Mature fish that will be natural origin spawners.

Return_HOS Array [nsim, nstocks, nage, nyears]. Mature fish that will be hatchery origin spawners.

Escapement_NOS Array [nsim, nstocks, nage, nyears]. The escapement of mature fish that will be natural origin spawners.

Escapement_HOS Array [nsim, nstocks, nage, nyears]. The escapement of mature fish that will be hatchery origin spawners.

NOS Array [nsim, nstocks, proyears]. Natural origin spawners.

HOS Array [nsim, nstocks, proyears]. Hatchery origin spawners.

HOS_effective Array [nsim, nstocks, proyears]. Hatchery origin spawners discounted by gamma.

KPT_NOS Array [nsim, nstocks, proyears]. Pre-terminal fishery kept catch of natural origin spawners.

KT_NOS Array [nsim, nstocks, proyears]. Terminal fishery kept catch of natural origin spawners.

KPT_HOS Array [nsim, nstocks, proyears]. Pre-terminal fishery kept catch of hatchery origin spawners.

KT_HOS Array [nsim, nstocks, proyears]. Terminal fishery kept catch of hatchery origin spawners.

DPT_NOS Array [nsim, nstocks, proyears]. Pre-terminal fishery released catch (live and dead) of natural origin spawners.

DT_NOS Array [nsim, nstocks, proyears]. Terminal fishery released catch (live and dead) of natural origin spawners.

DPT_HOS Array [nsim, nstocks, proyears]. Pre-terminal fishery released catch (live and dead) of hatchery origin spawners.

DT_HOS Array [nsim, nstocks, proyears]. Terminal fishery released catch (live and dead) hatchery origin spawners.

UPT_NOS Array [nsim, nstocks, proyears]. Pre-terminal fishery harvest rate (from kept catch) of natural origin spawners.

UT_NOS Array [nsim, nstocks, proyears]. Terminal fishery harvest rate of natural origin spawners.

UPT_HOS Array [nsim, nstocks, proyears]. Pre-terminal fishery harvest rate of hatchery origin spawners.

UT_HOS Array [nsim, nstocks, proyears]. Terminal fishery harvest rate of hatchery origin spawners.

ExPT_NOS Array [nsim, nstocks, proyears]. Pre-terminal fishery exploitation rate (from kept catch and dead releases) of natural origin spawners.

ExT_NOS Array [nsim, nstocks, proyears]. Terminal fishery exploitation rate of natural origin spawners.

ExPT_HOS Array [nsim, nstocks, proyears]. Pre-terminal fishery exploitation rate of hatchery origin spawners.

ExT_HOS Array [nsim, nstocks, proyears]. Terminal fishery exploitation rate of hatchery origin spawners.

Misc List. Miscellaneous output

Examples

```
showClass("SHist")
```

SMSE-class

Class "SMSE"

Description

Stores the outputs from the simulation of salmon operating models.

Details

In generation t , proportionate natural influence (PNI) is defined as:

$$\text{PNI}_t = \frac{p_t^{\text{NOB}}}{p_t^{\text{NOB}} + p_t^{\text{HOSeff}}}$$

with $p^{\text{HOSeff}} = \text{HOSeff}/(\text{NOS} + \text{HOSeff})$.

The proportion of wild salmon is defined as:

$$p_t^{\text{WILD}} = q_t^{\text{HOSeff}} \frac{(q_{t-1}^{\text{HOSeff}})^2}{(q_{t-1}^{\text{HOSeff}})^2 + 2\gamma \times p_{t-1}^{\text{HOSeff}} q_{t-1}^{\text{HOSeff}} + \gamma^2 (p_{t-1}^{\text{HOSeff}})^2}$$

where $q = 1 - p$ and $p^{\text{HOSeff}} = \text{HOS}/(\text{NOS} + \text{HOS})$.

Slots

Name Character. Identifying name

proyears Integer. The number of projected years

nsim Integer. The number of simulations

nstocks Integer. The number of stocks

Snames Character. Stock names

Egg_NOS Array [nsim, nstocks, proyears]. Spawning output, i.e., egg production, of natural origin spawners.

Egg_HOS Array [nsim, nstocks, proyears]. Spawning output of hatchery origin spawners.

Fry_NOS Array [nsim, nstocks, proyears]. Fry that are offspring of natural origin spawners.

Fry_HOS Array [nsim, nstocks, proyears]. Fry that are offspring of hatchery origin spawners.

Smolt_NOS Array [nsim, nstocks, proyears]. Smolts that are offspring of natural origin spawners.

Smolt_HOS Array [nsim, nstocks, proyears]. Smolts that are offspring of hatchery origin spawners.

Smolt_Rel Array [nsim, nstocks, proyears]. Smolts that are offspring of broodtake, i.e., hatchery releases.

Njuv_NOS Array [nsim, nstocks, nage, proyears]. Abundance of juvenile natural origin fish at the beginning of the year.

Njuv_HOS Array [nsim, nstocks, nage, proyears]. Abundance of juvenile hatchery origin fish at the beginning of the year.

Return_NOS Array [nsim, nstocks, nage, proyears]. Mature fish that will be natural origin spawners.

Return_HOS Array [nsim, nstocks, nage, proyears]. Mature fish that will be hatchery origin spawners.

Escapement_NOS Array [nsim, nstocks, nage, proyears]. The escapement of mature fish that will be natural origin spawners.

Escapement_HOS Array [nsim, nstocks, nage, proyears]. The escapement of mature fish that will be hatchery origin spawners.

NOB Array [nsim, nstocks, proyears]. Natural origin broodtake.

HOB Array [nsim, nstocks, proyears]. Hatchery origin broodtake (local + strays).

HOB_stray Array [nsim, nstocks, proyears]. Hatchery origin broodtake (strays only).

HOB_import Array [nsim, nstocks, proyears]. Imported hatchery origin broodtake used for hatchery production.

NOS Array [nsim, nstocks, nage, proyears]. Natural origin spawners.

HOS Array [nsim, nstocks, nage, proyears]. Hatchery origin spawners (local + strays).

HOS_stray Array [nsim, nstocks, nage, proyears]. Hatchery origin spawners (strays only).

HOS_effective Array [nsim, nstocks, nage, proyears]. Hatchery origin spawners (local + strays) discounted by gamma.

KPT_NOS Array [nsim, nstocks, proyears]. Pre-terminal fishery kept catch of natural origin spawners.

KT_NOS Array [nsim, nstocks, proyears]. Terminal fishery kept catch of natural origin spawners.

KPT_HOS Array [nsim, nstocks, proyears]. Pre-terminal fishery kept catch of hatchery origin spawners.

KT_HOS Array [nsim, nstocks, proyears]. Terminal fishery kept catch of hatchery origin spawners.

DPT_NOS Array [nsim, nstocks, proyears]. Pre-terminal fishery released catch (live and dead) of natural origin spawners.

DT_NOS Array [nsim, nstocks, proyears]. Terminal fishery released catch (live and dead) of natural origin spawners.

DPT_HOS Array [nsim, nstocks, proyears]. Pre-terminal fishery released catch (live and dead) of hatchery origin spawners.

DT_HOS Array [nsim, nstocks, proyears]. Terminal fishery released catch (live and dead) hatchery origin spawners.

UPT_NOS Array [nsim, nstocks, nage, proyears]. Pre-terminal fishery harvest rate (from kept catch) of natural origin spawners.

UT_NOS Array [nsim, nstocks, nage, proyears]. Terminal fishery harvest rate of natural origin spawners.

- UPT_HOS Array [nsim, nstocks, nage, proyears]. Pre-terminal fishery harvest rate of hatchery origin spawners.
- UT_HOS Array [nsim, nstocks, nage, proyears]. Terminal fishery harvest rate of hatchery origin spawners.
- ExPT_NOS Array [nsim, nstocks, nage, proyears]. Pre-terminal fishery exploitation rate (from kept catch and dead releases) of natural origin spawners.
- ExT_NOS Array [nsim, nstocks, nage, proyears]. Terminal fishery exploitation rate of natural origin spawners.
- ExPT_HOS Array [nsim, nstocks, nage, proyears]. Pre-terminal fishery exploitation rate of hatchery origin spawners.
- ExT_HOS Array [nsim, nstocks, nage, proyears]. Terminal fishery exploitation rate of hatchery origin spawners.
- fitness Array [nsim, nstocks, 2, proyears]. Fitness of the population in the natural (1) and hatchery (2) environments.
- pNOB Array [nsim, nstocks, proyears]. Proportion of natural fish in the brood.
- pHOS_census Array [nsim, nstocks, proyears]. Proportion of spawners of hatchery origin, weighted by age class fecundity.
- pHOS_effective Array [nsim, nstocks, proyears]. Proportion of spawners of hatchery origin, discounted by gamma, weighted by age class fecundity.
- PNI Array [nsim, nstocks, proyears]. Proportionate natural influence, index of gene flow from hatchery to the natural environment.
- p_wild Array [nsim, nstocks, proyears]. Proportion of wild spawners, natural spawners whose parents were also produced in the natural environment assuming non-assortative mating, defined under Canada's Wild Salmon Policy.
- Mjuv_loss Array [nsim, nstocks, nage, proyears]. Realized juvenile natural mortality, which may differ from inputs due to fitness loss.
- Misc List. Miscellaneous output:
- Ref for reference points
 - SHist for the [SHist](#) object
 - SOM for the [SOM](#) object.
 - LHG list nstocks long containing state variables by life history group

Creating Object

Objects can be created by calls of the form `new("SMSE")`

References

Withler et al. 2018. Genetically Based Targets for Enhanced Contributions to Canadian Pacific Chinook Salmon Populations. DFO Can. Sci. Advis. Sec. Res. Doc. 2018/019. xii + 88 p.

Examples

```
showClass("SMSE")
```

SOM-class

Class "SOM"

Description

An object containing all the parameters for a salmon operating model (SOM).

Slots

Name Character. Identifying name

nsim Integer. Number of simulations

proyears Integer. The number of projected years

seed Integer. A random seed to ensure users can reproduce results exactly

Bio [Bio](#) object informing biological parameters, natural production, and habitat effects. Provide a list of Bio objects for multi-population models.

Habitat [Habitat](#) object containing management levers for habitat mitigation. Provide a list of Habitat objects for multi-population models.

Hatchery [Hatchery](#) object containing management levers for hatchery production. Provide a list of Hatchery objects for multi-population models.

Harvest [Harvest](#) object containing management levers for harvest. Provide a list of Harvest objects for multi-population models.

Historical [Historical](#) object to inform historical reconstruction and informing starting abundance for the projection. Provide a list of Historical objects for multi-population models.

stray Matrix [np, np] where np = length(Bio) and row p indicates the re-assignment of hatchery fish to each population when they mature (at the recruitment life stage). For example, `SOM@stray <- matrix(c(0.75, 0.25, 0.25, 0.75), 2, 2)` indicates that 75 percent of mature fish return to their natal river and 25 percent stray in both populations. By default, an identity matrix is used (no straying).

Objects from the Class

Objects can be created by calls of the form `new("SOM", Bio, Habitat, Hatchery, Harvest, Historical)`.

Index

* classes

- Bio-class, 3
- Habitat-class, 25
- Harvest-class, 26
- Hatchery-class, 27
- Historical-class, 29
- SHist-class, 42
- SMSE-class, 44
- SOM-class, 47

* datasets

- salmonMSE_env, 42

AHA, 2

base::mean(), 13

Bio, 47

Bio-class, 3

calc_MSJ (calc_ref), 4

calc_ref, 4

calc_ref(), 8

calc_Sgen (calc_ref), 4

calc_Sgen_Ricker (calc_Smsy_Ricker), 8

calc_smolt, 7

calc_Smsy_Ricker, 8

calc_Smsy_Ricker(), 6

calc_SRR, 8

calc_SRR(), 10

calc_SRRpars, 9

calc_SRRpars(), 9

calc_Umsy_Ricker (calc_Smsy_Ricker), 8

check_SOM, 10

check_SOM(), 6, 31

CM2SOM, 11

CM2SOM(), 20

CM_covariate (get_report), 21

CM_CWT_ER (get_report), 21

CM_ER (get_report), 21

CM_esc (get_report), 21

CM_F (get_report), 21

CM_fit_CWTcatch (get_report), 21

CM_fit_CWTesc (get_report), 21

CM_fit_esc (get_report), 21

CM_fit_pHOS (get_report), 21

CM_M (get_report), 21

CM_maturity (get_report), 21

CM_Megg (get_report), 21

CM_Njuv (get_report), 21

CM_pairs (get_report), 21

CM_prod (get_report), 21

CM_recr (get_report), 21

CM_Srep (get_report), 21

CM_SRR (get_report), 21

CM_surv (get_report), 21

CM_surv2 (get_report), 21

CM_trace (get_report), 21

CM_vul (get_report), 21

CM_wt (get_report), 21

CM_wto (get_report), 21

CMfigures (get_report), 21

compare, 12

compare(), 15, 39

compare_escapement (compare_spawnners),
13

compare_escapement(), 13

compare_fitness (compare_spawnners), 13

compare_fitness(), 13

compare_spawnners, 13

compare_spawnners(), 13

compare_statevar_hist
(compare_statevar_ts), 14

compare_statevar_ts, 14

compare_statevar_ts(), 36

fit_CM, 15

fit_CM(), 41

get_CMdata (get_report), 21

get_report, 21

get_report(), 40, 41

- glossary, 24
- graphics::pairs(), 23
- grepl(), 22
- Habitat, 47
- Habitat-class, 25
- Harvest, 47
- Harvest-class, 26
- Harvest_MMP(), 30, 32
- Hatchery, 47
- Hatchery-class, 27
- Historical, 47
- Historical-class, 29
- make_Fleet (make_Harvest_MMP), 30
- make_Fleet(), 30
- make_Harvest_MMP, 30
- make_Harvest_MMP(), 30, 31
- make_Stock (make_Harvest_MMP), 30
- make_Stock(), 30
- mean(), 34, 36
- median(), 34, 36
- MMSE2SMSE (make_Harvest_MMP), 30
- MMSE2SMSE(), 30, 41
- MSEtool::Fleet, 30, 32
- MSEtool::MMSE, 31, 41
- MSEtool::MOM, 30, 32, 41
- MSEtool::Stock, 30, 32
- multiHist2SHist (make_Harvest_MMP), 30
- multiHist2SHist(), 30
- plot_decision_table, 32
- plot_decision_table(), 36, 37
- plot_escapement (plot_statevar_ts), 34
- plot_fishery (plot_statevar_ts), 34
- plot_fitness (plot_statevar_ts), 34
- plot_Kobe (plot_statevar_ts), 34
- plot_LHG, 33
- plot_LHG(), 36
- plot_RS (plot_LHG), 33
- plot_spawnners (plot_statevar_ts), 34
- plot_statevar_hist (plot_statevar_ts), 34
- plot_statevar_ts, 34
- plot_statevar_ts(), 15, 33, 34, 37
- plot_tradeoff, 36
- plot_tradeoff(), 33
- PNI50, 38
- PNI80 (PNI50), 38
- report, 39
- report(), 12
- report, SMSE-method (report), 39
- report_CM, 40
- report_CM(), 16, 20
- rmarkdown::render(), 12, 39–41
- RTMB::MakeADFun(), 16
- salmonMSE, 41
- salmonMSE(), 13, 14, 30, 34, 35, 38
- salmonMSE-int (make_Harvest_MMP), 30
- salmonMSE_env, 30, 31, 41, 42
- sample_CM (fit_CM), 15
- sample_CM(), 11, 22, 40
- Sgen100 (PNI50), 38
- SHist, 30, 32, 41, 46
- SHist-class, 42
- SMSE, 3, 12, 30, 32, 34, 35, 39, 41
- SMSE-class, 44
- SMSY85 (PNI50), 38
- SOM, 3, 6, 10, 11, 30, 31, 41, 46
- SOM (SOM-class), 47
- SOM-class, 47
- SOM2MOM (make_Harvest_MMP), 30
- SOM2MOM(), 30, 41
- stats::median(), 13
- stats::nlminb(), 16
- TMB::MakeADFun(), 16
- WILD50 (PNI50), 38