

Package ‘worcs’

February 22, 2026

Type Package

Title Workflow for Open Reproducible Code in Science

Version 0.1.20

Description Create reproducible and transparent research projects in 'R'.

This package is based on the Workflow for Open Reproducible Code in Science (WORCS), a step-by-step procedure based on best practices for Open Science. It includes an 'RStudio' project template, several convenience functions, and all dependencies required to make your project reproducible and transparent. WORCS is explained in the tutorial paper by Van Lissa, Brandmaier, Brinkman, Lamprecht, Struiksma, & Vreede (2021). [doi:10.3233/DS-210031](https://doi.org/10.3233/DS-210031).

License CC0

Encoding UTF-8

LazyData true

URL <https://github.com/cjvanlissa/worcs>,
<https://cjvanlissa.github.io/worcs/>

RoxygenNote 7.3.3

Imports methods, rmarkdown, renv, prereg (>= 0.6.0), gert (>= 2.0.1), ranger, yaml, digest, rticles (>= 0.27), tinytex, credentials, usethis (>= 3.1.0), gh, xfun, cli, rlang, rprojroot

Suggests papaja (>= 0.1.1), targets (>= 1.11.1), lavaan, tidySEM, tarchetypes, remotes, knitr, missRanger, curl, fs, withr, desc, purrr, testthat (>= 3.0.0), pkgdown

SystemRequirements pandoc (>= 1.14) - <https://pandoc.org>

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation no

Author Caspar J. Van Lissa [aut, cre] (ORCID:

<https://orcid.org/0000-0002-0808-5024>),

Aaron Peikert [aut] (ORCID: <https://orcid.org/0000-0001-7813-818X>),

Andreas M. Brandmaier [aut] (ORCID:
 <<https://orcid.org/0000-0001-8765-6982>>)

Maintainer Caspar J. Van Lissa <c.j.vanlissa@tilburguniversity.edu>

Repository CRAN

Date/Publication 2026-02-22 15:00:02 UTC

Contents

| | |
|---|----|
| add_endpoint | 3 |
| add_license_file | 4 |
| add_manuscript | 5 |
| add_preregistration | 7 |
| add_recipe | 8 |
| add_synthetic | 9 |
| add_targets | 11 |
| add_testthat | 11 |
| check_endpoints | 12 |
| check_worcs | 13 |
| check_worcs_installation | 14 |
| cite_all | 15 |
| cite_essential | 16 |
| closed_data | 17 |
| data_label | 18 |
| data_unlabel | 19 |
| descriptives | 20 |
| export_project | 20 |
| github_action_check_endpoints | 21 |
| git_ignore | 22 |
| git_release_publish | 23 |
| git_remote_connect | 23 |
| git_remote_create | 24 |
| git_update | 25 |
| git_user | 26 |
| has_git_user | 27 |
| list_endpoints | 27 |
| load_data | 28 |
| load_entrypoint | 29 |
| make_codebook | 30 |
| notify_synthetic | 31 |
| open_data | 33 |
| remove_endpoint | 34 |
| reproduce | 35 |
| skew_kurtosis | 36 |
| snapshot_endpoints | 37 |
| synthetic | 38 |
| worcs_badge | 40 |
| worcs_checklist | 41 |

add_endpoint 3

worcs_path 42
worcs_project 43
worcs_root 44

Index 46

`add_endpoint` *Add endpoint to WORCS project*

Description

Add a specific endpoint to the WORCS project file (a filename, or "testthat" integration tests), see Details.

Usage

```
add_endpoint(filename = NULL, worcs_directory = ".", verbose = TRUE, ...)
```

Arguments

`filename` Character, indicating a file to be tracked as endpoint, or "testthat" to add a folder of integration tests as endpoints. Default: NULL.

`worcs_directory` Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. Default: '.'

`verbose` Logical. Whether or not to print status messages to the console. Default: TRUE

... Additional arguments.

Details

Endpoints are either:

1. Files that are expected to be exactly reproducible (e.g., "manuscript.html", "myfigure.png", "results_table.csv", et cetera). For individual files, reproducibility is checked by ensuring that the endpoint's checksum is unchanged, see [digest](#). Be mindful that the checksum also changes if two files are practically, but not literally, identical. This can occur when using random numbers anywhere in your analysis (e.g., Monte Carlo estimation, or even jittering points in a plot), or when numbers are rounded differently in the 15th decimal on different computers.
2. A folder of integration tests, created using the `testthat` package (see [add_testthat](#)). Note that `testthat` allows you, for example, to test whether numbers are equal within rounding tolerance.

Value

No return value. This function is called for its side effects.

See Also

[snapshot_endpoints](#) [check_endpoints](#)

Examples

```
# Create directory to run the example
old_wd <- getwd()
test_dir <- file.path(tempdir(), "add_endpoint")
dir.create(test_dir)
setwd(test_dir)
file.create(".worcs")
writeLines("test", "test.txt")
add_endpoint("test.txt")
# Cleaning example directory
setwd(old_wd)
unlink(test_dir, recursive = TRUE)
```

add_license_file *Add License File to Project*

Description

This function wraps usethis' [licenses](#) functions, which are designed for R-packages. This function makes them applicable to other use cases (e.g., WORCS projects, FAIR theory).

Usage

```
add_license_file(path = ".", license = "ccby", ...)
```

Arguments

| | |
|---------|--|
| path | Character, indicating the directory in which to create the license file. Default: <code>'.'</code> . |
| license | Character, indicating which license function to call. The usethis functions all have the form <code>use_{licensename}_license()</code> . The license argument consists only of the <code>{licensename}</code> , e.g. <code>ccby</code> . |
| ... | Additional arguments passed to usethis function. |

Value

No return value. This function is called for its side effects.

Examples

```

if(requireNamespace("withr", quietly = TRUE)){
  withr::with_tempdir({
    add_license_file(path = ".",
                    license = "proprietary",
                    copyright_holder = "test")
  })
}

```

| | |
|----------------|---------------------------------|
| add_manuscript | <i>Add Rmarkdown manuscript</i> |
|----------------|---------------------------------|

Description

Adds an Rmarkdown manuscript to a 'worcs' project.

Usage

```

add_manuscript(
  worcs_directory = ".",
  manuscript = "APA6",
  remote_repo = NULL,
  verbose = TRUE,
  ...
)

```

Arguments

| | |
|-----------------|--|
| worcs_directory | Character, indicating the directory in which to create the manuscript files. Default: '.', which points to the current working directory. |
| manuscript | Character, indicating what template to use for the 'R Markdown' manuscript. Default: 'APA6'. Available choices include: "APA6", "github_document", "None" and the templates from the rticles package. See Details. |
| remote_repo | Character, 'https' link to the remote repository for this project. This link should have the form https://[...].git. This link will be inserted in the draft manuscript. |
| verbose | Logical. Whether or not to print messages to the console during project creation. Default: TRUE |
| ... | Additional arguments passed to and from functions. |

Details

Available choices include the following manuscript templates:

'APA6' An APA6 style template from the `papa` package

'github_document' A [github_document](#) from the rmarkdown package
'acm_article' acm style template from the rtices package
'acs_article' acs style template from the rtices package
'aea_article' aea style template from the rtices package
'agu_article' agu style template from the rtices package
'ajs_article' ajs style template from the rtices package
'amq_article' amq style template from the rtices package
'ams_article' ams style template from the rtices package
'arxiv_article' arxiv style template from the rtices package
'asa_article' asa style template from the rtices package
'bioinformatics_article' bioinformatics style template from the rtices package
'biometrics_article' biometrics style template from the rtices package
'copernicus_article' copernicus style template from the rtices package
'ctex_article' ctex style template from the rtices package
'elsevier_article' elsevier style template from the rtices package
'frontiers_article' frontiers style template from the rtices package
'glossa_article' glossa style template from the rtices package
'ieee_article' ieee style template from the rtices package
'ims_article' ims style template from the rtices package
'informs_article' informs style template from the rtices package
'iop_article' iop style template from the rtices package
'isba_article' isba style template from the rtices package
'jasa_article' jasa style template from the rtices package
'jedm_article' jedm style template from the rtices package
'joss_article' joss style template from the rtices package
'jss_article' jss style template from the rtices package
'lipics_article' lipics style template from the rtices package
'mdpi_article' mdpi style template from the rtices package
'mnras_article' mnras style template from the rtices package
'oup_article' oup style template from the rtices package
'peerj_article' peerj style template from the rtices package
'pihph_article' pihph style template from the rtices package
'plos_article' plos style template from the rtices package
'pnas_article' pnas style template from the rtices package
'rjournal_article' rjournal style template from the rtices package
'rsos_article' rsos style template from the rtices package
'rss_article' rss style template from the rtices package

'sage_article' sage style template from the rtices package
 'sim_article' sim style template from the rtices package
 'springer_article' springer style template from the rtices package
 'tf_article' tf style template from the rtices package
 'trb_article' trb style template from the rtices package
 'wellcomeor_article' wellcomeor style template from the rtices package

Value

No return value. This function is called for its side effects.

Examples

```
the_test <- "worcs_manuscript"
old_wd <- getwd()
dir.create(file.path(tempdir(), the_test))
file.create(file.path(tempdir(), the_test, ".worcs"))
add_manuscript(file.path(tempdir(), the_test),
               manuscript = "None")
setwd(old_wd)
unlink(file.path(tempdir(), the_test))
```

add_preregistration *Add Rmarkdown preregistration*

Description

Adds an Rmarkdown preregistration template to a 'worcs' project.

Usage

```
add_preregistration(
  worcs_directory = ".",
  preregistration = "cos_prereg",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|-----------------|---|
| worcs_directory | Character, indicating the directory in which to create the manuscript files. Default: '.', which points to the current working directory. |
| preregistration | Character, indicating what template to use for the preregistration. Default: "cos_prereg"; use "None" to omit a preregistration. See Details for other available choices. |
| verbose | Logical. Whether or not to print messages to the console during project creation. Default: TRUE |
| ... | Additional arguments passed to and from functions. |

Details

Available choices include the templates from the [prereg](#) package, and several unique templates included with worcs:

- 'PSS' Preregistration and Sharing Software (Krypotos, Klugkist, Mertens, & Engelhard, 2019)
- 'Secondary' Preregistration for secondary analyses (Mertens & Krypotos, 2019)
- 'aspredicted_prereg' aspredicted template from the prereg package
- 'brandt_prereg' brandt template from the prereg package
- 'cos_prereg' cos template from the prereg package
- 'fmri_prereg' fmri template from the prereg package
- 'prp_quant_prereg' prp_quant template from the prereg package
- 'psyquant_prereg' psyquant template from the prereg package
- 'rr_prereg' rr template from the prereg package
- 'vantveer_prereg' vantveer template from the prereg package

Value

No return value. This function is called for its side effects.

Examples

```
the_test <- "worcs_prereg"
old_wd <- getwd()
dir.create(file.path(tempdir(), the_test))
file.create(file.path(tempdir(), the_test, ".worcs"))
add_preregistration(file.path(tempdir(), the_test),
                    preregistration = "cos_prereg")
setwd(old_wd)
unlink(file.path(tempdir(), the_test))
```

add_recipe

Add Recipe to Generate Endpoints

Description

Add a recipe to a WORCS project file to generate its endpoints.

Usage

```
add_recipe(
  worcs_directory = ".",
  recipe = "rmarkdown::render('manuscript/manuscript.Rmd')",
  terminal = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|-----------------|--|
| worcs_directory | Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. Default: '.' |
| recipe | Character string, indicating the function call to evaluate in order to reproduce the endpoints of the WORCS project. |
| terminal | Logical, indicating whether or not to evaluate the recipe in the terminal (TRUE) or in R (FALSE). Defaults to FALSE |
| verbose | Logical. Whether or not to print status messages to the console. Default: TRUE |
| ... | Additional arguments. |

Value

No return value. This function is called for its side effects.

See Also

[add_endpoint](#) [snapshot_endpoints](#) [check_endpoints](#)

Examples

```
# Create directory to run the example
if(requireNamespace("withr", quietly = TRUE)){
  withr::with_tempdir({
    file.create(".worcs")
    writeLines("test", "test.txt")
    add_recipe()
  })
}
```

add_synthetic

Add synthetic data to WORCS project

Description

This function adds a user-specified synthetic data resource for public use to a WORCS project with closed data.

Usage

```
add_synthetic(
  data,
  synthetic_name = paste0("synthetic_", original_name),
  original_name,
  worcs_directory = ".",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|-----------------|---|
| data | A data.frame containing the synthetic data. |
| synthetic_name | Character, naming the file synthetic data should be written to. By default, prepends "synthetic_" to the original_name. |
| original_name | Character, naming an existing data resource in the WORCS project with which to associate the synthetic data object. |
| worcs_directory | Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. |
| verbose | Logical. Whether or not to print status messages to the console. Default: TRUE |
| ... | Additional arguments passed to and from functions. |

Value

Returns NULL invisibly. This function is called for its side effects.

See Also

open_data closed_data save_data

Examples

```
# Create directory to run the example
old_wd <- getwd()
test_dir <- file.path(tempdir(), "add_synthetic")
dir.create(test_dir)
setwd(test_dir)
worcs::write_worcsfile(".worcs")
# Prepare data
df <- iris[1:3, ]
# Run closed_data without synthetic
closed_data(df, codebook = NULL, synthetic = FALSE)
# Manually add synthetic
add_synthetic(df, original_name = "df.csv")
# Remove original from file and environment
file.remove("df.csv")
rm(df)
# See that load_data() now loads the synthetic file
load_data()
# Cleaning example directory
setwd(old_wd)
unlink(test_dir, recursive = TRUE)
```

| | |
|-------------|-------------------------------------|
| add_targets | <i>Add targets to WORCS Project</i> |
|-------------|-------------------------------------|

Description

Add a computational pipeline to a worcs project using the targets and tarchetypes packages (which must be installed). See those packages for extensive documentation.

Usage

```
add_targets(worcs_directory = ".", verbose = TRUE, ...)
```

Arguments

| | |
|-----------------|--|
| worcs_directory | Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. Default: '.' |
| verbose | Logical. Whether or not to print status messages to the console. Default: TRUE |
| ... | Arguments passed to targets::use_targets(). |

Value

No return value. This function is called for its side effects.

Examples

```
# Create directory to run the example
old_wd <- getwd()
test_dir <- file.path(tempdir(), "targets")
dir.create(test_dir)
setwd(test_dir)
file.create(".worcs")
add_targets()
# Cleaning example directory
setwd(old_wd)
unlink(test_dir, recursive = TRUE)
```

| | |
|--------------|--------------------------------------|
| add_testthat | <i>Add testthat to WORCS Project</i> |
|--------------|--------------------------------------|

Description

Wraps [use_testthat](#) to add integration testing to a WORCS Project.

As testthat is primarily geared towards integration tests for 'R' packages, this function conducts testthat test for WORCS projects.

Usage

```
add_testthat(worcs_directory = ".", ...)

test_worcs(worcs_directory = ".", ...)
```

Arguments

```
worcs_directory
PARAM_DESCRIPTION, Default: '?'

...
Additional arguments passed to other functions.
```

Value

No return value. This function is called for its side effects.

No return value. This function is called for its side effects.

Examples

```
if(requireNamespace("withr", quietly = TRUE) &
  requireNamespace("testthat", quietly = TRUE)){
  withr::with_tempdir({
    usethis::create_project(path = ".", rstudio = FALSE, open = FALSE)
    add_testthat()
  })
}
if(requireNamespace("withr", quietly = TRUE) &
  requireNamespace("testthat", quietly = TRUE)){
  tmpdr <- file.path(tempdir(), "testworcs")
  usethis::create_project(path = tmpdr, rstudio = FALSE, open = FALSE)
  usethis::with_project(tmpdr, {
    writeLines("", ".worcs")
    add_testthat()
    usethis::use_test(name = "testme", open = FALSE)
    test_worcs()
  })
}
```

check_endpoints

Check endpoints in WORCS project

Description

Check that the checksums of all endpoints in a WORCS project match their snapshots.

Usage

```
check_endpoints(worcs_directory = ".", verbose = TRUE, ...)
```

Arguments

| | |
|-----------------|--|
| worcs_directory | Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. Default: '.' |
| verbose | Logical. Whether or not to print status messages to the console. Default: TRUE |
| ... | Additional arguments. |

Value

Returns a logical value (TRUE/FALSE) invisibly.

See Also

[add_endpoint](#) [snapshot_endpoints](#)

Examples

```
# Create directory to run the example
old_wd <- getwd()
test_dir <- file.path(tempdir(), "check_endpoint")
dir.create(test_dir)
setwd(test_dir)
file.create(".worcs")
writeLines("test", "test.txt")
add_endpoint("test.txt")
check_endpoints()
# Cleaning example directory
setwd(old_wd)
unlink(test_dir, recursive = TRUE)
```

check_worcs

Evaluate project with respect to WORCS checklist

Description

Evaluates whether a project meets the criteria of the WORCS checklist (see [worcs_checklist](#)).

Usage

```
check_worcs(path = ".", verbose = TRUE)
```

Arguments

| | |
|---------|---|
| path | Character. Path to a WORCS project folder (a project with a .worcs file). Default: '.' (path to current directory). |
| verbose | Logical. Whether or not to show status messages while evaluating the checklist. Default: TRUE. |

Value

A data.frame with a description of the criteria, and a column with evaluations (\$pass). For criteria that must be evaluated manually, \$pass will be FALSE.

Examples

```
example_dir <- file.path(tempdir(), "badge")
dir.create(example_dir)
write("a", file.path(example_dir, ".worcs"))
check_worcs(path = example_dir)
```

check_worcs_installation

Check worcs dependencies

Description

This function checks that all worcs dependencies are correctly installed, and suggests how to remedy any missing dependencies.

Usage

```
check_worcs_installation(what = "all")

check_dependencies(package = "worcs")

check_git()

check_github(pat = TRUE, ssh = FALSE)

check_ssh()

check_tinytex()

check_rmarkdown()

check_renv()

check_renv_synchronized(worcs_directory = ".", ...)
```

Arguments

| | |
|---------|---|
| what | Character vector indicating which dependencies to check. Default: "all". All checks defined in the Usage section can be called, e.g. check_git can be called using the argument what = "git". |
| package | Atomic character vector, indicating for which package to check the dependencies. |

| | |
|-----------------|---|
| pat | Logical, whether to run tests for the existence and functioning of a GitHub Personal Access Token (PAT). This is the preferred method of authentication, so defaults to TRUE. |
| ssh | Logical, whether to run tests for the existence and functioning of an SSH key. This method of authentication is not recommended, so defaults to FALSE. |
| worcs_directory | Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. |
| ... | Additional parameters passed to and from functions. |

Value

Logical, indicating whether all checks passed or not.

Examples

```
check_worcs_installation("none")
```

cite_all

Comprehensive citation Knit function for 'RStudio'

Description

This is a wrapper for [render](#). First, this function parses the citations in the document, converting citations marked with double at sign, e.g.: @@reference2020, into normal citations, e.g.: @reference2020. Then, it renders the file.

Usage

```
cite_all(...)
```

Arguments

... All arguments are passed to [render](#).

Value

Returns NULL invisibly. This function is called for its side effect of rendering an 'R Markdown' file.

Examples

```
# NOTE: Do not use this function interactively, as in the example below.
# Only specify it as custom knit function in an 'R Markdown' file, like so:
# knit: worcs::cite_all

if (rmarkdown::pandoc_available("2.0")){
  if(requireNamespace("withr", quietly = TRUE)){
    withr::with_tempdir({
```

```

file_name <- file.path("citeall.Rmd")
loc <- rmarkdown::draft(file_name,
                        template = "github_document",
                        package = "rmarkdown",
                        create_dir = FALSE,
                        edit = FALSE)
write(c("", "Optional reference: @reference2020"),
      file = file_name, append = TRUE)
cite_all(file_name)
}, pattern = "cite_all")
}
}

```

cite_essential

Essential citations Knit function for 'RStudio'

Description

This is a wrapper for [render](#). First, this function parses the citations in the document, removing citations marked with double at sign, e.g.: @@reference2020. Then, it renders the file.

Usage

```
cite_essential(...)
```

Arguments

... All arguments are passed to [render](#).

Value

Returns NULL invisibly. This function is called for its side effect of rendering an 'R Markdown' file.

Examples

```

# NOTE: Do not use this function interactively, as in the example below.
# Only specify it as custom knit function in an R Markdown file, like so:
# knit: worcs::cite_all

```

```

if (rmarkdown::pandoc_available("2.0")){
  file_name <- tempfile("citeessential", fileext = ".Rmd")
  rmarkdown::draft(file_name,
                  template = "github_document",
                  package = "rmarkdown",
                  create_dir = FALSE,
                  edit = FALSE)
  write(c("", "Optional reference: @reference2020"),
        file = file_name, append = TRUE)
  cite_essential(file_name)
}

```

closed_data

Use closed data in WORCS project

Description

This function saves a data.frame as a .csv file (using [write.csv](#)), stores a checksum in '.worcs', appends the .gitignore file to exclude filename, and saves a synthetic copy of data for public use. To generate these synthetic data, the function [synthetic](#) is used.

Usage

```
closed_data(
  data,
  filename = paste0(deparse(substitute(data)), ".csv"),
  codebook = paste0("codebook_", deparse(substitute(data)), ".Rmd"),
  value_labels = paste0("value_labels_", deparse(substitute(data)), ".yaml"),
  worcs_directory = ".",
  synthetic = TRUE,
  save_expression = write.csv(x = data, file = filename, row.names = FALSE),
  load_expression = read.csv(file = filename, stringsAsFactors = TRUE),
  ...
)
```

Arguments

| | |
|-----------------|---|
| data | A data.frame to save. |
| filename | Character, naming the file data should be written to. By default, constructs a filename from the name of the object passed to data. |
| codebook | Character, naming the file the codebook should be written to. An 'R Markdown' codebook will be created and rendered to github_document ('markdown' for 'GitHub'). By default, constructs a filename from the name of the object passed to data, adding the word 'codebook'. Set this argument to NULL to avoid creating a codebook. |
| value_labels | Character, naming the file the value labels of factors and ordinal variables should be written to. By default, constructs a filename from the name of the object passed to data, adding the word 'value_labels'. Set this argument to NULL to avoid creating a file with value labels. |
| worcs_directory | Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. |
| synthetic | Logical, indicating whether or not to create a synthetic dataset using the synthetic function. Additional arguments for the call to synthetic can be passed through |

`save_expression`
 An R-expression used to save the data. Defaults to `write.csv(x = data, file = filename, row.names = FALSE)`, which writes a comma-separated, spreadsheet-style file. The arguments `data` and `filename` are passed from `open_data()` to the expression defined in `save_expression`.

`load_expression`
 An R-expression used to load the data from the file created by `save_expression`. Defaults to `read.csv(file = filename, stringsAsFactors = TRUE)`. This expression is stored in the project's `.worcs` file, and invoked by `load_data()`.

... Additional arguments passed to and from functions.

Value

Returns NULL invisibly. This function is called for its side effects.

See Also

`open_data` `closed_data` `save_data`

Examples

```
if(requireNamespace("withr", quietly = TRUE)){
  withr::with_tempdir({
    file.create(".worcs")
    df <- iris[1:3, ]
    df$Species <- droplevels(df$Species)
    closed_data(df, codebook = NULL)
  })
}
```

data_label

Label factor variables using metadata

Description

For each column of `x`, this function checks whether value labels exist in `value_labels`. If so, integer values are replaced with these value labels.

Usage

```
data_label(
  x,
  variables = names(x),
  value_labels = read_yaml(paste0("value_labels_", substitute(x), ".yaml"))
)
```

Arguments

| | |
|--------------|--|
| x | A data.frame. |
| variables | Column names of x to replace, Default: names(x) |
| value_labels | A list with value labels, typically read from metadata generated by open_data or closed_data . Default: read_yaml(paste0("value_labels_", substitute(x), ".yaml")) |

Value

A data.frame.

Examples

```
## Not run:
if(interactive()){
  labs <- list(x = list(class = "factor", `1` = "a", `2` = "b"))
  df <- data.frame(x = 1:2)
  df <- data_label(df, value_labels = labs)
}

## End(Not run)
```

| | |
|--------------|--------------------------|
| data_unlabel | <i>Drop value labels</i> |
|--------------|--------------------------|

Description

Coerces factor and ordered variables to class integer.

Usage

```
data_unlabel(x, variables = names(x)[sapply(x, inherits, what = "factor")])
```

Arguments

| | |
|-----------|---|
| x | A data.frame. |
| variables | Column names of x to coerce to integer. |

Value

A data.frame.

Examples

```
## Not run:
if(interactive()){
  df <- data.frame(x = factor(c("a", "b")))
  df <- data_unlabel(df)
}

## End(Not run)
```

descriptives*Describe a dataset*

Description

Provide descriptive statistics for a dataset.

Usage

```
descriptives(x, ...)
```

Arguments

`x` An object for which a method exists.
`...` Additional arguments.

Value

A `data.frame` with descriptive statistics for `x`.

Examples

```
descriptives(iris)
```

export_project*Export project to .zip file*

Description

Export project to .zip file

Usage

```
export_project(zipfile = NULL, worcs_directory = ".", open_data = TRUE)
```

Arguments

| | |
|-----------------|--|
| zipfile | Character. Path to a .zip file that is to be created. The default argument NULL creates a .zip file in the directory one level above the 'worcs' project directory. By default, all files tracked by 'Git' are included in the .zip file, excluding 'data.csv' if open_data = FALSE. |
| worcs_directory | Character. Path to the WORCS project directory to export. Defaults to ".", which refers to the current working directory. |
| open_data | Logical. Whether or not to include the original data, 'data.csv', if this file exists. If open_data = FALSE and an open data file does exist, then it is excluded from the .zip file. If it does not yet exist, a synthetic data set is generated and added to the .zip file. |

Value

Logical, indicating the success of the operation. This function is called for its side effect of creating a .zip file.

Examples

```
export_project(worcs_directory = tempdir())
```

```
github_action_check_endpoints
```

Set up GitHub Actions to Check Endpoints

Description

Sets up a GitHub Action to perform continuous integration (CI) for a WORCS project. CI automatically evaluates check_endpoints() or reproduce(check_endpoints = TRUE). at each push or pull request.

Usage

```
github_action_check_endpoints(worcs_directory = ".")
```

```
github_action_reproduce(worcs_directory = ".")
```

```
github_action_testthat(worcs_directory = ".")
```

Arguments

| | |
|-----------------|--|
| worcs_directory | Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. Default: '.' |
|-----------------|--|

Value

No return value. This function is called for its side effects.

See Also

[use_github_action](#) [add_endpoint](#) [check_endpoints](#)

git_ignore

Modify .gitignore file

Description

Arguments passed through ... are added to the .gitignore file. Elements already present in the file are modified. When ignore = TRUE, the arguments are added to the .gitignore file, which will cause 'Git' to not track them.

When ignore = FALSE, the arguments are prepended with !, This works as a "double negation", and will cause 'Git' to track the files.

Usage

```
git_ignore(..., ignore = TRUE, repo = ".")
```

Arguments

| | |
|--------|--|
| ... | Any number of character arguments, representing files to be added to the .gitignore file. |
| ignore | Logical. Whether or not 'Git' should ignore these files. |
| repo | a path to an existing repository, or a git_repository object as returned by git_open, git_init or git_clone. |

Value

No return value. This function is called for its side effects.

Examples

```
if(requireNamespace("withr", quietly = TRUE)){
  withr::with_tempdir({
    dir.create(".git")
    git_ignore("ignorethis.file")
  })
}
```

git_release_publish *Publish a Release on 'GitHub'*

Description

Given that a 'GitHub' user is configured, with the appropriate permissions, this function pushes the current branch (if safe), then publishes a 'GitHub' Release of the repository indicated by repo to that user's account.

Usage

```
git_release_publish(repo = ".", tag_name = NULL, release_name = NULL)
```

Arguments

| | |
|--------------|---|
| repo | The path to the 'Git' repository. |
| tag_name | Optional character string to specify the tag name. By default, this is set to NULL and git_release_publish() uses version numbers starting with 0.1.0 for both the tag_name and release_name arguments. Override this behavior, for example, to increment the major version number by specifying 0.2.0. |
| release_name | Optional character string to specify the tag name. By default, this is set to NULL and git_release_publish() uses version numbers starting with 0.1.0 for both the tag_name and release_name arguments. Override this behavior, for example, to increment the major version number by specifying 0.2.0. |

Value

No return value. This function is called for its side effects.

Examples

```
## Not run:  
git_release_publish()  
  
## End(Not run)
```

git_remote_connect *Connect to Existing 'GitHub' Repository*

Description

Given that a 'GitHub' user is configured, with the appropriate permissions, this function connects to an existing repository.

Usage

```
git_remote_connect(repo, remote_repo)
```

Arguments

| | |
|-------------|--|
| repo | a path to an existing repository, or a git_repository object as returned by git_open, git_init or git_clone. |
| remote_repo | Character, indicating the name of a repository on your account. |

Value

Invisibly returns a list with the following elements:

- repo_url: Character, URL of the connected repository
- repo_exists: Logical
- prior_commits: Logical

See Also

[gh_whoami](#) [git_fetch](#), [git_remote](#)

Examples

```
## Not run:  
git_remote_connect()  
  
## End(Not run)
```

git_remote_create *Create a New 'GitHub' Repository*

Description

Given that a 'GitHub' user is configured, with the appropriate permissions, this function creates a new repository on your account.

Usage

```
git_remote_create(name, private = TRUE)
```

Arguments

| | |
|---------|---|
| name | Name of the repository to be created. |
| private | Whether or not the repository should be private, defaults to FALSE. |

Value

Invisibly returns a logical value, indicating whether the function was successful or not.

Examples

```
## Not run:
git_remote_create()

## End(Not run)
```

| | |
|------------|---------------------------------------|
| git_update | <i>Add, commit, and push changes.</i> |
|------------|---------------------------------------|

Description

This function is a wrapper for `git_add`, `git_commit`, and `git_push`. It adds all locally changed files to the staging area of the local 'Git' repository, then commits these changes (with an optional message, and then pushes them to a remote repository. This is used for making a "cloud backup" of local changes. Do not use this function when working with privacy sensitive data, or any other file that should not be pushed to a remote repository. The `git_add` argument `force` is disabled by default, to avoid accidentally committing and pushing a file that is listed in `.gitignore`.

Usage

```
git_update(
  message = paste0("update ", Sys.time()),
  files = ".",
  repo = ".",
  author,
  committer,
  remote,
  refspec,
  password,
  ssh_key,
  mirror,
  force,
  verbose = TRUE
)
```

Arguments

| | |
|-----------|--|
| message | a commit message |
| files | vector of paths relative to the git root directory. Use "." to stage all changed files. |
| repo | a path to an existing repository, or a <code>git_repository</code> object as returned by <code>git_open</code> , <code>git_init</code> or <code>git_clone</code> . |
| author | A <code>git_signature</code> value, default is <code>git_signature_default</code> . |
| committer | A <code>git_signature</code> value, default is same as author |
| remote | name of a remote listed in <code>git_remote_list()</code> |
| refspec | string with mapping between remote and local refs |

| | |
|----------|--|
| password | a string or a callback function to get passwords for authentication or password protected ssh keys. Defaults to askpass which checks <code>getOption('askpass')</code> . |
| ssh_key | path or object containing your ssh private key. By default we look for keys in ssh-agent and <code>credentials::ssh_key_info</code> . |
| mirror | use the <code>-mirror</code> flag |
| force | use the <code>-force</code> flag |
| verbose | display some progress info while downloading |

Value

No return value. This function is called for its side effects.

Examples

```
git_update()
```

| | |
|----------|-------------------------------------|
| git_user | <i>Set global 'Git' credentials</i> |
|----------|-------------------------------------|

Description

This function is a wrapper for [git_config_global_set](#). It sets two name/value pairs at once: `name = "user.name"` is set to the value of the `name` argument, and `name = "user.email"` is set to the value of the `email` argument.

Usage

```
git_user(name, email, overwrite = !has_git_user(), verbose = TRUE)
```

Arguments

| | |
|-----------|---|
| name | Character. The user name you want to use with 'Git'. |
| email | Character. The email address you want to use with 'Git'. |
| overwrite | Logical. Whether or not to overwrite existing 'Git' credentials. Use this to prevent code from accidentally overwriting existing 'Git' credentials. The default value uses has_git_user to set <code>overwrite</code> to <code>FALSE</code> if user credentials already exist, and to <code>TRUE</code> if no user credentials exist. |
| verbose | Logical. Whether or not to print status messages to the console. Default: <code>TRUE</code> |

Value

No return value. This function is called for its side effects.

Examples

```
git_user("name", "email", overwrite = FALSE)
```

| | |
|--------------|---|
| has_git_user | <i>Check whether global 'Git' credentials exist</i> |
|--------------|---|

Description

Check whether the values `user.name` and `user.email` exist exist for the current repository. Uses `git_signature_default`.

Usage

```
has_git_user(repo = ".")
```

Arguments

| | |
|------|---------------------------------|
| repo | The path to the git repository. |
|------|---------------------------------|

Value

Logical, indicating whether 'Git' global configuration settings could be retrieved, and contained the values `user.name` and `user.email`.

Examples

```
testdir <- file.path(tempdir(), "test_git_user")
dir.create(testdir)
gert::git_init(testdir)
has_git_user(testdir)
unlink(testdir, recursive = TRUE)
```

| | |
|----------------|--|
| list_endpoints | <i>List endpoints in WORCS project</i> |
|----------------|--|

Description

List the endpoints in a WORCS project.

Usage

```
list_endpoints(worcs_directory = ".", verbose = TRUE, ...)
```

Arguments

| | |
|-----------------|--|
| worcs_directory | Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. Default: '.' |
| verbose | Logical. Whether or not to print status messages to the console. Default: TRUE |
| ... | Additional arguments. |

Value

None, prints to the console.

See Also

[add_endpoint](#) [snapshot_endpoints](#)

Examples

```
if(requireNamespace("withr", quietly = TRUE)){
  withr::with_tempdir({
    file.create(".worcs")
    write.csv(iris, "iris.csv")
    add_endpoint("iris.csv")
    list_endpoints()
  })
}
```

load_data

Load WORCS project data

Description

Scans the WORCS project file for data that have been saved using [open_data](#) or [closed_data](#), and loads these data into the global (working) environment. The function will load the original data if available on the current system. If only a synthetic dataset is available, this function loads the synthetic data. The name of the object containing the data is derived from the file name by removing the file extension, and, when applicable, the prefix "synthetic_". Thus, both "data.csv" and "synthetic_data.csv" will be loaded into an object called data.

Usage

```
load_data(
  worcs_directory = ".",
  to_envir = TRUE,
  envir = parent.frame(1),
  verbose = TRUE,
  use_metadata = TRUE
)
```

Arguments

worcs_directory

Character, indicating the WORCS project directory from which to load data. The default value "." points to the current directory.

| | |
|--------------|---|
| to_envir | Logical, indicating whether to load objects directly into the environment, or return a list containing the objects. The environment is designated by argument <code>envir</code> . Loading objects directly into the global environment is user-friendly, but has the risk of overwriting an existing object with the same name, as explained in load . The function <code>load_data</code> gives a warning when this happens. |
| envir | The environment where the data should be loaded. The default value <code>parent.frame(1)</code> refers to the global environment in an interactive session. |
| verbose | Logical. Whether or not to print status messages to the console. Default: TRUE |
| use_metadata | Logical. Whether or not to use the codebook and value labels and attempt to coerce the class and values of variables to those recorded therein. Default: TRUE |

Value

Returns a list invisibly. If `to_envir = TRUE`, this list contains the loaded data files. If `to_envir = FALSE`, the list is empty, and the loaded data files are attached directly to the global environment.

Examples

```
if(requireNamespace("withr", quietly = TRUE)){
  withr::with_tempdir({
    file.create(".worcs")
    df <- iris[1:5, ]
    df$Species <- droplevels(df$Species)
    closed_data(df, codebook = NULL)
    temp_env <- new.env()
    load_data(envir = temp_env)
    rm("df", envir = temp_env)
    file.remove("df.csv")
    load_data(envir = temp_env)
  })
}
```

| | |
|-----------------|----------------------------------|
| load_entrypoint | <i>Load project entry points</i> |
|-----------------|----------------------------------|

Description

Loads the designated project entry point into the default editor, using [file.edit](#).

Usage

```
load_entrypoint(worcs_directory = ".", verbose = TRUE, ...)
```

Arguments

| | |
|-----------------|---|
| worcs_directory | Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. |
| verbose | Logical. Whether or not to print status messages to the console. Default: TRUE |
| ... | Additional arguments passed to file.edit . |

Value

No return value. This function is called for its side effects.

Examples

```
## Not run:
if(requireNamespace("withr", quietly = TRUE)){
  withr::with_tempdir({
    # Prepare worcs file and dummy entry point
    worcs::write_worcsfile(".worcs", entry_point = "test.txt")
    writeLines("Hello world", con = file("test.txt", "w"))
    # Demonstrate load_entrypoint()
    load_entrypoint()
  })
}

## End(Not run)
```

make_codebook

Create codebook for a dataset

Description

Creates a codebook for a dataset in 'R Markdown' format, and renders it to 'markdown' for 'GitHub'. A codebook contains metadata and documentation for a data file. We urge users to customize the automatically generated 'R Markdown' document and re-knit it, for example, to add a paragraph with details on the data collection procedures. The variable descriptives are stored in a .csv file, which can be edited in 'R' or a spreadsheet program. Columns can be appended, and we encourage users to complete at least the following two columns in this file:

category Describe the type of variable in this column. For example: "morality".

description Provide a plain-text description of the variable. For example, the full text of a questionnaire item: "People should be willing to do anything to help a member of their family".

Re-knitting the 'R Markdown' file (using [render](#)) will transfer these changes to the 'markdown' file for 'GitHub'.

Usage

```
make_codebook(
  data,
  filename = "codebook.Rmd",
  render_file = TRUE,
  csv_file = gsub("rmd$", "csv", filename, ignore.case = TRUE),
  verbose = TRUE
)
```

Arguments

| | |
|-------------|--|
| data | A data.frame for which to create a codebook. |
| filename | Character. File name to write the codebook rmarkdown file to. |
| render_file | Logical. Whether or not to render the document. |
| csv_file | Character. File name to write the codebook rmarkdown file to. By default, uses the filename stem of the filename argument. Set to NULL to write the codebook only to the 'R Markdown' file, and not to .csv. |
| verbose | Logical. Whether or not to print status messages to the console. Default: TRUE |

Value

Logical, indicating whether or not the operation was successful. This function is mostly called for its side effect of rendering an 'R Markdown' codebook.

Examples

```
if(rmarkdown::pandoc_available("2.0")){
  library(rmarkdown)
  library(knitr)
  filename <- tempfile("codebook", fileext = ".Rmd")
  make_codebook(iris, filename = filename, csv_file = NULL)
  unlink(c(
    ".worcs",
    filename,
    gsub("\\.Rmd", "\\md", filename),
    gsub("\\.Rmd", "\\html", filename),
    gsub("\\.Rmd", "_files", filename)
  ), recursive = TRUE)
}
```

 notify_synthetic

Notify the user when synthetic data are being used

Description

This function prints a notification message when some or all of the data used in a project are synthetic (see [closed_data](#) and [synthetic](#)). See details for important information.

Usage

```
notify_synthetic(..., msg = NULL, worcs_directory = ".")
```

Arguments

`...` Objects of class `worcs_data`. The function will check if these are original or synthetic data.

`msg` Expression containing the message to print in case not all `worcs_data` are original.

`worcs_directory` Character, indicating the WORCS project directory to which to save data. The default value `"."` points to the current directory.

Details

The preferred way to use this function is to provide specific data objects in the function call, using the `...` argument. If no such objects are provided, `notify_synthetic` will scan the parent environment for objects of class `worcs_data`.

This function is emphatically designed to be included in an 'R Markdown' file, to dynamically generate a notification message when a third party 'Knits' such a document without having access to all original data.

Value

No return value. This function is called for its side effect of printing a notification message.

See Also

`closed_data` `synthetic` `add_synthetic`

Examples

```
if(requireNamespace("withr", quietly = TRUE)){
  withr::with_tempdir({
    file.create(".worcs")
    df <- iris
    class(df) <- c("worcs_data", class(df))
    attr(df, "type") <- "synthetic"
    result <- capture.output(notify_synthetic(df, msg = "it is synthetic"))
    if(!grepl("synthetic", result)) stop()
    df <- df[1:10, ]
    closed_data(df, codebook = NULL)
    file.remove("df.csv")
    result <- capture.output(notify_synthetic(msg = "synthetic"))
    if(!grepl("synthetic", result)) stop()
    if(requireNamespace("rmarkdown", quietly = TRUE)){
      add_manuscript(manuscript = "github_document")
      print(readLines("manuscript/manuscript.Rmd"))
      rmarkdown::render("manuscript/manuscript.Rmd")
      if(!any(grepl("reproduced using synthetic",
```

```

      readLines("manuscript/manuscript.html")))) stop()
    }
  })
}

```

open_data

*Use open data in WORCS project***Description**

This function saves a data.frame as a .csv file (using [write.csv](#)), stores a checksum in '.worcs', and amends the .gitignore file to exclude filename.

Usage

```

open_data(
  data,
  filename = paste0(deparse(substitute(data)), ".csv"),
  codebook = paste0("codebook_", deparse(substitute(data)), ".Rmd"),
  value_labels = paste0("value_labels_", deparse(substitute(data)), ".yaml"),
  worcs_directory = ".",
  save_expression = write.csv(x = data, file = filename, row.names = FALSE),
  load_expression = read.csv(file = filename, stringsAsFactors = TRUE),
  ...
)

```

Arguments

| | |
|-----------------|---|
| data | A data.frame to save. |
| filename | Character, naming the file data should be written to. By default, constructs a filename from the name of the object passed to data. |
| codebook | Character, naming the file the codebook should be written to. An 'R Markdown' codebook will be created and rendered to github_document ('markdown' for 'GitHub'). By default, constructs a filename from the name of the object passed to data, adding the word 'codebook'. Set this argument to NULL to avoid creating a codebook. |
| value_labels | Character, naming the file the value labels of factors and ordinal variables should be written to. By default, constructs a filename from the name of the object passed to data, adding the word 'value_labels'. Set this argument to NULL to avoid creating a file with value labels. |
| worcs_directory | Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. |
| save_expression | An R-expression used to save the data. Defaults to <code>write.csv(x = data, file = filename, row.names = FALSE)</code> , which writes a comma-separated, spreadsheet-style file. The arguments data and filename are passed from <code>open_data()</code> to the expression defined in <code>save_expression</code> . |

load_expression An R-expression used to load the data from the file created by save_expression. Defaults to read.csv(file = filename, stringsAsFactors = TRUE). This expression is stored in the project's .worcs file, and invoked by load_data().

... Additional arguments passed to and from functions.

Value

Returns NULL invisibly. This function is called for its side effects.

See Also

open_data closed_data save_data

Examples

```
if(requireNamespace("withr", quietly = TRUE)){
  withr::with_tempdir({
    file.create(".worcs")
    df <- iris[1:5, ]
    open_data(df, codebook = NULL)
  })
}
```

| | |
|-----------------|---|
| remove_endpoint | <i>Remove endpoint from WORCS project</i> |
|-----------------|---|

Description

Remove an endpoint from a WORCS project.

Usage

```
remove_endpoint(filename = NULL, worcs_directory = ".", verbose = TRUE, ...)
```

Arguments

filename Character, indicating the file to be removed from the endpoints. Default: NULL.

worcs_directory Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. Default: '.'

verbose Logical. Whether or not to print status messages to the console. Default: TRUE

... Additional arguments.

Value

None, prints to the console.

See Also

[add_endpoint](#) [snapshot_endpoints](#)

Examples

```
if(requireNamespace("withr", quietly = TRUE)){
  withr::with_tempdir({
    file.create(".worcs")
    write.csv(iris, "iris.csv")
    add_endpoint("iris.csv")
    list_endpoints()
    remove_endpoint("iris.csv")
    list_endpoints()
  })
}
```

reproduce

Reproduce WORCS Project

Description

Evaluate the recipe contained in a WORCS project to derive its endpoints.

Usage

```
reproduce(worcs_directory = ".", verbose = TRUE, check_endpoints = TRUE, ...)
```

Arguments

| | |
|-----------------|--|
| worcs_directory | Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. Default: '.' |
| verbose | Logical. Whether or not to print status messages to the console. Default: TRUE |
| check_endpoints | Logical. Whether or not to call <code>check_endpoints()</code> after reproducing the recipe. Default: TRUE |
| ... | Additional arguments. |

Value

No return value. This function is called for its side effects.

See Also

[add_endpoint](#) [snapshot_endpoints](#) [check_endpoints](#)

Examples

```
# Create directory to run the example
if(requireNamespace("withr", quietly = TRUE)){
  withr::with_tempdir({
    file.create(".worcs")
    worcs::add_recipe(recipe = 'writeLines("test", "test.txt")')
  })
}
```

skew_kurtosis

Calculate skew and kurtosis

Description

Calculate skew and kurtosis, standard errors for both, and the estimates divided by two times the standard error. If this latter quantity exceeds an absolute value of 1, the skew/kurtosis is significant. With very large sample sizes, significant skew/kurtosis is common.

Usage

```
skew_kurtosis(x, verbose = FALSE, se = FALSE, ...)
```

Arguments

| | |
|---------|--|
| x | An object for which a method exists. |
| verbose | Logical. Whether or not to print messages to the console, Default: FALSE |
| se | Whether or not to return the standard errors, Default: FALSE |
| ... | Additional arguments to pass to and from functions. |

Value

A matrix of skew and kurtosis statistics for x.

Examples

```
skew_kurtosis(datasets::anscombe)
```

snapshot_endpoints *Snapshot endpoints in WORCS project*

Description

Update the checksums of all endpoints in a WORCS project.

Usage

```
snapshot_endpoints(worcs_directory = ".", verbose = TRUE, ...)
```

Arguments

| | |
|-----------------|--|
| worcs_directory | Character, indicating the WORCS project directory to which to save data. The default value "." points to the current directory. Default: '.' |
| verbose | Logical. Whether or not to print status messages to the console. Default: TRUE |
| ... | Additional arguments. |

Value

No return value. This function is called for its side effects.

See Also

[add_endpoint](#) [check_endpoints](#)

Examples

```
# Create directory to run the example
old_wd <- getwd()
test_dir <- file.path(tempdir(), "update_endpoint")
dir.create(test_dir)
setwd(test_dir)
file.create(".worcs")
writeLines("test", "test.txt")
add_endpoint("test.txt")
writeLines("second test", "test.txt")
snapshot_endpoints()
# Cleaning example directory
setwd(old_wd)
unlink(test_dir, recursive = TRUE)
```

| | |
|-----------|--------------------------------|
| synthetic | <i>Generate synthetic data</i> |
|-----------|--------------------------------|

Description

Generates a synthetic version of a `data.frame`, with similar characteristics to the original. See Details for the algorithm used.

Usage

```
synthetic(  
  data,  
  model_expression = ranger(x = x, y = y),  
  predict_expression = predict(model, data = xsynth)$predictions,  
  missingness_expression = NULL,  
  verbose = TRUE  
)
```

Arguments

| | |
|-------------------------------------|---|
| <code>data</code> | A <code>data.frame</code> of which to make a synthetic version. |
| <code>model_expression</code> | An R-expression to estimate a model. Defaults to <code>ranger(x = x, y = y)</code> , which uses the fast implementation of random forests in ranger . The expression is evaluated in an environment containing objects <code>x</code> and <code>y</code> , where <code>x</code> is a <code>data.frame</code> with the predictor variables, and <code>y</code> is a vector of outcome values (see Details). |
| <code>predict_expression</code> | An R-expression to generate predicted values based on the model estimated by <code>model_expression</code> . Defaults to <code>predict(model, data = xsynth)\$predictions</code> . This expression must return a vector of predicted values. The expression is evaluated in an environment containing objects <code>model</code> and <code>xsynth</code> , where <code>model</code> is the model estimated by <code>model_expression</code> , and <code>xsynth</code> is the <code>data.frame</code> of synthetic data used to predict the next column (see Details). |
| <code>missingness_expression</code> | Optional. An R-expression to impute missing values. Defaults to <code>NULL</code> , which means listwise deletion is used. The expression is evaluated in an environment containing the object <code>data</code> , as specified in the call to <code>synthetic</code> . It must return a <code>data.frame</code> with the same dimensions and column names as the original data. For example, use <code>missingness_expression = missRanger::missRanger(data = data)</code> for a fast implementation of the excellent 'missForest' single imputation technique. |
| <code>verbose</code> | Logical, Default: <code>TRUE</code> . Whether to show a progress bar while running the algorithm and provide informative messages. |

Details

Based on the work by Nowok, Raab, and Dibben (2016), this function uses a simple algorithm to generate a synthetic dataset with similar characteristics to the original. The algorithm is as follows:

1. Let `x` be the original `data.frame`, with columns 1:j
2. Let `xsynth` be a synthetic `data.frame`, with columns 1:j
3. Column 1 of `xsynth` is a bootstrapped version of column 1 of `x`
4. Using `model_expression`, a predictive model is built for column `c`, for `c` along 2:j, with `c` predicted from columns 1:(c-1) of the original data.
5. Using `predict_expression`, columns 1:(c-1) of the synthetic data are used to predict synthetic values for column `c`.

Variables are thus imputed in order of occurrence in the `data.frame`. To impute in a different order, reorder the data.

Note that, for data synthesis to work properly, it is essential that the class of variables is defined correctly. The default algorithm `ranger` supports numeric, integer, and factor types. Other types of variables should be converted to one of these types, or users can use a custom `model_expression` and `predict_expression` when calling `synthetic`.

Note that for data synthesis to work properly, it is essential that the class of variables is defined correctly. The default algorithm `ranger` supports numeric, integer, factor, and logical data. Other types of variables should be converted to one of these types.

Users can provide use a custom `model_expression` and `predict_expression` to use a different algorithm when calling `synthetic`.

As demonstrated in the example, users could call `lm` as a `model_expression` to use linear regression, which preserves linear marginal relationships but can give rise to values out of range of the original data. Or users could call `sample` as a `predict_expression` to bootstrap each variable, a very quick solution that maintains univariate distributions but loses all marginal relationships. These examples are not exhaustive, and users can even create custom functions.

Value

A `data.frame` with synthetic data, based on `data`.

References

Nowok, B., Raab, G.M and Dibben, C. (2016). `synthpop`: Bespoke creation of synthetic data in R. *Journal of Statistical Software*, 74(11), 1-26. doi:[10.18637/jss.v074.i11](https://doi.org/10.18637/jss.v074.i11).

Examples

```
## Not run:  
# Example using the iris dataset and default ranger algorithm  
iris_syn <- synthetic(iris)  
  
# Example using lm as prediction algorithm (only works for numeric variables)  
# note that, within the model_expression, a new data.frame is created because  
# lm() requires a separate data argument:
```

```

dat <- iris[, 1:4]
result <- synthetic(dat,
  model_expression = lm(.outcome ~ .,
    data = data.frame(.outcome = y,
      xsynth)),
  predict_expression = predict(model, newdata = xsynth), verbose = FALSE)

## End(Not run)
# Example using bootstrapping:
result <- synthetic(iris,
  model_expression = NULL,
  predict_expression = sample(y, size = length(y), replace = TRUE), verbose = FALSE)

## Not run:
# Example with missing data, no imputation
iris_missings <- iris
for(i in 1:10){
  iris_missings[sample.int(nrow(iris_missings), 1, replace = TRUE),
    sample.int(ncol(iris_missings), 1, replace = TRUE)] <- NA
}
iris_miss_syn <- synthetic(iris_missings)

# Example with missing data, imputation by median/mode substitution
# First, define a simple function for median/mode substitution:
imp_fun <- function(x){
  if(is.data.frame(x)){
    return(data.frame(sapply(x, imp_fun)))
  } else {
    out <- x
    if(inherits(x, "numeric")){
      out[is.na(out)] <- median(x[!is.na(out)])
    } else {
      out[is.na(out)] <- names(sort(table(out), decreasing = TRUE))[1]
    }
    out
  }
}

# Then, call synthetic() with this function as missingness_expression:
iris_miss_syn <- synthetic(iris_missings,
  missingness_expression = imp_fun(data))

## End(Not run)

```

worcs_badge

Add WORCS badge to README.md

Description

Evaluates whether a project meets the criteria of the WORCS checklist (see [worcs_checklist](#)), and adds a badge to the project's README .md.

Usage

```
worcs_badge(
  path = ".",
  update_readme = "README.md",
  update_csv = "checklist.csv"
)
```

Arguments

| | |
|---------------|---|
| path | Character. This can either be the path to a WORCS project folder (a project with a .worcs file), or the path to a checklist.csv file. The latter is useful if you want to evaluate a manually updated checklist file. Default: '.' (path to current directory). |
| update_readme | Character. Path to the README.md file to add the badge to. Default: 'README.md'. Set to NULL to avoid updating the README.md file. |
| update_csv | Character. Path to the README.md file to add the badge to. Default: 'checklist.csv'. Set to NULL to avoid updating the checklist.csv file. |

Value

No return value. This function is called for its side effects.

Examples

```
example_dir <- file.path(tempdir(), "badge")
dir.create(example_dir)
write("a", file.path(example_dir, ".worcs"))
worcs_badge(path = example_dir,
  update_readme = NULL)
```

worcs_checklist

WORCS checklist

Description

This checklist can be used to see whether a project adheres to the principles of open reproducible code in science, as set out in the WORCS paper.

Usage

```
data(worcs_checklist)
```

Format

A data frame with 15 rows and 5 variables.

Details

| | | |
|--------------------|---------|---|
| category | factor | Category of the checklist element. |
| name | factor | Name of the checklist element. |
| description | factor | What are the requirements to claim that this checklist element is met? |
| importance | factor | Whether the checklist element is essential to obtain a green 'open science' badge, or optional. |
| check | logical | Whether the criterion is checked automatically by worcs_badge . |

References

Van Lissa, C. J., Brandmaier, A. M., Brinkman, L., Lamprecht, A., Peikert, A., , Struiksma, M. E., & Vreede, B. (2021) [doi:10.3233/DS210031](https://doi.org/10.3233/DS210031).

worcs_path

Specify File Path Relative to WORCS Project Directory

Description

Construct the path to a file inside a worcs project directory in a platform-independent way, see [file.path](#).

Usage

```
worcs_path(..., worcs_directory = ".", fsep = .Platform$file.sep)
```

Arguments

`...` Character vectors, indicating directory- or file names.

`worcs_directory` The project directory (or one of its subdirectories, in which case the project directory is determined via [worcs_root](#)), Default: '.' (current directory).

`fsep` Path separator to use.

Value

Normalized path to file.

Examples

```
if(requireNamespace("withr", quietly = TRUE)){
  withr::with_tempdir({
    writeLines("", ".worcs")
    writeLines("hello world", "myfile.txt")
    file.exists(worcs_path("myfile.txt"))
  })
}
```

| | |
|---------------|---------------------------------|
| worcs_project | <i>Create new WORCS project</i> |
|---------------|---------------------------------|

Description

Creates a new 'worcs' project. This function is invoked by the 'RStudio' project template manager, but can also be called directly to create a WORCS project through syntax or the console.

Usage

```
worcs_project(
  path = "worcs_project",
  manuscript = "APA6",
  preregistration = "cos_prereg",
  add_license = "ccby",
  use_renv = TRUE,
  use_targets = FALSE,
  remote_repo = "https",
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|-----------------|--|
| path | Character, indicating the directory in which to create the 'worcs' project. Default: 'worcs_project'. |
| manuscript | Character, indicating what template to use for the 'R Markdown' manuscript. Default: 'APA6'. Available choices include APA6 from the papaja package, a github_document , and templates included in the rticles package. For more information, see add_manuscript . |
| preregistration | Character, indicating what template to use for the preregistration. Default: 'cos_prereg'. Available choices include: "PSS", "Secondary", "None", and all templates from the prereg package. For more information, see add_preregistration . |
| add_license | Character, indicating what license to include. Default: 'ccby'. Available options include: c("cc0", "ccby", "gpl", "gpl3", "agpl", "agpl3", "apache", "apl2", "lgpl", "mit", "proprietary", "None". For more information, see use_cc0_license . |
| use_renv | Logical, indicating whether or not to use 'renv' to make the project reproducible. Default: TRUE. See init . |
| use_targets | Logical, indicating whether or not to use 'targets' to create a Make-like pipeline. Default: FALSE See targets-package . |
| remote_repo | Character, URL of, or name for, the remote repository for this project. If a URL of an existing repository is specified, it should have the form <code>https://github.com[username][repo].git</code> (preferred) or <code>git@[...].git</code> (if using SSH). Alternatively, a name for a new repository can be provided. If a 'GitHub' user is authenticated on your device, |

this repository will be created on your account. Finally, a commit will be made containing the 'README.md' file, and will be pushed to the remote repository. Default: 'https', which results in no repository being created.

verbose Logical. Whether or not to print messages to the console during project creation. Default: TRUE

... Additional arguments passed to and from functions.

Value

No return value. This function is called for its side effects.

Examples

```
the_test <- "worcs_template"
old_wd <- getwd()
dir.create(file.path(tempdir(), the_test))
do.call(git_user, worcs:::get_user())
worcs_project(file.path(tempdir(), the_test, "worcs_project"),
              manuscript = "github_document",
              preregistration = "None",
              add_license = "None",
              use_renv = FALSE,
              remote_repo = "https")
setwd(old_wd)
unlink(file.path(tempdir(), the_test))
```

worcs_root

Return Absolute File Path of WORCS Project Directory

Description

The search starts at path, and recursively proceeds up the directory hierarchy until a worcs project directory is found.

Usage

```
worcs_root(path = ".")
```

Arguments

path Start directory, Default: '.' (current directory).

Value

Normalized path of the worcs project root directory.

See Also

[find_root](#)

Examples

```
if(requireNamespace("withr", quietly = TRUE)){  
  withr::with_tempdir({  
    writeLines("", ".worcs")  
    worcs_root()  
  })  
}
```

Index

* datasets

- worcs_checklist, 41

- add_endpoint, 3, 9, 13, 22, 28, 35, 37
- add_license_file, 4
- add_manuscript, 5, 43
- add_preregistration, 7, 43
- add_recipe, 8
- add_synthetic, 9
- add_targets, 11
- add_testthat, 3, 11

- check_dependencies
 - (check_worcs_installation), 14
- check_endpoints, 4, 9, 12, 22, 35, 37
- check_git (check_worcs_installation), 14
- check_github
 - (check_worcs_installation), 14
- check_renv (check_worcs_installation), 14
- check_renv_synchronized
 - (check_worcs_installation), 14
- check_rmarkdown
 - (check_worcs_installation), 14
- check_ssh (check_worcs_installation), 14
- check_tinytex
 - (check_worcs_installation), 14
- check_worcs, 13
- check_worcs_installation, 14
- cite_all, 15
- cite_essential, 16
- closed_data, 17, 19, 28, 31

- data_label, 18
- data_unlabel, 19
- descriptives, 20
- digest, 3

- export_project, 20

- file.edit, 29, 30

- file.path, 42
- find_root, 44

- gh_whoami, 24
- git_add, 25
- git_commit, 25
- git_config_global_set, 26
- git_fetch, 24
- git_ignore, 22
- git_push, 25
- git_release_publish, 23
- git_remote, 24
- git_remote_connect, 23
- git_remote_create, 24
- git_signature_default, 27
- git_update, 25
- git_user, 26
- github_action_check_endpoints, 21
- github_action_reproduce
 - (github_action_check_endpoints), 21
- github_action_testthat
 - (github_action_check_endpoints), 21
- github_document, 6, 17, 33, 43

- has_git_user, 26, 27

- init, 43

- licenses, 4
- list, 29
- list_endpoints, 27
- load, 29
- load_data, 28
- load_entrypoint, 29

- make_codebook, 30

- notify_synthetic, 31

open_data, [19](#), [28](#), [33](#)

prereg, [8](#), [43](#)

ranger, [38](#), [39](#)

remove_endpoint, [34](#)

render, [15](#), [16](#), [30](#)

reproduce, [35](#)

rticles, [5](#), [43](#)

skew_kurtosis, [36](#)

snapshot_endpoints, [4](#), [9](#), [13](#), [28](#), [35](#), [37](#)

synthetic, [17](#), [31](#), [38](#)

test_worcs (add_testthat), [11](#)

use_cc0_license, [43](#)

use_github_action, [22](#)

use_testthat, [11](#)

worcs_badge, [40](#), [42](#)

worcs_checklist, [13](#), [40](#), [41](#)

worcs_path, [42](#)

worcs_project, [43](#)

worcs_root, [42](#), [44](#)

write.csv, [17](#), [33](#)